

Altair Access Web 2019.1

# Administrator's Guide



PBS Works is a brand of  Altair

## Intellectual Property Rights Notice: Copyrights, Trademarks, Trade Secrets, Patents and Third Party Software Licenses

Updated: April 25, 2019.

### Altair® PBS Works® v.2019.1

Accelerating Innovation in the Cloud™

Copyright© 1994-2019 Altair Engineering Inc. All Rights Reserved.

Special Notice: Pre-release versions of Altair software are provided 'as is', without warranty of any kind. Usage of pre-release versions is strictly limited to non-production purposes.

### PBS Works - Accelerating Innovation in the Cloud™

Altair PBS Professional™ ©1994-2019

Altair Control™ © 2008-2019; (formerly PBS Control)

Altair Access™ © 2008- 2019; (formerly PBS Access)

Altair Accelerator™ © 1995- 2019; (formerly NetworkComputer)

Altair Accelerator Plus™ © 1995- 2019; (formerly WorkloadXelerator)

Altair FlowTracer™ © 1995- 2019; (formerly FlowTracer)

Altair Allocator™ © 1995- 2019; (formerly LicenseAllocator)

Altair Monitor™ © 1995- 2019; (formerly LicenseMonitor)

Altair Hero™ © 1995- 2019; (formerly HERO)

Altair Software Asset Optimization™ (SAO) © 2007- 2019

#### Note:

Compute Manager™ ©2012-2017 is now part of Altair Access

Display Manager™ ©2013-2017 is now part of Altair Access

PBS Application Services™ ©2008-2017 is now part of Altair Access

PBS Analytics™ ©2008-2017 is now part of Altair Control

PBS Desktop™ ©2008-2012 is now part of Altair Access, specifically Altair Access desktop, which also has Altair Access web and Altair Access mobile

e-Compute™ ©2000-2010 was replaced by "Compute Manager" which is now Altair Access

### Altair HyperWorks - A Platform for Innovation®

Altair AcuConsole™ ©2006-2019

Altair AcuSolve™ ©1997-2019

Altair ElectroFlo™ ©1992-2019

Altair ESAComp™ ©1992-2019

Altair Feko™ ©1999-2014 Altair Development S.A. (Pty) Ltd.; ©2014-2019 Altair Engineering Inc.

Altair Flux™ ©1983-2019

Altair FluxMotor™ ©2017-2019

Altair HyperCrash™ ©2001-2019

Altair HyperGraph™ ©1995-2019  
Altair HyperMesh™ ©1990-2019  
Altair HyperStudy™ ©1999-2019  
Altair HyperView™ ©1999-2019  
Altair Virtual Wind Tunnel™ ©2012-2019  
Altair HyperXtrude™ ©1999-2019  
Altair MotionSolve™ ©2002-2019  
Altair MotionView™ ©1993-2019  
Altair Multiscale Designer™ ©2011-2019  
Altair OptiStruct™ ©1996-2019  
Altair Radioss™ ©1986-2019  
Altair SimLab™ ©2004-2019  
Altair SimSolid™ ©2015-2019  
Altair nanoFluidX™ © 2013-2018 Fluidyna GmbH, © 2018-2019 Altair Engineering Inc.  
Altair ultraFluidX™ © 2010-2018 Fluidyna GmbH, © 2018-2019 Altair Engineering Inc.  
Altair WinProp™ ©2000-2019  
Altair ConnectMe™ ©2014-2019  
*Plus other products from the Altair solidThinking Platform.*

#### **Altair Packaged Solution Offerings (PSOs)**

Altair Automated Reporting Director ©2008-2019  
Altair GeoMechanics Director ©2011-2019  
Altair Impact Simulation Director ©2010-2019  
Altair Model Mesher Director ©2010-2019  
Altair NVH Director ©2010-2019  
Altair Squeak and Rattle Director ©2012-2019  
Altair Virtual Gauge Director ©2012-2019  
Altair Weight Analytics ©2013-2019  
Altair Weld Certification Director ©2014-2019  
Altair Multi-Disciplinary Optimization Director ©2012-2019

#### **solidThinking - Where Innovation Begins™**

Altair Inspire™ ©2009-2019 including Altair Inspire Motion and Altair Inspire Structures  
Altair Inspire™ Extrude-Metal ©1996-2019 (formerly Click2Extrude®-Metal)  
Altair Inspire™ Extrude-Polymer ©1996-2019 (formerly Click2Extrude®-Polymer)  
Altair Inspire™ Cast ©2011-2019 (formerly Click2Cast®)  
Altair Inspire™ Form ©1998-2019 (formerly Click2Form®)  
Altair Inspire™ Mold ©2009-2019  
Altair Inspire™ Studio ©1993-2019 (formerly 'Evolve')  
Altair Compose™ ©2007-2019 (formerly solidThinking Compose®)  
Altair Activate™ ©1989-2019 (formerly solidThinking Activate®)  
Altair Embed™ ©1989-2019 (formerly solidThinking Embed®)

- Altair Embed SE ©1989-2019 (formerly solidThinking Embed® SE)
  - Altair Embed/Digital Power Designer ©2012-2019
- Altair SimLab™ ©2004-2019  
Altair 365™ ©1994-2019

**Altair SmartWorks™ - Innovation Intelligence®**

Altair SmartCore™ ©2011-2019  
Altair SmartEdge™ ©2010-2019  
Altair SmartSight™ ©2014-2019

Altair intellectual property rights are protected under U.S. and international laws and treaties. Additionally, Altair software is protected under patent #6,859,792 and other patents pending. All other marks are the property of their respective owners.

ALTAIR ENGINEERING INC. Proprietary and Confidential. Contains Trade Secret Information.

Not for use or disclosure outside of Altair and its licensed clients. Information contained in Altair software shall not be decompiled, disassembled, “unlocked”, reverse translated, reverse engineered, or publicly displayed or publicly performed in any manner. Usage of the software is only as explicitly permitted in the end user software license agreement. Copyright notice does not imply publication.

[Third party software licenses](#)

AcuConsole contains material licensed from Intelligent Light ([www.ilight.com](http://www.ilight.com)) and used by permission.

**Software Security Measures:**

Altair Engineering Inc. and its subsidiaries and affiliates reserve the right to embed software security mechanisms in the Software for the purpose of detecting the installation and/or use of illegal copies of the Software. The Software may collect and transmit non-proprietary data about those illegal copies. Data collected will not include any customer data created by or used in connection with the Software and will not be provided to any third party, except as may be required by law or legal process or to enforce our rights with respect to the use of any illegal copies of the Software. By using the Software, each user consents to such detection and collection of data, as well as its transmission and use if an illegal copy of the Software is detected. No steps may be taken to avoid or detect the purpose of any such security mechanisms.

## Technical Support

Location	Telephone	e-mail
Australia	+1 800 174 396	anz-pbssupport@india.altair.com
China	+86 21 6117 1666	es@altair.com.cn
France	+33 (0)1 4133 0992	pbssupport@europe.altair.com
Germany	+49 (0)7031 6208 22	pbssupport@europe.altair.com
India	+91 80 66 29 4500 +1 800 425 0234 (Toll Free)	pbs-support@india.altair.com
Italy	+39 800 905595	pbssupport@europe.altair.com
Japan	+81 3 6225 5821	pbs@altairjp.co.jp
Korea	+82 70 4050 9200	support@altair.co.kr
Malaysia	+91 80 66 29 4500 +1 800 425 0234 (Toll Free)	pbs-support@india.altair.com
North America	+1 248 614 2425	pbssupport@altair.com
Russia	+49 7031 6208 22	pbssupport@europe.altair.com
Scandinavia	+46 (0) 46 460 2828	pbssupport@europe.altair.com
Singapore	+91 80 66 29 4500 +1 800 425 0234 (Toll Free)	pbs-support@india.altair.com
South Africa	+27 21 831 1500	pbssupport@europe.altair.com
South America	+55 11 3884 0414	br_support@altair.com
United Kingdom	+44 (0)1926 468 600	pbssupport@europe.altair.com

This document is proprietary information of Altair Engineering, Inc.

# Contents

<b>1 What's New</b>	5
<b>2 Get Started</b>	6
2.1 PBS Application Services	7
2.2 Document Conventions	8
2.3 System Requirements	9
2.3.1 System Requirements for Access Web	9
2.4 Hardware Requirements	10
2.5 Ports Used by Access Web	12
2.6 Memory used by Services in Access Web	14
2.7 Supported Product Configurations	15
2.8 Prerequisites for Installation	16
2.8.1 Prerequisites for Installing Access Web	16
2.8.2 Prerequisites for Installing Remote Session Components	17
2.9 Roles in Access Web	20
<b>3 Install Access Web and the Remote Session Component</b>	21
3.1 Install Access Web	22
3.2 Install Remote Session Components	24
3.2.1 Install the Remote Session Component on the PBS Professional Server and on PAS	24
3.2.2 Install the Remote Session Component on the PBS MoMs	26
3.2.3 Install the Interactive Proxy on the Access Web Server	28
<b>4 Configure Access Web After Installation</b>	29
4.1 Copy Application Definitions and Site Configuration File	30
4.2 Configure the License Server	31
4.3 Log into Access Web	32
4.4 Add a Service Cluster	33
4.5 Onboard an Application Definition	36
4.5.1 Integrate Right Click Context Menu of Access Web	36
4.5.2 Master File Analyzer	39
<b>5 Upgrade and Downgrade Access Web</b>	40
5.1 Upgrade Access Web	41
5.2 Downgrade Access Web	42

<b>6 Uninstall Access Web and Remote Session Component</b>	43
6.1 Uninstall Access Web	44
6.2 Uninstall Remote Session	45
6.2.1 Unconfigure PBS Professional and PBS Application Services	45
6.2.2 Uninstall Remote Session Components	46
<b>7 Access Web Service Commands</b>	47
<b>8 Manage Service Clusters</b>	48
8.1 Add a Service Cluster	49
8.2 Edit a Service Cluster	52
8.3 Delete a Service Cluster	54
<b>9 Advanced Configurations</b>	55
9.1 Configure the Access Web Component	56
9.1.1 Change Port Numbers	56
9.1.2 Change Memory used by the Services	64
9.1.3 Set the Double-Click Delay Time	68
9.1.4 Change the Database Password	68
9.1.5 Configure Default File Viewer	69
9.1.6 Configure Default Columns in Job List View	70
9.1.7 Change the Maximum File Upload Size	70
9.1.8 Change the File Opening behavior of a Remote Session Application	71
9.1.9 Configure Notifications for a Job State Change	71
9.1.10 Disable to View all Jobs	73
9.1.11 Add a Generic Action for a PAS server	73
9.1.12 Map a File Extensions to an Icon	78
9.1.13 Set Maximum Page Size for Files	79
9.1.14 Install and Configure SSL Certificate	79
9.1.15 Enable Mobile Notification Service	80
9.2 Configure PBS Application Services	81
9.2.1 Enable PBS Job History	81
9.2.2 Verify the Installation of PBS Application Services	81
9.2.3 Configure System Zip Utility	82
9.2.4 Configure System Unzip Utility	82
9.2.5 Configurable Parameters	83
9.2.6 Configure PBS Resources	87
9.2.7 Configure PAS Server Logging Behavior	87
9.2.8 Configure JVM Performance	94
9.3 Configure the Remote Session Component	95
9.3.1 Change the Session Timeout Value for Interactive Applications	95

9.3.2	Change the Job Submission Host for Interactive Applications.....	95
9.3.3	Change the Job Submission Port for Interactive Applications.....	96
9.3.4	Configure GPU Limits when the Number of GPUs Change.....	96
9.4	Configure Results Visualization Service.....	99
9.4.1	Configure HyperWorks Location.....	99
9.4.2	Configure HyperWorks Licenses.....	99
9.4.3	Configure Solver File Readers.....	100
9.4.4	Supported Result File Types.....	102
9.4.5	Configure Data Directory.....	107
9.4.6	Set a Data Cleanup.....	107
9.4.7	Configure RVS Parameters.....	108
9.5	Access Web Windows Setup.....	111
9.5.1	PAS Setup.....	111
9.5.2	Access Web and Docker Setup.....	112
9.5.3	Remote Session Windows Setup.....	113
9.6	Running Job Operations in Windows.....	115
9.6.1	Configuration in Windows for Faster Running Job Operations.....	115
9.6.2	Configuration in Linux for Faster Running Job Operations.....	116

## **10 Application Definitions.....118**

10.1	Application Definition Components.....	119
10.1.1	Application Input File.....	119
10.1.2	Application Converter File (HPCBP Converter).....	119
10.1.3	Application Runtime Scripts.....	119
10.1.4	Site Configuration File.....	120
10.1.5	Server Configuration File.....	120
10.2	Sample Application Definition ShellScript.....	121
10.3	Map Icons to an Application.....	122
10.4	Define a Category in Application Definition.....	123
10.5	Administration of Application Definition.....	125
10.5.1	Add a New Application Definitions.....	125
10.5.2	Application Definition Validation.....	125
10.5.3	Maintenance of Existing Application Definition.....	126
10.6	Sitewide Settings.....	127
10.6.1	Site Configuration File Content.....	127
10.6.2	Initial Site Configuration File after Installation of PAS.....	127
10.6.3	Sample of a Site Configuration File.....	128
10.6.4	Use Site Configuration Information in an Application Definition.....	129
10.6.5	Site Configuration File Backup.....	129
10.6.6	Site Configuration File Validation.....	129
10.7	Interactive Application Definitions.....	130
10.7.1	Mandatory Interactive Application Definitions Changes.....	130
10.7.2	Special Interactive Application Arguments.....	130
10.7.3	Add a New Interactive Application.....	132



<b>11 Establish Access Controls</b>	135
11.1 Managing Roles	136
11.1.1 Default Roles and Resources	136
11.1.2 Add a New Role	136
11.1.3 Change the Resources of a Role	137
11.1.4 Change the Name of a Role	137
11.1.5 Delete a Role	137
11.2 Managing Users	139
11.2.1 Add a User	139
11.2.2 Assign a Role to a User	139
11.2.3 Remove a Role from a User	139
11.2.4 Change the User Name	140
11.2.5 Delete a User	140
<b>12 Log Files</b>	141
12.1 PAS Log File	142
12.2 Other Log Files	143
<b>13 Troubleshoot Access Web</b>	144
13.1 Run the Access Web Diagnosis Script	145
13.2 Troubleshoot PBS Application Services	146
13.2.1 Verify PAS Status	146
13.2.2 Troubleshoot PAS Job Submission Issues	147
13.2.3 Troubleshoot Error Messages during Installation	148
13.3 Troubleshoot Remote Session Components	151
13.3.1 Run the Remote Session Diagnosis Script	151
13.3.2 Remote Session Checklist	152
13.3.3 Display Session is shown but not the Application that was Started	153
13.3.4 Application Definition working in VirtualGL Environment Issue	154
13.3.5 Desktop Manager not Displaying	154
13.3.6 Graphic Card Compatibility Issues	155
13.4 Troubleshoot Results Visualization Service	157
13.4.1 Troubleshoot Checklist	157
13.4.2 Locate Log Files	157
13.4.3 Common Issues	158

Latest features available with Altair Access™ Web.

## Job Submission Wizard

New enhanced job submission wizard allows you to submit a job by selecting an application and the saved profiles.

## New Profile Management

Create and manage profiles using the Job Submission wizard, so that you can submit multiple jobs to the same application with the same arguments, thereby streamlining job submission.

## Inline Progress of Job Input File

An inline progress bar is displayed while uploading an input file in the Job Submission form.

## Using Plot Templates

You can now save a plot as a template file (.rvst). You can apply the template to a valid result file to generate a plot.

## Access Control

Access Web provides a workflow for creating roles, creating users and assigning user to roles to restrict access to the various features. Refer to [Establish Access Controls](#) for more information.

## Screen shots of Remote Session

Remote desktop screen shots can be copied to the clipboard. You can use the browser context menu to copy the image to clipboard or you can download the modal.

## Copy Text to Remote Session

Now you can copy text from your local machine to remote sessions and from remote sessions to your local machine.

## Windows Support



**Note:** This is Beta version in this release.

Using Docker, you can load Access Web, install PAS, and install Remote Session in Windows. Refer to [Access Web Windows Setup](#) for more information.

## Running Job Operations in Windows

Earlier the operations executed on a running job used to be slow while interacting with the Access Web. In this release, Access Web uses messaging-based infrastructure which makes these operations run faster on a running job. Refer to [Running Job Operations in Windows](#) for more information.

Use Access Web to submit jobs to a Workload Manager.

This chapter covers the following:

- [2.1 PBS Application Services](#) (p. 7)
- [2.2 Document Conventions](#) (p. 8)
- [2.3 System Requirements](#) (p. 9)
- [2.4 Hardware Requirements](#) (p. 10)
- [2.5 Ports Used by Access Web](#) (p. 12)
- [2.6 Memory used by Services in Access Web](#) (p. 14)
- [2.7 Supported Product Configurations](#) (p. 15)
- [2.8 Prerequisites for Installation](#) (p. 16)
- [2.9 Roles in Access Web](#) (p. 20)

Altair's new Access Web provides a simple, powerful, and consistent interface for submitting and monitoring jobs on remote clusters, clouds, or other resources. Engineers and researchers can now focus on core activities and spend less time learning how to run applications or moving data around. The Access Web remote visualization and collaboration capabilities bring access to an expensive, highend 3D visualization datacenter hardware right to the user. Access Web provides an ability to visualize the results by extracting plot and animation data. You can view plots for running jobs as well as for jobs which have been successfully completed. You can download and analyze animations using the Altair HyperView Player. Results Visualization Service allows you to compare two or more plots in the result viewer, save the plot you generated with the data as .rvs file and directly view your saved plots with the selected data.

## Access Web Features:

- **Novice to Expert:** simple and powerful
- **Same UX:** desktop and web
- **Secure:** protected access to HPC resources
- **End-to-end:** submit, monitor progress, steer, fix, and rerun jobs
- **Collaborate:** shared 3D analysis
- **3D Remote Visualization**
- **Save time:** Simplify job submission and management thanks to a powerful GUI with smart, simplified interfaces
- **Be more productive:** Spend more time focused on work and not IT tasks - for example, monitor jobs graphically without having to download huge job files
- **Increase ROI:** Consolidate access to applications and optimize license availability
- **Reduce errors and improve consistency:** Embed your company's best-practice "know how" directly into Application Definitions used for job submission

## 2.1 PBS Application Services

PBS Application Services (PAS) allows users to quickly create application portals that boost productivity and accelerate innovation.

Today, doing more with less is simply business as usual. Enterprises and institutions are placing higher demands upon their high performance computing infrastructure – larger and more complex applications and dynamic end-user work loads. Optimizing end-user productivity and getting the most from limited resources and complex application work loads can seem to be an impossible challenge.

PAS is a middleware component that communicates with the PBS Professional complex and the operating system, and provides services for the front end client applications such as graphical user interfaces. This middleware component is used as the preferred method of communication between the integration of client applications and the PBS Professional complex. PAS allows users to quickly create application portals that boost productivity and accelerate innovation. Application administrators can use PAS to create custom, solver specific application definitions. Leveraging key industry standards like the Open Grid Forum High Performance Computing Basic Profile, PAS makes it easy to respond to dynamic changes to your users and applications.

Benefits of PBS Application Services:

- Stable WS-based application programming interface (API) for integration into bigger systems
- Streamlined APIs for integration of applications into PBS Professional for the independent software vendors
- Front end graphical user interface application building is made easier
- Independent software vendors and the community can define new application definitions and exchange them within the PBS Professional complex in a turn-key fashion
- Platform neutrality allowing PBS Application Services to run on Linux platforms
- Customized application definition files can be shared across all supported platforms
- Transactional manner of operations (e.g. eliminates out of sync issues with resources not included in scheduling, etc.)
- Grid-friendly as it uses the same extensible markup language/web services (XML/WS) as large-scale grid solutions
- Easier integration into Enterprise SOA and business process management
- Standards-based implementation using Web Services, WS-Security, high performance computing basic profile (HPCBP)

PBS Application Services provides the following major groups of functionality:

- Installation and management of application definitions by administrators
- Site configuration such as billing accounts and MPROC by administrators
- User submission and management of PBS Professional jobs
- File operations services

## 2.2 Document Conventions

Common typographical conventions for Access Web technical publications.

### *PA\_HOME*

The Access Web home directory which contains configuration, data, and logging files. Default location is `/var/spool/pbsworks/2019.1/access/home`, however this can be overridden during the installation of Access Web.

### *PA\_EXEC*

The Access Web execution directory which contains binaries and scripts. Default location is `/opt/altair/pbsworks/2019.1/access/exec`, however this can be overridden during the installation of Access Web.

### *PBS\_HOME*

The PBS Professional home directory which contains configuration and logging files. Default location is `/var/spool/pbs`, however this can be overridden during the installation of PBS Professional.

### *PBS\_EXEC*

The PBS Professional execution directory which contains binaries and scripts. Default location is `/opt/pbs`, however this can be overridden during the installation of PBS Professional.

## 2.3 System Requirements

Supported platforms, browsers, and hardware requirements for Access Web and for running an interactive application.

### 2.3.1 System Requirements for Access Web

Supported platforms and browsers for Access Web.

#### Supported Platforms

Access Web is supported on the following Linux 64-bit platforms:

- Red Hat Enterprise Linux 7.1 to 7.6
- Cent OS 7.1 to 7.6
- SLES 12 SP1 to 12 SP3

#### Supported Server Platforms

Access Web supports only the 64-bit (x86\_64) architecture platforms for visualization of results.

#### Supported Browsers

Access Web is supported on the following browsers:

##### Windows

- Firefox latest ESR (Only Extended Support Release is supported. Please refer to <https://www.mozilla.org/en-US/firefox/organizations/>)
- Google Chrome latest
- Microsoft Internet Explorer 11
- Microsoft Edge (limited testing)

##### Linux

- Not supported at this time.

##### OSX

- Firefox latest ESR (Only Extended Support Release is supported. Please refer to <https://www.mozilla.org/en-US/firefox/organizations/>)
- Google Chrome latest
- Safari Latest

## 2.4 Hardware Requirements

Minimum and recommended hardware requirements necessary to install and run Access Web.

### Hardware Requirements for Access Web


Minimum hardware configuration required for Access Web are:

Hardware	Minimum Requirement	Recommended
CPU	2 CPU cores with a minimum speed of 2.5 GHz	4 CPU cores with a minimum speed of 2.5 GHz
Memory (Physical)	4 GB	8 GB
Disk Space	4 GB	10 GB


### Hardware Requirements for Results Visualization Service

Minimum hardware configuration required for Results Visualization Service (RVS) are:

Hardware	Minimum Requirement	Recommended
CPU	A Quad Core Processor of 2.5 GHz	A Quad Core Processor of 3.1 GHz
Memory (Physical)	16 GB	32 GB
Disk Space	500 GB	500 GB

 **Note:** Result Visualization of results requires good network connectivity to all the connected file servers such as PAS server and job execution hosts. A minimum speed of 100mbps is required while a speed of 1gbps is recommended.

You can install Access Web and HyperWorks Desktop software separately. The HyperWorks Desktop path can be made accessible from Access Web by creating a mounting point for the HyperWorks installed directory on Access Web installed machine.

 **Tip:** For a better performance of RVS, mount the stage directory and scratch directory on the Access Web installed machine if Access Web and PAS are installed separately.

### Hardware Requirements for Remote Session Component

Hardware configuration required for Remote Session component are:

*Graphics*

Supported only on Nvidia and ATI(AMD) graphics cards.

*GPU Cores and Memory*

Specific to the interactive applications being run.

*CPU Cores and Physical Memory*

Specific to the interactive applications being run.

Also, refer to [Prerequisites for Installing Remote Session Components](#).



## 2.5 Ports Used by Access Web

A list of ports used by Access Web services and components.

The Access Web installer has the auto-port detection logic in place and ports will be picked up by each service within the specified range.

If the required port is not available during the installation, then Access Web will increment the port number and try again. This will continue until a free port is found, or until 100 consecutive ports are refused at which point the installer will ask for a port.

Below is a table of all ports and the port range used by Access Web.

Table 1: Ports Used by Access Web

Port	Port Range	Service Using the Port
4222	4222 (no port range)	NATS Message Broker Port
4443	4443 - 4542	Gateway
4543	4543 - 4642	Access Web Server
4643	4643 - 4742	Postgres Database
4743	4743 - 4842	Message Broker (ActiveMQ)
4843	4843 - 4942	Remote Session Services Webserver
4943	4943 - 5042	Remote Session Services Job Update
5043	5043 - 5142	Result Manager Services
5143	5143 - 5242	Result Core Services
5243	5243 - 5342	PBS Application Services
5343	5343 - 5442	Job Profiles Services
5443	5443 - 5542	Remote Session Services Proxy
5543	5543 - 5642	AMS Services
5643	5643 - 5742	Mobile Notification Service
5901	5901 to 59XX	Turbo VNC Server Port for Remote Session



**Note:** It is recommended to have firewall on installation node and block all Access Web ports from outside world except Gateway port (4443) and Remote Session Services Job Update port (4943).

### See Also

[Change Port Numbers](#)

## 2.6 Memory used by Services in Access Web

A list of services with its configuration path and value used by Access Web.

The Access Web memory settings for each of the services used are as follows:


 **Note:** You can add the following line in the configuration file if the memory value is found:  
`JAVA_OPTS="$JAVA_OPTS -Xmx512M"`

Table 2: Service with its configuration path and value used by Access Web

Service	Configuration Path and File	Value
Gateway	PA_HOME/config/api_gateway/nginx.conf	"-Xmx512m"
Access Web Server	PA_EXEC/pa/scripts/setenv.sh	"-Xmx512m"
Message Broker (ActiveMQ)	PA_EXEC/shared/thirdparty/apache/activemq/bin/env	"-Xms64M -Xmx512M"
Remote Session Services Webserver	PA_EXEC/displaymanager/scripts/setenv.sh	"-Xmx512m"
Result Manager Services	PA_EXEC/resultmanager/scripts/setenv.sh	"-Xmx512m"
Result Core Services	PA_EXEC/resultservice/scripts/setenv.sh	"-Xmx512m"
Job Profiles Services	PA_EXEC/jobprofiles/scripts/setenv.sh	"-Xmx512m"
AMS Services	PA_EXEC/ams/scripts/setenv.sh	"-Xmx512m"
Mobile Notification Service	PA_EXEC/mobile_notification_service/scripts/setenv.sh	"-Xmx512m"
Executor	PA_EXEC/executor/scripts/setenv.sh	"-Xmx512m"

### See Also

[Change Memory used by the Services](#)


## 2.7 Supported Product Configurations

Supported product configurations for using Access Web in Linux and in Windows.

### Linux Support

The currently supported Access Web product configurations for Linux are:

Access Web	PAS	PBS Professional	Hyperworks
2019.1	2019.1	19.1.1(OSS) 18.2.3 18.2.2 18.1.1(OSS)	14.0 2017.2

 **Note:** HyperWorks Desktop application is required to visualize CAE results. Access Web is tested in Hyperworks 2017.2

### Windows Support

The currently supported Access Web product configurations for Windows Server 2016 are:

Access Web	PAS	PBS Professional	Hyperworks
2019.1	2019.1	19.1.1(OSS) 18.2.3	14.0 2017.2

## 2.8 Prerequisites for Installation

Prerequisites and planning for installing Access Web, PBS Application Services, Remote Session Components, and for Enabling Visualization of CAE Results.

### 2.8.1 Prerequisites for Installing Access Web

Mandatory requirements for PBS Professional and the Service User.

#### Service User

The Service User is provided by the administrator during installation and it should be pre-existing in the system. This user will own Access Web services and the files in PA\_HOME and PA\_EXEC. The default user is "pbsworks" for installing Access Web.

#### Time Synchronization

Administrator must make sure that there is a time synchronization enabled between machines on which Altair Access and HPC cluster installed. In lack of proper time synchronization functionalities like getting job updates, files update times etc. of Access will not work correctly.

#### PBS Professional

Ensure that a supported version of PBS Professional is installed on the HPC cluster.

#### PAS

To take full advantage of all the new features available with Access Web, the cluster must be updated to the latest version of PAS.

#### PBS Application Services Staging Directory

During the installation of the PAS Server, you will be prompted to enter a value for the PAS staging directory. The staging directory is where the necessary job files are transferred after job submission via a client, for example Access Web, for transfer to PBS Professional for execution.

The default location of the staging directory is: /stage

However, you have the option to choose a custom stage directory during installation.

Following are considerations for selecting and creating the staging directory:

- The stage area can grow quite large, depending on the size of the average job. Give careful consideration to the disk usage and disk capacity.
- The pathname for the staging directory should not contain spaces.
- PAS implements an automatic staging directory cleanup such that any data in the staging directory that is not generated by PAS is at risk of being purged without notice. It is recommended to select a staging directory where only PAS data files will be stored. Use of a directory that contains important data is not recommended. The automatic staging directory cleanup does not delete any files in the user's home directory. When the staging directory is set to \$USER\_HOME (for

example: `$USER_HOME/stage`), the files in that directory are not automatically cleaned up and the responsibility for maintaining the staging directory falls on the individual user.

## Altair HyperWorks Desktop

To use the results visualization features of Access Web to extract and plot animation data, a supported version of Altair HyperWorks Desktop must be installed on the HPC cluster. If HyperWorks Desktop is not installed, only plotting of CSV files is supported.

**Tip:** Verify the license features HV Trans and HMathserv validation details before installing the software.

The HyperWorks Desktop installation should not be in `/root` or any user's home directory and in a location where all users have read and write permission.

Install "`libXScrnSaver-1.2.2-6.1.el7.x86_64`" package for HMathserv to run after installing the HyperWorks Desktop software.

**Tip:** Install HyperWorks Desktop by following the Linux installation instructions in the HyperWorks 2017 Installation Guide.

## 2.8.2 Prerequisites for Installing Remote Session Components

Mandatory requirements for Remote Session components.

### Access Web

Access Web must be installed prior to installing the Remote Session components.

### Host Name and Port

It is recommended to configure hostname resolution, so that the PBS MoMs can connect to the Access Web server using its hostname rather than IP address and the configured Remote Session Service Job Update port.

The Remote Session Proxy should be able to connect to interactive execution node through hostname and Turbo VNC Port.

Refer to *Ports Used by Access Web* topic for more information on ports.

### Prerequisites for Installing on the PBS MoM

- Install the 3D adapter drivers provided by the manufacturer.
- Full 3D acceleration or Pixel Buffer support should be enabled by the Linux drivers.
- For running interactive sessions, X Server and application on local display must be configured and working.
- X Server must be configured to export True Color(24bit or 32bit) visuals.

- Use Virtual Private Networking or secured channels for communication between clients and interactive server if encryption is required.
- The PBS Professional execution host must be able to access and run the applications available through Access Web.
- For the Access Web Remote Session installer to set the custom resource at each execution host. Follow the below steps:

- The root user of all execution hosts must be granted operator access. Prior to starting the Remote Session installer, issue the following command to grant this access:

```
qmgr: s s operators+=root@*
```

- If root operator permission is set, number of ngpus available will be set by the remote session installer while installing agent.
- After installing the Remote Session components, you can remove the root user of the PBS MOMs from the operators list on the PBS server using the command:

```
qmgr: s s operators-=root@*
```

- If this access is not granted, then you will manually have to set the custom resource by issuing a `qmgr set` command for each execution host after installation of Remote Session. For example:

```
set node <node> resources_available.ngpus = 4
```



**Warning:** Restricting it to a specific subdomain still allows anyone running Linux on the subdomain access to the PBS Server.

## Prerequisite Resource Libraries for Interactive Application

The following libraries must be installed on the machine hosting the Access Web interactive proxy (these libraries do not need to be installed on the PBS Server or the PBS MoM) before attempting to install the Interactive Application component. Use the appropriate system tool (e.g. RPM, YUM, YAST etc.) to install them.

- |                                  |                                       |
|----------------------------------|---------------------------------------|
| • libc.so.6()(64bit)             | • libpthread.so.0()(64bit)            |
| • libc.so.6(GLIBC_2.2.5)(64bit)  | • libpthread.so.0(GLIBC_2.2.5)(64bit) |
| • libc.so.6(GLIBC_2.3)(64bit)    | • libpthread.so.0(GLIBC_2.3.2)(64bit) |
| • libcrypt.so.1()(64bit)         | • libSM.so.6()(64bit)                 |
| • libdl.so.2()(64bit)            | • libX11.so.6()(64bit)                |
| • libdl.so.2(GLIBC_2.2.5)(64bit) | • libXaw.so.7()(64bit)                |
| • libGL.so.1()(64bit)            | • libXcursor.so.1()(64bit)            |
| • libGLU.so.1()(64bit)           | • libXext.so.6()(64bit)               |
| • libICE.so.6()(64bit)           | • libXmu.so.6()(64bit)                |
| • libm.so.6()(64bit)             | • libXt.so.6()(64bit)                 |
| • libm.so.6(GLIBC_2.2.5)(64bit)  | • libXv.so.1()(64bit)                 |

- libpam.so.0()(64bit)

- libz.so.1()(64bit)



## 2.9 Roles in Access Web

Roles defined in Access Web.

### **Service User**

The Service User is provided by the administrator during installation and it should be pre-existing in the system. This user will own Access Web services and the files in PA\_HOME and PA\_EXEC. The default user is "pbsworks" for installing Access Web.

### **Portal Administrator**

The first user to login to Access Web after installation is automatically designated as the portal administrator. The portal administrator is the only user who can add, edit, and delete service clusters and other users' access permissions to the application.

# Install Access Web and the Remote Session Component

3

Instructions for installing Access Web, PBS Application Services, and Remote Session components, so that interactive and non-interactive jobs can be submitted.

This chapter covers the following:

- [3.1 Install Access Web](#) (p. 22)
- [3.2 Install Remote Session Components](#) (p. 24)

## 3.1 Install Access Web

Install Access Web component, so that you can submit non-interactive jobs to the Workload Manager.

- Review [System Requirements of Access Web](#)
- Review [Prerequisites of Access Web](#)
- [Uninstall](#) previous versions of Access Web.

Ensure you having the following information before you start your installation:

- License server details
- HyperWorks location

A binary or executable needs to be downloaded or obtained using your usual Altair support channels.

The Access Web 2019.1 installer provides an option for installing Access Web, PBS Application Services, or both.

1. Login to the machine as root where you want to install Access Web.
2. Enter the command:  

```
./AltairAccessWeb_<Version>_<Build ID>_<YYYYMMDD>_<Timestamp>.bin -i console
```
3. Read the introduction and press **ENTER**.
4. Page through the license agreement by pressing **ENTER** until you are asked to accept its terms and conditions.
5. Accept the license agreement by entering **Y** and pressing **ENTER**.
6. Choose one of the following options:
  - Enter **1** and press **ENTER** to install Access Web Services.
  - Enter **2** and press **ENTER** to install PBS Application Services.
  - Enter **3** and press **ENTER** to install Access Web Services and PBS Application Services. This is the default option.



**Note:** The following steps will change based on your choice.

7. Enter the license server details and press **ENTER**.

The license server details should have the port and hostname in the format `port@hostname`. You can provide multiple license server details separated by a colon in Linux and semi-colon in Windows.



**Tip:** It is not mandatory to provide the license server at installation time. You will however be required to configure the license server information prior to logging into Access Web.

8. If you are installing PAS, enter a staging directory and press **ENTER**.

The staging directory is where user's job files will be staged prior to execution. This directory must exist prior to the installation of PAS.



**Tip:** The stage area can grow quite large depending on the size of the average job. It's not recommended the use `/tmp` or user's `/home` as the staging directory, as they will get periodically purge.

9. Enter the service user and press `ENTER`.



**Note:** The default service user is 'pbsworks' and the Access Web service is registered under this user.

10. Enter the location where the Access Web binaries are to be installed.

You may choose to install in the default location.

11. Enter the location where the Access Web configuration and logs files are to be installed.

You may choose to install in the default location.

12. Optional: If Access Web is being installed, enter the HyperWorks location for visualizing your results.

The Access Web 2019.1 supports HyperWorks 2017.2.0.16.

13. Review the installation summary and press `ENTER`.

The installation starts. It may take a few minutes for the installation to complete.

14. Start Access Web manually by entering the following command:

```
service pbsworks-pa start
```

15. Login to the machine hosting the PBS Server.

16. As a PBS Operator or Manager enter the following command:

```
qmgr -c 'set server job_history_enable=True'
```

If you want to run interactive jobs, you must now install the [Interactive Application component of Access Web](#).

## 3.2 Install Remote Session Components

Install components necessary to enable the remote session capabilities of Access Web.

Review the [system requirements](#) and [prerequisites](#) for installation.

A binary that installs the Remote Session components needs to be downloaded or obtained using your usual Altair support channels.

The installer will need to be run multiple times across several machines and must be performed in the following sequence:

1. Install the Remote Session component on the PBS Professional headnode and in the machine where PBS Application Services is installed. This installation will:
  - add a custom resource to PBS Professional called "ngpus"
  - creates an interactive queue called "iworkq"
  - add a new application definition "GlxSpheres" to PAS
  - restart PBS Professional and Access Web
2. Install the Remote Session component on all PBS MoMs on which you want to run interactive jobs.
3. Install proxy software necessary for running interactive applications on the machine hosting Access Web.

After installing the Remote Session component, view the value of the `jobsub.monitor.host` variable in the file `PA_HOME/config/displaymanager/dmrest.properties` to confirm the configured hostname. If there is no access through hostname, then a slight delay may occur while opening a remote session for the first time.

### 3.2.1 Install the Remote Session Component on the PBS Professional Server and on PAS

Install binaries and configure PBS Professional and PAS to support interactive applications.

Review the [system requirements](#) and [prerequisites](#) for installation.

Install the remote session component on the PBS Professional headnode and in the machine where PAS is installed.

This installation will:

- add a custom resource to PBS Professional called "ngpus"
- add an interactive queue called "iworkq"
- restart Access Web
- restart PBS Professional



**CAUTION:** It is advisable that you run the installer when critical jobs are not running.

1. Login to the machine as root where the PBS Professional Server and PAS is installed.
2. Enter the command:

```
./AltairRemoteSessionAgent_<Version>_<Build ID>_<YYYYMMDD>_<Timestamp>.bin -i  
console
```

3. Read the introduction and press `ENTER`.
4. Page through the license agreement by pressing `ENTER` until you are asked to accept its terms and conditions.
5. Accept the license agreement by entering `Y` and pressing `ENTER`.  
Four options are displayed.
6. Enter `1` to configure the PBS Professional and PAS servers and press `ENTER`.
7. PBS Professional and PAS is restarted during the installation process, choose whether you want to proceed:
  - Choose `No` to exit and run the installer at a more suitable time.
  - Choose `Yes` to run the installer.
8. Enter the number of GPUs that are available in the cluster and press `ENTER`.  
If you have a cluster with 10 execution hosts and only two of those execution hosts have associated GPUs, then add up the number of GPUs for both execution hosts and enter this number.
9. Review the installation summary and press `ENTER`.  
The installation starts. It may take a few minutes for the installation to complete.
10. Press `ENTER` to complete the installation process.

Verify that `iworkq` is created, a `GPU resource` is configured, and `GlxSpheres` is installed.

## Verifying the Existence of the Interactive Queue

Verify that a PBS Professional interactive queue has been created.

After running the interactive installer on the PBS Professional Server, a queue called "iworkq" should exist. All interactive jobs are submitted to this queue. The attribute `max_queued_res.ngpus` denotes the number of GPUs available in the cluster and should reflect the number entered during installation. Other attributes used internally by Access Web are `resource_max.ngpus` and `resource_min.ngpus`. These two attributes are always to set the value of "1".

Enter the command:

```
qmgr -c "p q iworkq"
```

Output similar to the following is displayed:

```
#  
# Create queues and set their attributes.  
#  
#  
# Create and define queue iworkq  
#  
create queue iworkq  
set queue iworkq queue_type = Execution  
set queue iworkq Priority = 150  
set queue iworkq max_queued_res.ngpus = [o:PBS_ALL=7]  
set queue iworkq resources_max.ngpus = 1  
set queue iworkq resources_min.ngpus = 1  
set queue iworkq resources_default.arch = linux  
set queue iworkq resources_default.place = free  
set queue iworkq default_chunk.mem = 512mb
```

```
set queue iworkq default_chunk.ncpus = 2
set queue iworkq enabled = True
set queue iworkq started = True
```

## Verifying the Existence of the Interactive Custom Resource

Verify that a new resources called ngpus has been added to PBS Professional.

After running the interactive installer on the PBS Professional headnode, a new custom resource called ngpus is added to PBS Professional. This resource is necessary to run interactive jobs. You can verify the existence of this custom resource by viewing the contents of the PBS Professional resource definition file and the scheduler's configuration file.

1. Navigate to the location `PBS_HOME/server_priv`
2. Enter the command:

```
grep -A3 "DM STATIC" resourcedef
```

The resource ngpus should be defined in this file.

```
# ***** BEGINNING OF DM STATIC RESOURCES SECTION.DO NOT EDIT BY HAND *****
ngpus type=long flag=nh
# ***** END OF DM STATIC RESOURCES SECTION.DO NOT EDIT BY HAND *****
```

3. Navigate to the location `PBS_HOME/sched_priv`
4. Enter the command:

```
grep ngpus sched_config
```

The resource ngpus should be displayed in the list of resources defined in this file.

```
resources: "ncpus, mem, arch, host, vnode, netwins, aoe, ngpus"
```

## Verifying the Installation of the Interactive Application Definition

Verify that a new application definition called GlxSpheres is installed.

1. Login to the machine hosting the PAS Server as root or a user with sudo permissions.
2. Navigate to the directory `PA_HOME/data/pas/targets/localhost/repository/applications`.
3. Verify that a new application definition has been placed in this location called GlxSpheres.

### 3.2.2 Install the Remote Session Component on the PBS MoMs

Install binaries and configure the PBS Mom to support interactive applications.

Review the [system requirements](#) and [prerequisites](#) for installation.

Install necessary components on the PBS MoM to support interactive applications, including TurboVNC and Virtual GL. The installer also configures a new resource called "ngpus".



**Note:** This installation process must be repeated for all execution hosts where you want to run interactive jobs.

1. Login to the machine as root where the PBS Professional MoM is installed.
2. Enter the command:  

```
./AltairRemoteSessionAgent_<Version>_<Build ID>_<YYYYMMDD>_<Timestamp>.bin -i console
```
3. If you are installing the PBS MoM interactive component on a machine hosting both the PBS Professional Server and the MoM you will see the below message, enter 1 and press **ENTER**.  

```
Manage Instances
-----
->1- Install a new instance
   2- Modify an existing instance
```
4. Read the introduction and press **ENTER**.
5. Page through the license agreement by pressing **ENTER** until you are asked to accept its terms and conditions.
6. Accept the license agreement by entering **Y** and pressing **ENTER**.  
Four options are displayed.
7. Enter 2 and press **ENTER**.
8. Enter the location where the binaries are to be installed and press **ENTER**.  
You may choose to install in the default location.
9. Enter the location where the configuration and logs files are to be installed and press **ENTER**.  
You may choose to install in the default location.
10. Enter the number of GPUs available on the execution host and press **ENTER**.
11. Review the installation summary and press **ENTER**.  
The installation starts. It may take a few minutes for the installation to complete.
12. Press **ENTER** to complete the installation process.  
The TurboVNC and Virtual GL is installed to support interactive applications by configuring X Server.
13. Restart the X Server.



**Warning:** Restarting the X Server might affect any running graphical applications. Please make sure that there are no critical graphical applications running.

Verify that "ngpus" resource has been added to the execution host by executing the command:

```
pbsnodes -av
```

The new resource should be listed and it should be assigned the value entered for the available GPUs entered during installation.

```
resources_available.ngpus = <NGPUS>
```



## 3.2.3 Install the Interactive Proxy on the Access Web Server

Install the Guacamole proxy server on the machine hosting Access Web to support interactive applications.

Review the [system requirements](#) and [prerequisites](#) for installation.

1. Login to the machine as root where Access Web is installed.
2. Enter the command:

```
./AltairRemoteSessionAgent_<Version>_<Build ID>_<YYYYMMDD>_<Timestamp>.bin -i  
console
```

3. If you are installing the Interactive Proxy server on a machine hosting either the PBS Professional Server or the MoM you will see the below message, enter 1 and press ENTER.

```
Manage Instances  
-----  
->1- Install a new instance  
   2- Modify an existing instance
```

4. Read the introduction and press ENTER.
5. Page through the license agreement by pressing ENTER until you are asked to accept its terms and conditions.
6. Accept the license agreement by entering Y and pressing ENTER.  
Four options are displayed.
7. Enter 4 and press ENTER.
8. Enter the location where the binaries are to be installed and press ENTER.  
You may choose to install in the default location.
9. Enter the location where the configuration and logs files are to be installed and press ENTER.  
You may choose to install in the default location.  
The installation starts. It may take a few minutes for the installation to complete.
10. Press ENTER to complete the installation process.

Verify that the Guacamole proxy daemon is installed and running by issuing the following command:

```
service guacd status
```

# Configure Access Web After Installation

## 4

Mandatory configuration steps that must be completed before Access Web can be started.

This chapter covers the following:

- [4.1 Copy Application Definitions and Site Configuration File](#) (p. 30)
- [4.2 Configure the License Server](#) (p. 31)
- [4.3 Log into Access Web](#) (p. 32)
- [4.4 Add a Service Cluster](#) (p. 33)
- [4.5 Onboard an Application Definition](#) (p. 36)

Before you start the Access Web service, you must copy over default application definitions provided by Altair and a corresponding PAS site configuration file.

## 4.1 Copy Application Definitions and Site Configuration File

Copy default application definitions and a PAS site configuration file.

Default application definitions and a site configuration file are provided to get you up and running quickly. Obtain them through your usual Altair support channels.

1. Login to the machine where PAS is installed.
2. Copy any default application definitions required for your site to the location: `PA_HOME/data/pas/targets/localhost/repository/applications`
3. Copy the default `site-config.xml` file to `PA_HOME/data/pas/targets/localhost/repository`
4. Edit the `site-config.xml` file.
5. For each application, update the value of the XML element `<Executable>` to the location of the application's executable.


```
<Application id="Abaqus">
  <ApplicationVersions>
    <ApplicationVersion>
      <Option>13.0</Option>
      <Executable>/opt/scripts/abaqus</Executable>
    </ApplicationVersion>
  </ApplicationVersions>
</Application>
```

6. Remove `time_stamp.txt` from `PA_HOME/data/pas/`

## 4.2 Configure the License Server

Configure the license server after Access Web installation in console mode.

During the installation Access Web, you are prompted to provide a license server in the format `port@hostname`. If this information is not provided at that time, then the license server must be configured post-installation.

 **Note:** You must have administrative privileges to configure the Access Web license server.

1. Login to the machine as root where Access Web is installed.
2. Open the file `app.properties` located at `PA_HOME/config/license/`
3. Change the value of `pbsworks.license.server` to the port and hostname of the license server in the format `port@hostname`.

```
Licensed application name
pbsworks.license.application=PBSAccess

#server location for license server
pbsworks.license.server=6200@cntrlicsrv03
```

4. Restart Access Web for these changes to take effect by entering the following command:


```
service pbsworks-pa restart
```

## 4.3 Log into Access Web

Log into Access Web so that you can submit and monitor jobs.

Review the [supported browsers](#) before logging into Access Web.

Before you can submit a job, a service cluster must be added. Only the portal administrator can add service clusters. The first person to login to Access Web after installation is considered the portal administrator.

 **Note:** A localhost cluster is added by default, if Access Web is installed with PBS Application Services (PAS).

1. Enter the URL `https://<hostname>:4443/pbsworks` in the address bar of a supported browser. where `<hostname>` is the IP address or hostname of the machine where Access Web is installed. The Access Web login screen is displayed.
2. Enter your username and password.
3. Click **Log In**.


If Access Web is not installed with PAS, then you must [add a service cluster](#).

## 4.4 Add a Service Cluster


Establish a connection to an HPC cluster so that you may begin submitting jobs.

Before you can configure a cluster, you must know the hostname of the PAS Server installed on the PBS Professional headnode.

The first person to login to Access Web after installation is considered the portal administrator. The portal administrator is the only user who can add or delete service clusters. A service cluster must be added before jobs can be submitted to the Workload Manager.

 **Note:** A localhost cluster is added by default, if Access Web is installed with PBS Application Services (PAS).

1. Choose one of the following options:

- If no service clusters have been configured, click the **Configure one or more services** link.
- Click  and then click **Add**.

The Add Service Cluster screen is displayed.







Figure 1: Add Service Cluster

2. For **Server Name**, enter a short name describing the cluster.
3. For **URL**, enter the URL for connecting to the Workload Manager.

The URL is in the format `https://<hostname>:5243/pas` where `<hostname>` is the hostname of the machine where the PAS Server is installed (typically the PBS Professional headnode).

 **Note:** It is recommended to add a cluster using the hostname of the PAS Server rather than the IP address. This prevents connectivity issues from arising when an IP address is changed (DHCP, etc.).

4. For **User Name** and **Password**, enter your login credentials.  
The user name and password must be available in PAS.
5. For **Root Dir**, enter the pathname where user job input and result files are stored.  
Ex: /home, /users, /stage
6. Click  if you want to add another **Root Dir** and enter the pathname.




The screenshot shows the 'Add Service Cluster' form with the following fields and values:

- Server Name: hpc\_cluster
- URL: https://172.16.80.35:5243/pas
- User Name: pbsadmin
- Password: .....
- Root Dir: /stage
- Root Dir: /johnsmith (with a delete 'x' button)
- Default Root Dir: /stage (dropdown menu)

Buttons at the bottom: Add, Cancel, Done, + Root Dir.

Figure 2: Multiple Root Directory Entry

7. Select the default root directory to be displayed from the **Default Root Dir** drop-down menu.



The screenshot shows the 'Add Service Cluster' form with the 'Default Root Dir' dropdown menu open. The dropdown menu lists the following options:

- /stage
- /stage
- /johnsmith
- /hpc

The 'Add' button is highlighted in black.

Figure 3: Default Root Directory

8. Click **Add**.

If the service cluster is added successfully, then a notification is displayed.



**Note:** A notification is displayed to all users logged into Access Web when a service cluster gets added, edited, deleted, if it goes down or if it is unreachable.

- 9. Repeat steps 2 through 8 to add additional service clusters.
- 10. Click **Done**.  
A list of service clusters that have been added is displayed.

The screenshot shows the 'Manage Services' window with a legend indicating green for 'Available' and red for 'Not Available'. A table lists two service clusters: 'hpccluster' and 'pbscluster', both with green status icons and 'Available' in the details column.

Name	Uri	Last Seen On	Last Modified	Details	
hpccluster	https://localhost:5243/pas	10/2/2018, 1:56:15 AM	9/20/2018, 9:58:50 PM	Available	
pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:56:15 AM	10/2/2018, 1:55:20 AM	Available	

Figure 4: Service Clusters List

The green color next to the service cluster indicates that it is available to use. The red color indicates that the service cluster is not available.

The **Details** column provides the reason when a service cluster is not available. Mouse hover the **Details** column of a service cluster to view the error message.

The screenshot shows the 'cluster' row highlighted in blue. The 'Details' column for this row displays an error message when hovered over.

Name	Uri	Last Seen On	Last Modified	Details	
cluster	https://172.16.80.35:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:57:37 AM	I/O error on GET request for "https://172.16.80.35:5243/pas/restservice/jobs/select": Connect to 172.16.80.35:5243 [/172.16.80.35] failed: Connection refused; nested exception is org.apache.http.conn.HttpHostConnectException: Connect to 172.16.80.35:5243 [/172.16.80.35] failed: Connection refused	
hpccluster	https://localhost:5243/pas	10/2/2018, 1:57:50 AM			
pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:57:50 AM			

Figure 5: Service Cluster Details



## 4.5 Onboard an Application Definition

Port an application definition from a legacy version of PBS Works so that it can be used by Access Web.

Access Web allows onboarding the legacy application definitions in a very easy way and it can be done at any time. Recommended techniques for onboarding legacy application definitions:

- Test your legacy application definitions without making any changes – Submit jobs to an HPC cluster and verify that Access Web can render and submit the job properly.
- Upgrade your application definitions to use Access Web features - Access Web allows you to enhance your application definition by making some modification for using the following features of Access Web:
  - File System Right Click Context Menu Integration
  - Master File Analyzer

### 4.5.1 Integrate Right Click Context Menu of Access Web

Enrich your legacy application definition to use the right click context menu integration feature of Access Web.

Access Web allows you to enhance your application definition by making some modification to use the right click context menu integration feature. You can use this feature by defining:

- PRIMARY\_FILE and QUEUE arguments in application definition

Application definitions must have a PRIMARY\_FILE argument defined in the application definition input file that represents the primary input file for the solver. If a legacy application definition calls the primary input file something other than PRIMARY\_FILE, then a mapping file must be updated to port the application definition. Additionally, if the legacy application definition contains an application argument that represents the queue to which the job is submitted, the name of the application argument must be QUEUE. If it is not, the mapping file must be updated.

- Update a solver's application definition to link it to a specific file extension.

Update a solver's application definition to link it to a specific file extension. Access Web links a job input file to a specific application or solver via the file's extension. For example, the solver Optistruct is a structural analysis solver and can process input files with a .fem extension. The association between the file extension and the solver is done through the application definition and must be set up so that Access Web can determine which solvers are available for a file extension.

1. Edit the solver's application input file `app-inp-application.xml`
2. Link the file extension to the solver by adding the following XML:

```
<ApplicationExtension>file_extension</ApplicationExtension>
```

The below example links a file with the extension of .fem to the Optistruct solver.

```
<ApplicationId>Optistruct</ApplicationId>
<ApplicationName>Optistruct</ApplicationName>
<ApplicationExtension>.fem</ApplicationExtension>
```

3. Save the application input file.

4. Update the site configuration file `site-config.xml` with the appropriate application information such as versions and policies:

```
<Applications>
  <Application id="Optistruct">
    <ApplicationVersions>
      <ApplicationVersion>
        <Option>11.0</Option>
        <Executable>/opt/hyperworks/11.0/altair/scripts/optistruct</
Executable>
      <ApplicationVersion>
        <ApplicationVersion>
          <Option>12.0</Option>
          <Executable>/opt/hyperworks/12.0/altair/scripts/optistruct</
Executable>
      <ApplicationVersion>
    </ApplicationVersions>
  </Application>
</Applications>
```

5. Edit the file `PA_HOME/config/pa/appmapping/applicationmapping.json`
6. Add the following JSON between the bracket []

```
{
  "serverName": "server-1", "version": "13.1", "applications":
  [
    {
      "applicationName": "RADIOSS-SMP",
      "primaryFile": "MASTER_FILE",
      "queue": "Queues"
    }
  ]
}
```

7. Change the value of `serverName` to the name of the server provided when adding the service cluster to Access Web.

```
"serverName": "server-1",
```

8. Change the value of `version` to the legacy version of PBS Works that you are porting from.

```
"version": "13.1",
```

9. Change the value of `applicationName` to the name of the application that you want to port. Denoted by the XML element `<ApplicationName>` in the legacy application definition. The legacy XML looks like this:

```
<ApplicationName>Optistruct</ApplicationName>
```

The JSON should look like this:

```
"applicationName": "Optistruct"
```

10. Change the value of `primaryFile` to the name of the application argument that represents the application input file for the solver.

Denoted by the XML element `<Name>` in the legacy application definition. The legacy XML looks like this:

```
<ArgumentChoice>
  <ArgumentFileName>
    <Name>MASTER_FILE</Name>
    <Description>Select your Optistruct Master file.</Description>
    <DisplayName>Master File</DisplayName>
    <InputRequired>true</InputRequired>
```

```
</ArgumentFileName>  
</ArgumentChoice>
```

The JSON should look like this:

```
"primaryFile": "MASTER_FILE"
```

11. Change the value of *queue* to the name of the application argument that represents the queue to which the job is submitted.

Denoted by the XML element `<Name>` in the legacy application definition. The legacy XML looks like this:

```
<ArgumentChoice>  
  <ArgumentStringEnumerated>  
    <Name>BATCH_QUEUE</Name>  
    <Description>Select the batch queue you would like to submit to.</  
Description>  
    <DisplayName>Batch Queue</DisplayName>  
    <InputRequired>>false</InputRequired>  
    <Option>workq</Option>  
    <Option>testq</Option>  
    <DefaultValue>workq</DefaultValue>  
  </ArgumentStringEnumerated>  
</ArgumentChoice>
```

The JSON should look like this:

```
"queue": "BATCH_QUEUE"
```

12. Add additional applications by repeating previous step 9-11 making sure that when you add the next application to the JSON mapping file you separate the applications using a comma.

```
"applications":  
[  
  {  
    "applicationName": "ShellScript",  
    "primaryFile": "JOB_SCRIPT"  
  },  
  {  
    "applicationName": "Optistruct",  
    "primaryFile": "MASTER"  
  }  
]
```

13. Save the file.
14. Copy your legacy application definitions to the PAS repository.
15. Restart PAS by issuing the command:

```
service pbsworks-pa restart
```

The following notification is displayed to any users that are logged into Access Web:

There is a change in configuration data. Application will reload.

Once Access Web reloads, the new application definition is available.

16. Right-click on a job input file that has the file extension that was just added to the application definition.
17. Verify that the correct solver and job profiles are being displayed in the context menu.

## 4.5.2 Master File Analyzer

The Master File Analyzer identifies the list of include files from the input or master file that is required to submit a job.

This feature must be enabled in the application definition to dynamically identify the include files. The default application definitions with Master File Analyzer capabilities are provided to get you up and running quickly. Obtain them through your usual Altair support channels.

You can refer to *Diving Into Application Definitions* guide and the samples provided to convert or write application definitions to support Master File Analyzer.

# Upgrade and Downgrade Access Web

Upgrade Access Web previous versions to 2019.1 and downgrade Access Web 2019.1.

This chapter covers the following:

- [5.1 Upgrade Access Web](#) (p. 41)
- [5.2 Downgrade Access Web](#) (p. 42)

The upgrade and downgrade of Access Web is not supported by the installer. You have to manually perform the steps to upgrade or downgrade.




**Note:** Access Web 2018.3 and 2018.4 versions are supported for upgrading and downgrading.

The Access Web 2019.1 supports only PAS 2019.1. So, if you are upgrading Access Web, then you have to upgrade PAS.

## 5.1 Upgrade Access Web

Upgrade Access Web 2018.3 or 2018.4 to 2019.1.

- Review [System Requirement](#) and [Prerequisites](#) of Access Web
- For installing Access Web 2019.1, refer to [Install Access Web](#)

 **Note:** Do not uninstall previous version of Access Web or PAS.

A binary or executable of Access Web 2019.1 needs to be downloaded or obtained using your usual Altair support channels.

Perform these steps to upgrade Access Web and PAS (single and different machine setup) 2018.3 or 2018.4 to 2019.1.

The upgrade script will perform the following:

- Migrate application definitions, the site configuration file, and the server configuration file
- Migrate the user preference and configuration related files from Home and Exec folders of previous versions 2018.3 or 2018.4 to 2019.1
- Automatically start Access Web 2019.1

**1.** Stop the currently installed version of Access Web:

```
service pbsworks-pa stop
```

**2.** Create a backup of /var/.com.zerog.registry.xml

**3.** Remove /var/.com.zerog.registry.xml

**4.** Create a backup of /etc/pbsworks-pa.conf as /etc/pbsworks-pa.conf.<PreviousVersion>

**5.** Install Access Web 2019.1.

 **Note:** Do not start Access Web 2019.1.

**6.** Navigate to PA\_EXEC/init/

**7.** Execute the pa-upgrade.sh script as follows:

```
pa-upgrade.sh <PreviousVersion_PA_HOME> <PreviousVersion_PA_EXEC>
```

where <PreviousVersion\_PA\_HOME> is the Access Web 2018.3 or 2018.4 home folder and

<PreviousVersion\_PA\_EXEC> is the Access Web 2018.3 or 2018.4 execution folder.

After upgrading, Access Web 2019.1 will be up and the following message will be displayed:

```
"Access Web upgraded successfully"
```

**8.** Enter the URL `https://<hostname>:4443/pbsworks` in the address bar of a supported browser.  
where <hostname> is the hostname of the machine where Access Web is installed.

The Access Web login screen is displayed.

**9.** Enter your username and password.

**10.** Click **Log In**.

To configure Access Web, refer to [Configuring Access Web After Installation](#).

## 5.2 Downgrade Access Web

Downgrade Access Web 2019.1 to Access Web 2018.3 or 2018.4.

Perform these steps to downgrade Access Web and PAS (single and different machine setup) 2019.1 to 2018.3 or 2018.4.

1. Stop Access Web 2019.1 using the following command:

```
service pbsworks-pa stop
```

2. Create a backup of `/etc/pbsworks-pa.conf` as `/etc/pbsworks-pa.conf.2019.1`
3. Rename `/etc/pbsworks-pa.conf.PreviousVersion` to `/etc/pbsworks-pa.conf`
4. Copy `PreviousVersion_PA_EXEC/init/pbsworks-pa` script to `/etc/init.d/`  
You are successfully downgraded to Access Web 2018.3 or 2018.4.
5. Start Access Web using the following command:  

```
/etc/init.d/pbsworks-pa start
```
6. Enter the URL `https://<hostname>:4443/pbsworks` in the address bar of a supported browser.  
where `<hostname>` is the IP address or hostname of the machine where Access Web is installed.  
The Access Web login screen is displayed.
7. Enter your username and password.
8. Click **Log In**.

# Uninstall Access Web and Remote Session Component

---

## 6

Instructions for uninstalling previous version of Access Web and Remote Session component.

This chapter covers the following:


- [6.1 Uninstall Access Web](#) (p. 44)
- [6.2 Uninstall Remote Session](#) (p. 45)



## 6.1 Uninstall Access Web

Remove a previous version of Access Web.

You must stop Access Web before uninstalling. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** Uninstalling Access Web will not remove PA\_HOME.

1. Login as root to the machine where Access Web is installed.
2. Navigate to the `/opt/altair/pbsworks/2019.1/access/Altair_Access_installation` directory.
3. Execute the uninstall script by entering the following command:

```
./Change_Altair_Access_Installation -i console
```

The command must contain spaces with escape characters.

4. Follow the instructions provided by the uninstaller.

## 6.2 Uninstall Remote Session

Unconfigure PBS Professional and PBS Application Services and uninstall remote session components to disable the remote session capabilities of Access Web.

The uninstalling must be run multiple times across several machines and must be performed in the following sequence:

1. Unconfigure PBS Professional and PAS in PBS Professional headnode and in the machine where PBS Application Services is installed. This will
  - delete the interactive queue
  - unconfigure GPUs as a custom resource
  - remove the application definitions Glxphere which is installed automatically when the Remote Session component was installed on the PAS Server
2. Uninstall Remote Session Components on all PBS MoMs.
3. Uninstall the interactive proxy.

### 6.2.1 Unconfigure PBS Professional and PBS Application Services

Unconfigure PBS Professional and PAS before uninstalling Remote Session Components.

You must stop Access Web before uninstalling. For more information about stopping Access Web, see [Access Web Service Commands](#).



**CAUTION:** It is advisable that you run the installer when critical jobs are not running.

Run the installer to unconfigure PBS Professional and PAS on the PBS Professional headnode and in the machine where PAS is installed.

This will:

- delete the interactive queue
- unconfigure GPUs as a custom resource
- remove the application definitions Glxphere which is installed automatically when the Remote Session component was installed on the PAS Server

1. Login to the machine as root where the PBS Professional Server and PAS is installed.
2. Navigate to the folder where you have the Remote Session Agent installer.
3. Enter the command:

```
./AltairRemoteSessionAgent_<Version>_<Build ID>_<YYYYMMDD>_<Timestamp>.bin -i console
```

4. If you are installing the remote session component for the first time, then you will see the below message, enter 1 and press ENTER.

```
Manage Instances
```

```
-----
```

```
->1- Install a new instance
```

2- Modify an existing instance


5. Read the introduction and press `ENTER`.
6. Page through the license agreement by pressing `ENTER` until you are asked to accept its terms and conditions.
7. Accept the license agreement by entering `Y` and pressing `ENTER`.  
Four Options are displayed.
8. Enter `3` to unconfigure the PBS Professional and PAS servers and press `ENTER`.
9. PBS Professional and PAS is restarted during the installation process, choose whether you want to proceed:
  - Choose `No` to exit and run the installer at a more suitable time.
  - Choose `Yes` to run the installer.

Perform [Uninstalling Remote Session components](#).

## 6.2.2 Uninstall Remote Session Components


Uninstall previous version of remote session components.

You must stop Access Web before uninstalling. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **CAUTION:** It is advisable that you run the installer when critical jobs are not running.

If it is a distributed deployment, then perform the following:

- Login to each of the PBS MoM and uninstall the Remote Session Components
- Login to the machine hosting Access Web and uninstall Remote Session Components to remove the proxy

 **Note:** This will uninstall the Remote Session component and Interactive Proxy only if you installed Access Web on the same machine as the PBS Professional Server.

1. Login as root to the machine where Access Web is installed.
2. Navigate to the `/opt/altair/pbsworks/2019.1/dmagent/_AltairRemoteSessionAgent_Installer_<Version>_installation` directory.
3. Execute the uninstall script by entering the following command:  

```
./Change\ AltairRemoteSessionAgent_Installer_<Version>\ Installation -i console
```

The command must contain spaces with escape characters.
4. Follow the instructions provided by the uninstaller.

# Access Web Service Commands

7

Commands for starting, stopping, restarting and checking the status of Access Web.

The below commands should be executed by the root as defined in `/etc/pbsworks-pa.conf`

## **Start Access Web**

```
service pbsworks-pa start
```

## **Stop Access Web**

```
service pbsworks-pa stop
```

## **Restart Access Web**

```
service pbsworks-pa restart
```

## **Determine the Status of Access Web**

```
service pbsworks-pa status
```

Add, edit, and delete service clusters.

This chapter covers the following:

- [8.1 Add a Service Cluster](#) (p. 49)
- [8.2 Edit a Service Cluster](#) (p. 52)
- [8.3 Delete a Service Cluster](#) (p. 54)


Only the portal administrator can add, edit, and remove service clusters. Regular users are unable to access the Manage Services page.

## 8.1 Add a Service Cluster


Establish a connection to an HPC cluster so that you may begin submitting jobs.

Before you can configure a cluster, you must know the hostname of the PAS Server installed on the PBS Professional headnode.

The first person to login to Access Web after installation is considered the portal administrator. The portal administrator is the only user who can add or delete service clusters. A service cluster must be added before jobs can be submitted to the Workload Manager.

 **Note:** A localhost cluster is added by default, if Access Web is installed with PBS Application Services (PAS).

1. Choose one of the following options:

- If no service clusters have been configured, click the **Configure one or more services** link.
- Click  and then click **Add**.

The Add Service Cluster screen is displayed.







Figure 6: Add Service Cluster

2. For **Server Name**, enter a short name describing the cluster.
3. For **URL**, enter the URL for connecting to the Workload Manager.

The URL is in the format `https://<hostname>:5243/pas` where `<hostname>` is the hostname of the machine where the PAS Server is installed (typically the PBS Professional headnode).

 **Note:** It is recommended to add a cluster using the hostname of the PAS Server rather than the IP address. This prevents connectivity issues from arising when an IP address is changed (DHCP, etc.).

4. For **User Name** and **Password**, enter your login credentials.  
The user name and password must be available in PAS.
5. For **Root Dir**, enter the pathname where user job input and result files are stored.  
Ex: /home, /users, /stage
6. Click  if you want to add another **Root Dir** and enter the pathname.




The screenshot shows the 'Add Service Cluster' form with the following fields and values:

- Server Name: hpc\_cluster
- URL: https://172.16.80.35:5243/pas
- User Name: pbsadmin
- Password: .....
- Root Dir: /stage
- Default Root Dir: /stage (selected in a dropdown menu)

At the bottom, there are four buttons: Add, Cancel, Done, and + Root Dir. The + Root Dir button is highlighted with a blue border.

Figure 7: Multiple Root Directory Entry

7. Select the default root directory to be displayed from the **Default Root Dir** drop-down menu.



The screenshot shows the 'Add Service Cluster' form with the following fields and values:

- Server Name: hpc\_cluster
- URL: https://172.16.80.35:5243/pas
- User Name: pbsadmin
- Password: .....
- Root Dir: /stage, /johnsmith, /hpc (three entries, each with a delete 'X' button)
- Default Root Dir: /stage (selected in a dropdown menu)

At the bottom, there are four buttons: Add, Cancel, Done, and + Root Dir. The + Root Dir button is highlighted with a blue border.

Figure 8: Default Root Directory

8. Click **Add**.

If the service cluster is added successfully, then a notification is displayed.



**Note:** A notification is displayed to all users logged into Access Web when a service cluster gets added, edited, deleted, if it goes down or if it is unreachable.

- 9. Repeat steps 2 through 8 to add additional service clusters.
- 10. Click **Done**.

A list of service clusters that have been added is displayed.

The screenshot shows the 'Manage Services' interface. At the top right is an 'Add' button. Below it are two status indicators: a green square for 'Available' and a red square for 'Not Available'. The main part of the interface is a table with the following columns: Name, Uri, Last Seen On, Last Modified, Details, and a gear icon for settings. There are two rows of data, both marked as 'Available' with green squares.

Name	Uri	Last Seen On	Last Modified	Details	
hpcccluster	https://localhost:5243/pas	10/2/2018, 1:56:15 AM	9/20/2018, 9:58:50 PM	Available	
pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:56:15 AM	10/2/2018, 1:55:20 AM	Available	

Figure 9: Service Clusters List

The green color next to the service cluster indicates that it is available to use. The red color indicates that the service cluster is not available.

The **Details** column provides the reason when a service cluster is not available. Mouse hover the **Details** column of a service cluster to view the error message.

This screenshot shows the 'Manage Services' interface with a mouse hovering over the 'Details' column of the 'cluster' row. The 'cluster' row is highlighted in light blue and has a red square next to its name, indicating it is 'Not Available'. The 'Details' column for this row is expanded, showing an error message. The other two rows, 'hpcccluster' and 'pbscluster', are green and marked as 'Available'.


Name	Uri	Last Seen On	Last Modified	Details	
cluster	https://172.16.80.35:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:57:37 AM	I/O error on GET request for "https://172.16.80.35:5243/restservice/jobs/select": Connect to 172.16.80.35:5243 [/172.16.80.35] failed: Connection refused; nested exception is org.apache.http.conn.HttpHostConnectException: Connect to 172.16.80.35:5243 [/172.16.80.35] failed: Connection refused	
hpcccluster	https://localhost:5243/pas	10/2/2018, 1:57:50 AM			
pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:57:50 AM			


Figure 10: Service Cluster Details




## 8.2 Edit a Service Cluster

Update a service cluster password or root directory so that you can continue to submit your jobs.

 **Note:** Only the portal administrator can edit a service cluster.

1. Click .  
A list of service clusters that have been previously added is displayed.



The screenshot shows the 'Manage Services' interface. At the top, there is a legend with a green square for 'Available' and a red square for 'Not Available'. Below the legend is a table with the following columns: Name, Url, Last Seen On, Last Modified, Details, and a gear icon for settings. The table contains three rows of data:






Name	Url	Last Seen On	Last Modified	Details	
 cluster	https://172.16.80.35:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:57:37 AM	I/O error on GET request for "htt	
 hpcccluster	https://localhost:5243/pas	10/2/2018, 1:57:50 AM	9/20/2018, 9:58:50 PM	Available	
 pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:55:20 AM	Available	

Figure 11: Manage Services

2. Right-click the cluster that you want to edit.
3. Click **Edit** from the context menu.



The screenshot shows the 'Manage Services' interface with a context menu open over the 'cluster' row. The context menu has two options: 'Edit' (with a pencil icon) and 'Delete' (with a trash can icon). The 'cluster' row is highlighted in blue.





Name	Url	Last Seen On	Last Modified	Details	
 cluster	https://172.16.80.35:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:57:37 AM	I/O error on GET request for "htt	
 hpcccluster	https://localhost:5243/pas	10/2/2018, 1:57:50 AM	9/20/2018, 9:58:50 PM	Available	
 pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:55:20 AM	Available	

Figure 12: Cluster Edit Option

The Edit Service Cluster screen is displayed.

The screenshot shows a web form titled "Edit Service Cluster" with the instruction "All fields are required". The form contains the following fields and values:

- Server Name: cluster
- URL: https://172.16.80.35:5243/pas
- User Name: pbsadmin
- Password: (empty)
- Root Dir: /stage
- Default Root Dir: /stage (selected from a dropdown menu)

At the bottom of the form are four buttons: "Save" (highlighted in black), "Cancel", "Done", and "+ Root Dir".

Figure 13: Edit Service Cluster

4. Update the service cluster information.
5. Click **Save**.




**Note:** A notification is displayed to all users logged into Access Web when a service cluster gets added, edited, deleted, if it goes down or if it is unreachable.

6. Click **Done**.


## 8.3 Delete a Service Cluster

Remove a service cluster when you no longer want to submit and manage jobs on that cluster.

 **Note:** Only the portal administrator can delete a service cluster.

1. Click .

A list of service clusters that have been previously added is displayed.



The screenshot shows the 'Manage Services' interface. At the top right is an 'Add' button. Below it are two status indicators: a green square for 'Available' and a red square for 'Not Available'. The main part of the interface is a table with the following columns: Name, Url, Last Seen On, Last Modified, Details, and a settings gear icon. The table contains three rows of data:






Name	Url	Last Seen On	Last Modified	Details	
 cluster	https://172.16.80.35:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:57:37 AM	I/O error on GET request for "htt	
 hpcccluster	https://localhost:5243/pas	10/2/2018, 1:57:50 AM	9/20/2018, 9:58:50 PM	Available	
 pbscluster	https://172.16.80.18:5243/pas	10/2/2018, 1:57:50 AM	10/2/2018, 1:55:20 AM	Available	

Figure 14: Manage Services

2. Right-click the cluster that you want to remove.
3. Click **Delete** from the context menu.




This screenshot is similar to Figure 14, but a context menu is open over the first row ('cluster'). The menu has two options: 'Edit' (with a pencil icon) and 'Delete' (with a trash can icon). A mouse cursor is pointing at the 'Delete' option.

Figure 15: Server Cluster Delete

4. Click **Yes**.

The files and jobs from this cluster will no longer be accessible.

 **Note:** A notification is displayed to all users logged into Access Web when a service cluster gets added, edited, deleted, if it goes down or if it is unreachable.

5. Click **Done**.

Advanced configurations for Access Web and its services.

This chapter covers the following:

- [9.1 Configure the Access Web Component](#) (p. 56)
- [9.2 Configure PBS Application Services](#) (p. 81)
- [9.3 Configure the Remote Session Component](#) (p. 95)
- [9.4 Configure Results Visualization Service](#) (p. 99)
- [9.5 Access Web Windows Setup](#) (p. 111)
- [9.6 Running Job Operations in Windows](#) (p. 115)

## 9.1 Configure the Access Web Component

Configurations required for Access Web component.

### 9.1.1 Change Port Numbers

Change the default port numbers used by Access Web.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

The Access Web installer has auto-port detection logic in place and ports will be picked up by each service within the specified range. Refer to [ports used by Access Web](#) for more information.

To allocate specific port to each of the service, then follow the steps mentioned in below topics:

### Change the Gateway Port Number

Change the port that the Gateway service listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The gateway port number has to be updated in the files:

- `nginx.conf`
- `rm_servers.xml`
- `dmrest.properties`

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/api_gateway/`
3. Edit the `nginx.conf` file and update the default value of 4443 of *listen* of *server*:

```
server {  
    listen      4443;  
    server_name localhost;  
    add_header X-Frame-Options "SAMEORIGIN";
```

4. Navigate to `PA_HOME/config/resultmanager/`
5. Edit the `rm_servers.xml` file and update the default value of 4443 in `<PAServerURL>`.

```
<PAServerURL>https://localhost:4443</PAServerURL>
```

6. Navigate to `PA_HOME/config/displaymanager/`
7. Edit the `dmrest.properties` file and update the default value of 4443.

```
pbsaccess.api_gateway.service.host=https://localhost:4443/
```

8. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Web Server Port Number

Change the port that the Access Web server listens on.


You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The web server port number has to be updated in the following files:

- `server.xml`
- `nginx.conf`
- `dmrest.properties`
- `dmrest.properties.template`

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/pa/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.

 **Note:** Search for the Connector port and replace 4543 with the new port number.

4. Navigate to `PA_HOME/config/api_gateway/`
5. Edit the `nginx.conf` file and update the port number.

```
env STORAGE_SERVICE_PORT=4543;

upstream pbsaccess {
    server localhost:4543;
}
```

6. Navigate to `PA_HOME/config/displaymanager/`
7. Edit the `dmrest.properties` file and update the port number.

```
pbsaccess.storage.service.host=https://localhost:4543/storage
```

8. Edit the `dmrest.properties.template` file and update the port number.

```
pbsaccess.storage.service.host=https://localhost:4543/storage
```

9. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Postgres Port Number

Change the port that Postgres listen on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

Changing the Postgres port requires the removal and recreation of the Postgres database. The script that performs this work also removes all log files located at `PA_HOME/logs`. Additionally, this script allows the Service User who owns the Postgres database and the files in `PA_HOME` and `PA_EXEC` to be changed. If you do not want to change the Service User, then provide the username of the current

Service User when executing the script. The current Service User can be determined by viewing the contents of `/etc/pbsworks-pa.conf`.

The Postgres database port number has to be updated in the files `configure.sh` and `app.properties`

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/database/scripts/`
3. Edit the `configure.sh` file and update the port number.

```
PG_PORT=4643;
```

4. Navigate to `PA_HOME/config/shared/`

5. Edit the `app.properties` file and update the port number.

```
spring.datasource.url=jdbc:postgresql://localhost:4643/pbsworks
```

6. Navigate to `PA_EXEC/init/`
7. Run the command:

```
./reconfigure-pa.sh
```

## Change the Message Broker Port Number

Change the port that the message broker (ActiveMQ) listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The Message Broker port number has to be updated in the files:

- `message-app.properties`
- `env`
- `activemq.xml`.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/shared/`
3. Edit the `message-app.properties` file and update the port number.

```
pbsworks.messaging.broker.url=tcp://localhost:4743
```

4. Navigate to `PA_EXEC/shared/thirdparty/apache/activemq/bin/`
5. Edit the `env` file and update the port number.

```
ACTIVEMQ_QUEUEMANAGERURL="--amqurl tcp://localhost:4743"
```

6. Navigate to `PA_EXEC/shared/thirdparty/apache/activemq/conf/`
7. Edit the `activemq.xml` file and update the port number.

```
<transportConnector name="openwire"  
uri="tcp://127.0.0.1:4743?  
maximumConnections=1000&wireFormat.maxFrameSize=104857600">
```

8. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Remote Session Proxy Port Number

Change the port that the Remote Session Proxy (GUACD) listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The Interactive Proxy port number has to be updated in the following files:

- `guacd.conf`
- `guacamole.properties`
- `guacamole.properties.template`

1. Login to the machine where Access Web is installed as root.

2. Navigate to `/etc/guacamole/`

3. Edit the `guacd.conf` file and update the port number.

```
bind_port = 5443
```

4. Navigate to `PA_HOME/config/displaymanager/`

5. Edit the `guacamole.properties` file and update the port number.

```
guacd-port: 5443
```

6. Edit the `guacamole.properties.template` file and update the port number.

```
guacd-port: 5443
```

7. Start Access Web by entering the command:

```
service pbsworks-pa start
```

8. Restart the Interactive Proxy by entering the command:

```
/etc/init.d/guacd start
```

## Change the Remote Session Web Server Port Number

Change the port that the Remote Session Web Server listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The Interactive Application web server port number has to be updated in the following files:

- `server.xml`
- `nginx.conf`
- `guacamole.properties`
- `guacamole.properties.template`

1. Login to the machine where Access Web is installed as root.

2. Navigate to `PA_HOME/config/displaymanager/tomcat/conf/`

3. Edit the `server.xml` file and update the port number.





**Note:** Search for the Connector port and replace 4843 with the new port number.

4. Navigate to `PA_HOME/config/api_gateway/`

5. Edit the `nginx.conf` file and update the port number.

```
upstream displaymanager {  
    server localhost:4843;  
}
```

6. Navigate to `PA_HOME/config/displaymanager/`

7. Edit the `guacamole.properties` file and update the port number.

```
dm-host: https://localhost:4843/displaymanager
```

8. Edit the `guacamole.properties.template` file and update the port number.

```
dm-host: https://localhost:4843/displaymanager
```

9. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Remote Session Job Update Port Number

Change the port that the Remote Session Job Update listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The Remote Session Job Update port number has to be updated in the files `dmrest.properties` and `dmrest.properties.template`.

1. Login to the machine where Access Web is installed as root.

2. Navigate to `PA_HOME/config/displaymanager/`

3. Edit the `dmrest.properties` file and update the port number.

```
jobsub.monitor.port=4943
```

4. Edit the `dmrest.properties.template` file and update the port number.

```
jobsub.monitor.port=4943
```

5. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Result Manager Services Port Number

Change the port that the Result Manager Services listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The Result Manager Services port number has to be updated in the files `server.xml` and `nginx.conf`.

1. Login to the machine where Access Web is installed as root.

2. Navigate to `PA_HOME/config/resultmanager/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.



**Note:** Search for the Connector port and replace 5043 with the new port number.

4. Navigate to `PA_HOME/config/api_gateway/`
5. Edit the `nginx.conf` file and update the port number.

```
upstream resultmanager {  
    server localhost:5043;  
}
```

6. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Result Core Services Port Number

Change the port that the Result Core Services listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The Result Core Services port number has to be updated in the files `server.xml`, `rm.servers.xml` and `resultmanager.conf`.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/resultservice/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.



**Note:** Search for the Connector port and replace 5143 with the new port number.

4. Navigate to `PA_HOME/config/resultmanager/`
5. Edit the `rm.servers.xml` file and update the port number in `RVSServerURL`.

```
<RVSServerURL>https://localhost:5143</RVSServerURL>
```

6. Navigate to `PA_HOME/config/api_gateway/default.d/`
7. Edit the `resultmanager.conf` file and update the port number:

```
proxy_pass https://localhost:5143/resultservice;
```

8. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the PBS Application Services Port Number


Change the port that the PAS listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The PAS port number has to be updated in the files `server.xml` and `nginx.conf`.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/pas/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.

 **Note:** Search for the Connector port and replace 5243 with the new port number.

4. Navigate to `PA_HOME/config/api_gateway/`
5. Edit the `nginx.conf` file and update the port number.

```
env PAS_SERVICE_PORT=5243;
```

6. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Job Profile Services Port Number


Change the port that the Job Profile Services listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The job profile services port number has to be updated in the files `server.xml` and `nginx.conf`.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/jobprofiles/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.

 **Note:** Search for the Connector port and replace 5343 with the new port number.

4. Navigate to `PA_HOME/config/api_gateway/`
5. Edit the `nginx.conf` file and update the port number.

```
upstream jobprofiles {  
    server localhost:5343;  
}
```

6. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the AMS Port Number

Change the port that the Access Management Services listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The AMS port number has to be updated in the files:

- server.xml
- app.properties
- nginx.conf
- ServiceRegistry.json.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/ams/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.



**Note:** Search for the Connector port and replace 5543 with the new port number.

4. Navigate to `PA_HOME/config/shared/`
5. Edit the `app.properties` file and update the port number.

```
pbsworks.ams.url = https://localhost:5543/AAService
```

6. Navigate to `PA_HOME/config/api_gateway/`
7. Edit the `nginx.conf` file and update the port number.

```
upstream amsservice {  
    server localhost:5543;  
}
```

8. Navigate to `PA_HOME/config/shared/token_handler_config/token_injector/`
9. Edit the `ServiceRegistry.json` file and update the port number.

```
{"service":[{"name":"ams","host":"localhost","port":"5543",  
  "service_name":"AAService","scheme":"https"}]}
```

10. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Mobile Notification Service Port Number

Change the port that the mobile notification service listens on.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

For information on default port and port range, refer to [Ports Used by Access Web](#).

The mobile notification service port number has to be updated in the files `server.xml` and `nginx.conf`.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/mobile_notification_service/tomcat/conf/`
3. Edit the `server.xml` file and update the port number.



**Note:** Search for the Connector port and replace 5643 with the new port number.

4. Navigate to `PA_HOME/config/api_gateway/`
5. Edit the `nginx.conf` file and update the port number.

```
upstream mobile_notification_service {  
    server localhost:5643;
```

```
}
```

6. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## 9.1.2 Change Memory used by the Services

Change the default memory value used by the services in Access Web.


You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

To change the default memory value used by the service, follow the steps mentioned in below topics:

### Change the Gateway Service Memory Value

Change the memory value of gateway service.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
jvm_options      "-Xmx512m";
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/api_gateway/`
3. Edit the `nginx.conf` file and update the default value of `jvm_options`:

```
jvm_options      "-Xmx512m";
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

### Change the Access Web Server Service Memory Value

Change the memory value of Access Web server service.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="-Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/pa/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="-Xmx512M"
```

4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Message Broker (ActiveMQ) Service Memory Value

Change the memory value of message broker (ActiveMQ) service.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).



**Note:** You can add the following line in the configuration file if the memory value is not found:

```
ACTIVEMQ_OPTS_MEMORY="-Xms64M -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/shared/thirdparty/apache/activemq/bin/`
3. Edit the `env` file and update the default value of `ACTIVEMQ_OPTS_MEMORY`:

```
ACTIVEMQ_OPTS_MEMORY="-Xms64M -Xmx512M"
```

4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Remote Session Webserver Service Memory Value

Change the memory value of remotoe session webserver service.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).



**Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/displaymanager/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Result Manager Services Memory Value

Change the memory value of result manager services.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/resultmanager/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Result Core Services Memory Value

Change the memory value of result core services.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/resultservice/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Job Profile Services Memory Value

Change the memory value of job profile services.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/jobprofiles/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the AMS Services Memory Value

Change the memory value of AMS services.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/ams/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

## Change the Mobile Notification Services Memory Value

Change the memory value of mobile notification services.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/mobile_notification_service/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

4. Start Access Web by entering the command:


```
service pbsworks-pa start
```



## Change the Executor Services Memory Value

Change the memory value of executor services.

You must stop Access Web before changing the port number. For more information about stopping Access Web, see [Access Web Service Commands](#).

 **Note:** You can add the following line in the configuration file if the memory value is not found:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_EXEC/executor/scripts/`
3. Edit the `setenv.sh` file and update the default value of `JAVA_OPTS`:

```
JAVA_OPTS="$JAVA_OPTS -Xmx512M"
```


4. Start Access Web by entering the command:

```
service pbsworks-pa start
```

### 9.1.3 Set the Double-Click Delay Time

Change the delay time required between two consecutive clicks for a double-click.

The default delay time between two consecutive clicks is set to 500ms (500 millisecond)

 **Note:** You must have administrative privileges to change the double-click delay time.

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/pa/`
3. Edit the file `configuration.json`.
4. Change the value of the `doubleClickDelay`.

### 9.1.4 Change the Database Password

Change the database password to encrypted text.

If the Postgres database password is changed (via `passwd`, `yppasswd`, etc.), then Access Web will need to be updated with the new password.

The Postgres database password is stored in the `app.properties` file. The location of the file for a typical installation of Access Web is: `PA_HOME/config/shared/`

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_EXEC/shared/thirdparty/postgresql/bin/`
3. Execute the following command:

```
./psql -p <DB_PORT> -d pbsworks -U <DB_USER>)
```

*DB\_PORT* is database port, and *DB\_USER* is database username.

For example,

```
./psql -p 4643 -d pbsworks -U pbsworks
```

4. Enter the existing password. The default password is `postgres`.

5. Enter `\password` in Postgres prompt.

6. Enter the new password.

7. Navigate to `PA_EXEC/init/`

8. Execute the following command:

```
./pa-encrypt.sh
```

9. Enter the new password given in step 7.

This command will output the password in its encrypted format.

10. Navigate to `PA_HOME/config/shared/`

11. Edit the `app.properties` file and update the value of `spring.datasource.password` to the encrypted format of the new password.

12. Restart Access Web by entering the command:

```
service pbsworks-pa restart
```

## 9.1.5 Configure Default File Viewer

Configure default file viewer to open the file based on the file extension.

By default, the file extension `.out`, `.Log`, `.stat`, `.rad`, `.fem` will open in the file viewer by double-clicking the files. If you double-click or open a file with unknown file extension, then an application list dialog box is displayed to choose the desired application to view the file.

 **Note:** You must have administrative privileges to change the double-click delay time.

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/pa/`
3. Open the `nativeviewer.json` file.
4. Add the file extensions under `ApplicationFileExtension` value.


```
"ApplicationFileExtension": {  
  "type": "array",  
  "items": {  
    "type": "string"  
  },  
  "value": [".sh",  
    ".fem",  
    ".py",  
    ".env",  
    ".txt",  
    ".Log",  
    ".stat",  
    ".rad",  
    ".out"  
  ],  
  "Displayable": false  
}
```

The file extensions mentioned in *ApplicationFileExtension* value will open with the default file viewer.

## 9.1.6 Configure Default Columns in Job List View

Configure the job properties columns that are displayed in the job list view.

By default, the job properties columns displayed in the job list view after clicking on the Jobs tab are Job ID, Job Name, Job State, Creation Time and User Name. You can add or remove the *defaultGridColumn*s property value in the *jobpropertiesmap.json* file.

 **Note:** You must have administrative privileges to change the default job properties value.

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/pa/`
3. Open the *jobpropertiesmap.json* file.
4. Update the *defaultGridColumn*s value.

```
"defaultGridColumn": ["jobId", "jobName", "jobState", "creationTime", "userName"]
```

The updated job properties value will be displayed in the job list view in Jobs tab.

## 9.1.7 Change the Maximum File Upload Size

Change the default file upload size based on site's requirements.

You must stop Access Web before changing the maximum file upload size. For more information about stopping Access Web, see [Access Web Service Commands](#).

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/api_gateway/`
3. Open the *nginx.conf* file.
4. Update the *client\_max\_body\_size* value in MB.

```
#set max file upload size to 4GB  
client_max_body_size 4096m;
```

5. Start Access Web using the following command:

```
service pbsworks-pa start
```

## 9.1.8 Change the File Opening behavior of a Remote Session Application

Change the file opening behavior of a remote session application from cross mounted file system to non-shared file system.

The default application definition provided with Access Web is configured such that the selected file is not copied to the execution node. The remote session will open the file in execution node with the assumption that the file name and file path is available in execution node. This option is the cross mounted file system where the file system is available on the execution node and head node.

In the case of non-shared file system, there is no shared file system between the execution node and head node. The Access Web will copy the file to execution node job directory and remote application will open with the copied file from job directory.

If your site does not have a cross-mounted file system that is accessible to both the PBS MoMs and the PBS Server, then you have two options for job submission:

- Update the Application Definition Input file and change the default value of *Run from job directory* to *true*.
- Uncheck the **Run from job directory** field from Job Submission Form while submitting.



**Note:** The **Run from job directory** field is displayed only if you select **All Fields** option in Job Submission form. The behavior will be changed for that session only.

When submitting an interactive job via Access Web, the Run from job directory field must be unchecked. You will need to do this every time you submit a job.

## 9.1.9 Configure Notifications for a Job State Change


Configure email notifications for a job state change.


Users of Access Web can configure email notifications when a job's state changes, including who will receive the email notification, and when the email will be sent. Currently, Access Web supports sending email notifications for the following job state changes:

- job is aborted
- job begins execution
- job finishes execution

However, the email will not be sent unless the application associated with the job has been configured accordingly. This is done through the application definition.

Each Access Web user must set their email preferences through the Access Web application.


1. Click .
2. Select **Profile**.  
Access Web Preferences is displayed.



The screenshot shows the 'Preferences' page with a left sidebar containing a list of options: Profile, Notifications, Files, Job Submission, Pagination, Tail Frequency, Persistence, RVS, and Diagnosis. The 'Profile' option is selected and highlighted. The main content area is titled 'Profile' and contains two input fields: 'Name' with the value 'John' and 'Email' with the value 'john@altair.com'.

Figure 16: Preferences

3. Double-click the **Email** field to enter additional email ID and press `Enter`. You can enter multiple email IDs separated by semi-colon (;).
4. Click **Job Submission** in the left menu. The Job Submission panel is displayed.



The screenshot shows the 'Preferences' page with the 'Job Submission' option selected in the left sidebar. The main content area is titled 'Job Submission' and contains two sections of checkboxes. The first section, 'Notify when job state changes to', has three options: 'Aborted', 'Begins Execution', and 'Ends Execution', all of which are unchecked. The second section, 'Close submission Form', has one option: 'Close submission Form after submission?', which is also unchecked.

Figure 17: Job Submission



**Note:** Click [< Back](#) to go back to the previous page.

5. Check any or all of the options in the **Notify when job state changes to** list to indicate when the email will be sent.
6. The application definition must be modified to support the email notification. This is accomplished by modifying the application definition submittime script, `presubmit.py`, with the following lines of code:

```
import re  
  
''' Mail Options '''
```

```
if userInputs['MAIL_USERS'.replace(';', ',')]:  
    job.attr_mail_list = userInputs['MAIL_USERS']  
  
if userInputs['MAIL_POINTS']:  
    mail_points = userInputs['MAIL_POINTS']  
  
    if re.match(r"[abe]", mail_points):  
        job.attr_mail_options = mail_points
```

This code captures the mail preferences entered through Access Web, and sets the job's mail options, so that PBS Professional knows to send an email when a particular job state is reached.

## 9.1.10 Disable to View all Jobs

Restrict users to only be able to view their own jobs.

By default, users can view all jobs.


1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/pa/`
3. Edit the `configuration.json` file.
4. Change the value of `restrictOthersJobs` to `true`.

## 9.1.11 Add a Generic Action for a PAS server

Perform a generic action on a job.

Generic actions are simple python scripts that run on a PAS server irrespective of the job or application.

A JSON file is used to define generic actions. You have to specify the PAS server name and the generic actions that has to be performed on that server. For a typical installation of Access Web, the generic action JSON file is `genericactions.json` and it is located at `PA_HOME/config/pa/`

 **Note:** Refer to <https://jsonlint.com/> to validate the JSON file and refer to <https://jsonformatter.org/> to format the code.

## Define a Generic Action

Define a generic action JSON file.

Here is an example of a generic action for a cluster denoted by "hpccluster":

```
{  
  "hpccluster": [{  
    "Name": "qstat",  
    "DisplayName": "Qstat of Job",  
    "Description": "Qstat of Job",  
    "ScriptLocation": "/stage/GenericActions/qstat.py",  
    "Arguments": {  
      "jobid": {
```

```
    "type": "string",  
    "DisplayName": "Job ID"  
  },  
  "required": ["jobid"]  
}
```

The following JSON elements provide a way of identifying and describing the generic action:

**Name**

An internal name of the generic action.

**DisplayName**

Name of the generic action that will be displayed to the user.

**Description**

Description of the generic action.

**ScriptLocation**

Location of the execution script.

**Arguments**

Defines arguments (input fields) that a user will enter prior to executing the generic action. The following elements define an argument:

**type**

Defines the type of the argument

**DisplayName**

Name of the argument that will be displayed

**required**

Indicates a required field

## Define a Generic Action Execution Script

Define a generic action execution script file.

A job can be selected from the Job Monitoring page of Access Web, and an action can be executed. This generic action allows a command and command options to be entered. Access Web will then run the command.

### Example of Generic Action for a Single Cluster

Below is an example of a generic action for the server "hpccluster", stored in a JSON file called genericactions.json.

```
{  
  "hpccluster": [{  
    "Name": "qstat",  
    "DisplayName": "Qstat of Job",  
    "Description": "Qstat of Job",  
    "ScriptLocation": "/stage/GenericActions/qstat.py",  
    "Arguments": {  
      "jobid": {  
        "type": "string",  
        "DisplayName": "Job ID"  
      }  
    }  
  }  
}
```

```
    },
    "required": ["jobid"]
  },
  {
    "Name": "Tracejob",
    "DisplayName": "Tracejob of Job",
    "Description": "Tracejob of Job",
    "ScriptLocation": "/stage/GenericActions/tracejob.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  },
  {
    "Name": "Distributed Tracejob",
    "DisplayName": "Distributed Tracejob of Job",
    "Description": "Distributed Tracejob of Job",
    "ScriptLocation": "/stage/GenericActions/dtj.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  },
  {
    "Name": "Node Status",
    "DisplayName": "Node status of cluster",
    "Description": "Node status of cluster",
    "ScriptLocation": "/stage/GenericActions/nodestatus.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": [ ]
    }
  }
]
```

### Example of Generic Action for a Multiple Cluster

Below is an example of a generic action for the server "hpccluster-1" and "hpccluster-2", stored in a JSON file called `genericactions.json`.

```
{
  "hpccluster-1": [{
    "Name": "qstat",
    "DisplayName": "Qstat of Job",
    "Description": "Qstat of Job",
    "ScriptLocation": "/stage/GenericActions/qstat.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  }
]
```



```
    }
  },
  {
    "Name": "Tracejob",
    "DisplayName": "Tracejob of Job",
    "Description": "Tracejob of Job",
    "ScriptLocation": "/stage/GenericActions/tracejob.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  },
  {
    "Name": "Distributed Tracejob",
    "DisplayName": "Distributed Tracejob of Job",
    "Description": "Distributed Tracejob of Job",
    "ScriptLocation": "/stage/GenericActions/dtj.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  },
  {
    "Name": "Node Status",
    "DisplayName": "Node status of cluster",
    "Description": "Node status of cluster",
    "ScriptLocation": "/stage/GenericActions/nodestatus.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": [ ]
    }
  }
],
},
{
  "hpccluster-2": [{
    "Name": "Queue Hold",
    "DisplayName": "Queue hold a job",
    "Description": "Queue hold a job",
    "ScriptLocation": "/stage/GenericActions/qhold.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  },
  {
    "Name": "Queue Release",
    "DisplayName": "Queue release a job",
    "Description": "Queue release a job",
    "ScriptLocation": "/stage/GenericActions/qrls.py",
    "Arguments": {
```

```

    "jobid": {
      "type": "string",
      "DisplayName": "Job ID"
    },
    "required": ["jobid"]
  },
  {
    "Name": "Suspend a job ",
    "DisplayName": "Suspend a job",
    "Description": "Suspend a job",
    "ScriptLocation": "/stage/GenericActions/qsig.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  },
  {
    "Name": "Delete jobs ",
    "DisplayName": "Delete job(s)",
    "Description": "Delete job(s)",
    "ScriptLocation": "/stage/GenericActions/qdel.py",
    "Arguments": {
      "jobid": {
        "type": "string",
        "DisplayName": "Job ID"
      },
      "required": ["jobid"]
    }
  }
]
}

```

## Execution Script

The generic action script is a python script that is responsible for executing the generic action, using the information entered by the user (defined by the generic action JSON file). You can directly edit this script, taking full advantage of Python to add further inspection and complexity to the execution of the generic action. In this example, the python script will create a subprocess to execute the command entered by the user.

```

import subprocess, sys, os

def execcmd(cmd):
    try:
        p = subprocess.Popen(cmd, shell=True, stdout=subprocess.PIPE,
stderr=subprocess.STDOUT)
        data = ""
        for line in p.stdout.readlines():
            data = data + line
    except:
        errTtype = sys.exc_type
        try:
            errName = errTtype.__name__
        except AttributeError:
            errName = errType
        data = "Error: " + str(errName) + " --- " + str(sys.exc_value)
    return data
cmd = "/opt/pbs/bin/qstat -fx " + sys.argv[2]


```

```
print (cmd)
print execcmd(cmd)
sys.stdout.flush()
```

## 9.1.12 Map a File Extensions to an Icon

Map icons to a file extension in the Access Web application.

Access Web displays customized file types and icons when viewing remote files.



<input type="checkbox"/>	Name	Created On	Owner	File Size	
<input type="checkbox"/>	archive-1544462297905	12/10/2018, 10:50:01 PM	pbsadmin	6 Bytes	
<input type="checkbox"/>	Cube_Files	12/10/2018, 10:33:12 PM	pbsadmin	8 KB	
<input type="checkbox"/>	rod.h3d	12/11/2018, 3:29:48 PM	pbsadmin	6.21 MB	
<input type="checkbox"/>	archive-1544462297905.zip	12/10/2018, 10:49:27 PM	pbsadmin	15.59 KB	
<input type="checkbox"/>	Cube_Files.zip	12/4/2018, 8:15:19 PM	pbsadmin	6.26 MB	
<input type="checkbox"/>	CUBE_0001.rad	12/10/2018, 10:50:01 PM	pbsadmin	292 Bytes	
<input type="checkbox"/>	CUBE_0000.rad	12/10/2018, 10:50:01 PM	pbsadmin	66.23 KB	
<input type="checkbox"/>	AltairAccessWeb_Information.pdf	12/11/2018, 3:29:22 PM	pbsadmin	148.87 KB	

Figure 18: File Icon Mapping

The file icons are mapped to a file extension in the JSON file, `fileextensions.json` and the location of this file is at `PA_HOME/config/pa/`

The file icon image file must be placed at the location `PA_HOME/config/pa/fileicons/`

Below is an example of a file extension and icon that has been mapped in `fileextensions.json` located at `PA_HOME/config/pa/`:

```
{
  "fileextension":
  [
    {
      "name": "pdf",
      "displayText": "Acrobat",
      "icon": "icon_pdf.png"
    },
    {
      "name": "zip",
      "displayText": "Archive",
      "icon": "icon_zip.png"
    },
    {
      "name": "h3d",
      "displayText": "H3D",
      "icon": "hvpctrl-32.gif"
    }
  ]
}
```

The XML attributes of the file extension mapping file is as follows:

*name*

The file extension.

*displayText*

Access Web will display this as the files type.

*icon*

Icon image file located at `PA_HOME/config/pa/fileicons/`

## 9.1.13 Set Maximum Page Size for Files

Set the maximum file size (in bytes) for displaying a file in a single page.

The default is 5000 bytes.



**Note:** You must have administrative privileges to change the file page size.

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/pa/`
3. Open the `configuration.json` file and change the value of the `filechunksize`.

```
"filechunksize": 5000
```

## 9.1.14 Install and Configure SSL Certificate

Install and configure SSL certificate on the server to secure communication.

If you do not have a valid domain certificate for your site, you need to create a Certificate Signing Request (CSR) and order your certificate.

1. You should have received a `your_domain_name.pem` file from Certificate Authority which contains both your primary certificate and the intermediate certificate. If you have that `.pem` file, you can skip to Step 4.
2. Download the intermediate (`Intermediate.crt`) and your primary certificate (`your_domain_name.crt`) files.
3. Copy these files, along with the `.key` file you generated when creating the CSR, to the directory on the server where the certificate and key files are kept.
4. Concatenate the primary certificate file (`your_domain_name.crt`) and the intermediate certificate file (`Intermediate.crt`) into a single `.pem` file by running the following command:

```
cat your_domain_name.crt Intermediate.crt >> bundle.crt
```

5. Navigate to `PA_HOME/config/api_gateway/`
6. Open the `nginx.conf` file and update the following line:

```
server
{
    ssl      on;
    ssl_certificate      /etc/ssl/your_domain_name.pem; (or bundle.crt)
    ssl_certificate_key  /etc/ssl/your_domain_name.key;
}
```

- `ssl_certificate` should be your primary certificate combined with the intermediate certificate (`your_domain_name.crt`).
- `ssl_certificate_key` should be the `.key` file generated when you created the CSR.

**7. Restart Access Web by entering the following command:**

```
service pbsworks-pa restart
```

## 9.1.15 Enable Mobile Notification Service

Enable mobile notification service in Access Web so that the job status notification is displayed in Access Mobile.

You must stop Access Web before enabling mobile notification service. For more information about stopping Access Web, see [Access Web Service Commands](#).

1. Login to the machine as root where Access Web is installed.
2. Navigate to `PA_HOME/config/shared/`
3. Open the `deployment.ini` file.
4. Add the following line under `pa_deploy_options` section:

```
option=("mobile_notification_service")
```

5. Start Access Web using the following command:

```
service pbsworks-pa start
```

## 9.2 Configure PBS Application Services

Information about configuration files, verification of your PAS installation, post-installation configuration and tasks.

### 9.2.1 Enable PBS Job History

Enable the PBS Professional job history status.

PAS does not automatically set the PBS Professional `job_history_enable` attribute to `true`.

Therefore, to enable job history use the PBS Professional command:

```
qmgr -c 'set server job_history_enable=True'
```

### 9.2.2 Verify the Installation of PBS Application Services

Verify PAS installation and server status.

1. Open any of the supported browsers.
2. Enter PAS URL (`https://<hostname>:<port>/pas`)



**Note:** The valid PAS port is 5243.

The browser will display the PAS information.

For example, if you type `https://<hostname>:5243/pas` the following information will be displayed:

## PBSWorks Application Services

**Version: 2018.4.0**

**Build: 20181209**

[REST Services](#)

**Copyright 2003 - 2018 Altair Engineering, Inc. All rights reserved.**

## 9.2.3 Configure System Zip Utility

Configure PAS to use the system compression utility.

By default, PAS uses zip 3.0 utility to compress the file.

### Configure System Zip Utility to Compress by Updating Python Script

Enable the system zip utility to compress the files by updating the Python Script.

1. As root, open the `FileCompress.py` file located at `PA_EXEC/pas/scripts/`
2. Before `zipcmd = [zip_full_path_normalized] + ['-rq'] + [compressionSpeed]` line, add the following: `zip_full_path_normalized = '/usr/bin/zip'`

The `/usr/bin/zip` is the path where the system zip utility is located.



**Note:** If you do not specify the system zip utility path, then PAS zip utility will be used to compress the files.

### Configure System Zip Utility to Compress without Updating Python Script

Enable the system zip utility to compress the files without updating the python script.

1. As root, navigate to `PA_EXEC/pas/bin/Linux-x86_64`
2. Rename the existing zip utility to `zip_backup`.
3. Create a soft link for zip with the system zip utility: `ln -s /usr/bin/zip zip`

The `/usr/bin/zip` mentioned, is the path where the system zip utility is located.



**Note:** Restore the permission of the changed zip utility.

## 9.2.4 Configure System Unzip Utility


Configure PAS to use the system uncompression utility.

By default, PAS uses unzip 6.0 utility to uncompress the file.

### Configure System Unzip Utility to Uncompress by Updating Python Script

Enable the system unzip utility to uncompress the files by updating the Python Script.


1. As root, open the `FileUncompress.py` file located at `PA_EXEC/pas/scripts/`
2. Before `files_list_cmd = [unzip_full_path_normalized] + ['-lqq'] + [archive]` line, add the following: `unzip_full_path_normalized = '/usr/bin/unzip'`  
The `/usr/bin/unzip` is the path where the system unzip utility is located.

 **Note:** If you do not specify the system unzip utility path, then PAS unzip utility will be used to uncompress the files.

## Configure System Unzip Utility to Uncompress without Updating Python Script

Enable the system unzip utility to uncompress the files without updating the python script.

1. As root, navigate to `PA_EXEC/pas/bin/Linux-x86_64`
2. Rename the existing unzip utility to `unzip_backup`.
3. Create a soft link for unzip with the system unzip utility: `ln -s /usr/bin/unzip unzip`  
The `/usr/bin/unzip` mentioned, is the path where the system unzip utility is located.

 **Note:** Restore the permission of the changed unzip utility.

## 9.2.5 Configurable Parameters

PAS stores its configuration data in a file called `server.conf`.

The default location of this file is: `PA_HOME/config/pas/conf`

All parameters are stored in `key=value` pairs. Spaces and tabs are preserved (as spaces) and providing quotes around values is optional. As spaces are preserved, do not use `key = value` (notice the space surrounding the `=`) unless spaces are intentional. Empty lines beginning with a comment symbol (i.e., `#`) are ignored.

## Standard Configuration Parameters

Standard configuration parameters and its default values in PAS Server.

The following table describes the standard configuration parameters:



Table 3: Standard Configuration Parameters

Parameter	Description	Default Value
LOGGING_CONFIG_FILE_RELATIV	The PAS logging configuration file (Log4J) which is used to configure logging levels. Since the PAS uses Log4J as its logging and tracing API, you can access additional information on Log4J via the Apache Log4J website at <a href="http://logging.apache.org/log4j">http://logging.apache.org/log4j</a>	server-log.xml
ADMIN_USER	The PAS administration account (for example, pbsadmin) that has complete control over the PAS Server. This account is required for any remote PAS administration tasks.  On Linux, the administration account can be a non-privileged user account that has been granted manager status for PBS Professional, and can be changed after installation.	pbsadmin
LOGIN_MODULE_NAME	The PAS authentication module. PAS uses the Java Authentication and Authorization Service (JAAS) as its authentication abstraction layer.	UnixLogin
STAGE_ROOT	The PAS file staging location.  This directory must exist prior to the installation of PAS. The staging directory is where the necessary files are transferred after job submission (via a client for example, PBS Portals or Access Web), but prior to the portal submitting the job to PAS for transfer to PBS Professional for execution. When PBS Professional selects the	/stage

Parameter	Description	Default Value
	<p>job for execution, the files are staged in to the execution host from the staging directory. Upon job completion, any files the job wants to retain are staged-out by PBS Professional to the staging directory, and the client retrieves them from there when it is ready to do so. Customer written portals may choose to do the same, but are not required to do so.</p> <p>The value of STAGE_ROOT can be set to point to the user's home directory by using the variable <code>\$USER_HOME</code> (for example: <code>\$USER_HOME/stage</code>) after installation.</p>	
FILE_TRANSFER_PROTOCOL	The PAS file transfer mechanism.	http
FILE_EXPIRATION_TIME	The PAS stage area file expiration time. That is, the age in days after which data is removed from the staging directory (as defined by the STAGE_ROOT parameter) and its subdirectories with the exception of the profiles directory. Files in the profiles directory are never removed by PAS.	14
ZIP_COMPRESSION_SPEED	<p>Compression speed for the default PAS and system compression utility.</p> <p>The compression utility uses this value to compress the files. The zip compression value -1 being fastest and -9 being slowest.</p>	-1
MAX_LIST_FILES_COUNT	The number of files to be returned by the FileList API. Allows sites to impose limits on	1000

Parameter	Description	Default Value
	how many files are returned to improve the response time of Access Web remote file operations.	
BUFFER_SIZE	Maximum buffer size for file operations in bytes.	65536

## Advanced Configuration Parameters

Optional parameters available to you that are appropriate for advanced configurations in PAS Server.

The following table describes the advanced configuration parameters:

Table 4: Advanced Configuration Parameters

Parameter	Description	Default Value
PYTHON_PATH	<p>The PAS Python binary. PAS requires that each PBS execution host provide a standard Python binary. The full path to your systems Python binary can be changed here.</p> <p>The PBS Professional daemon pbs_mom will look for a binary called pbs_python in PBS_EXEC/bin. If using custom actions or any other operations that involve the pbs_mom accessing this pbs_python (aka python binary) there may be problems if the python libraries are not located in the standard locations relative to PBS_EXEC/bin/pbs_python. If Python is installed elsewhere a link to (Linux)the actual python binary must exist as PBS_EXEC/bin/pbs_python.</p>	\$PBS_EXEC/bin/pbs_python

Parameter	Description	Default Value
PBS_DATA_REFRESH_TIME	Time interval in minutes to fetch PBS related data like qmgr, queues etc	15
SSH_LOGGER_ENABLE	SSH Log enabling	False
STAGE_ROOT_TEMP_DIR	Temporary folder for zip/download API	/tmp The default path can be changed to \$STAGE_ROOT/tmp
JSON_SCHEMA_VALIDATION	JSON Schema Validation	False

## 9.2.6 Configure PBS Resources

Configure PBS resources in PAS.

You can install PAS on a separate machine from the PBS Professional Server as a failover server. The PBS Professional *flatuid* attribute must be set to True. This attribute specifies whether, for each user, the username at the submission host must be the same as the one at the Server host. The username at the Server host must always be the same as the username at the execution host. When *flatuid* is set to True, the Server assumes that UserA@host1 is the same as UserA@host2. Therefore, if *flatuid* is True, UserA@host2 can operate on UserA@host1's job. Follow these steps to set *flatuid* to True. These steps must be performed either by root or a PBS manager.

1. At the command line, enter the command:

```
qmgr -c "print server"
```

2. If the attribute *flatuid* is equal to False or is not set (you do not see it in the output from the print server command), then set the value to True by issuing the command:

```
qmgr -c "set server flatuid=true"
```

## 9.2.7 Configure PAS Server Logging Behavior

Configure logging behavior for certain functional aspects of PAS, such as file operations or job submission to troubleshoot errors.

The PAS logging behavior can be defined in `server-log.xml` file located at `PAS_HOME/config/pas/conf/`

The functional areas are defined by the `<category>` element and the existing categories in the `server-log.xml` are useful as a basic configuration, are more course-grained, and provide the default PAS

logging. The default logging level is set to `info` providing informational messages that highlight the progress of the application at a coarse-grained level.

To configure the level of logging, edit the `server-log.xml` file and set the `<priority value>` attribute of a particular `<category>` to one of the following values:

- `off` - has the highest possible rank and is intended to turn off logging.
- `fatal` - very severe error events that will presumably lead the application to abort.
- `error` - error events that might still allow the application to continue running.
- `warn` - potentially harmful situations.
- `info` - informational messages highlighting the progress of the application at a coarse-grained level.
- `debug` - fine-grained informational events that are most useful to debug an application.
- `trace` - finer-grained informational events than the `DEBUG`.
- `all` - the lowest possible rank and is intended to turn on all logging.

```
<category name="category">
  <priority value="<logging_level>" />
</category>
```

## Remote File operations, Job submission, and Job Status

Configure logging behavior for remote file operations, job submission, and job status.

The logging for this category is relevant for the communication with the EIFL server.

1. Navigate to `PA_HOME/config/conf/`
2. Update `server-log.xml` with the following XML:

```
<category name=" com.altair.gw.aif.cli.implementation.BasicCommandsImpl">
  <priority value="debug" />
</category>
```

3. Update `server-log.xml` to get detailed troubleshooting information for the job status:

```
<category name="com.altair.gw.aif.pbs.ifl.implementations.PbsEiflWs">
  <priority value="debug" />
</category>
```

The following are examples of the type of messages that will be logged if debugging is enabled for the job status operation:

Table 5: Logging Messages for Communication with the EIFL Server

Event	Message
Before a web service API call to the EIFL server	"Success getting eifl server port <port>"
After an EIFL web service API call to the EIFL server	"Success returning from eifl.waitExit(), port is <port>"

Event	Message
For a job status request, before the web service API call to the EIFL server	"qstatJobs(): Success getting eifl server port <port>"
After an EIFL web service API call to the EIFL server	"qstatJobs(): Success returning from eifl.waitExit(), port is <port>"
For the get detailed job status operation, if an error occurs, the error code will be logged as returned by PBS	"PbsEiflWs.java getErrorCode(): pbs error code is <pbsErrorCodeStr>"

## File Operations (local and remote)

Configure logging behavior for file operations (local and remote).

1. Navigate to `PA_HOME/config/conf/`
2. Update `server-log.xml` to change the *priority* value:

```
<category name="com.altair.gw.aif.fileop.implementation.FileOperations">
  <priority value="debug" />
</category>

<category name="com.altair.gw.aif.fileop.implementation.FileOperationsHelper">
  <priority value="debug" />
</category>
```

## Job Submission

Configure logging behavior for job submission.

1. Navigate to `PA_HOME/config/conf/`
2. Update `server-log.xml` to get detailed logging information about user inputs and to see how long it takes to execute a submission request by adding the following XML:

```
<category name=" com.altair.gw.aif.rest. RESTJobsPortImpl">
  <priority value="debug" />
</category>
```

3. Update `server-log.xml` to get information about the process of creating PBS job attributes from user inputs and the application definition by adding the following XML:

```
<category name=" com.altair.gw.aif.rest.util.PASNextGenJobUtils">
  <priority value="debug" />
</category>
```

PAS supports multiple adapters to communicate with the workload manager.

4. If the SSH adapter is enabled for the communication with the PBS cluster, add the following XML to the `serverlog.xml` file to troubleshoot job submission:

```
<category name=" com.altair.gw.aif.ssh.implementation. SSHImplementation">
  <priority value="debug" />
</category>
```

The following are examples of the type of messages that will be logged if debugging is enabled for this class:

Table 6: Logging Messages for Job Submission

Event	Message
Before job submission, PAS will record the job name and the resources requested.	"PbsJobFactory.getPbsJob():job name = <job name>, resourceList to String: <job resources>"
Once the job is submitted, PAS will record the job id.	"JobSubmit success. Job id: <jobId>"
For job status requests, PAS will log any empty responses.	"HpcpPbsAdapter.jobList(): qstat is empty"

## Job Submission and Status

Configure logging behavior for job submission and status.

1. Navigate to PA\_HOME/config/conf/
2. Update server-log.xml with the following XML:

```
<category name="com.altair.gw.aif.pbs.ifl.responses.JobsStatus_Response">
  <priority value="debug" />
</category>

<category name=" com.altair.gw.aif.pbs.ifl.responses.PBSObjectStatus">
  <priority value="debug" />
</category>
```

Enabling a debugging level for the "PbsJobsPortImpl" class also provides the ability to determine the IP address of a client request for PAS job submission services.

For each job submission API call, a log record is created having the API name, requesting user name, and remote host. For example,

```
Entered getJobs(). User: <username>, client host: '<clientHost>'
```

## Application Definitions

Configure logging behavior for application definitions.

1. Navigate to PA\_HOME/config/conf/

2. Update `server-log.xml` to get detailed logging information about application definitions by adding the following XML:

```
<category name="com.altair.gw.aif.converter">
  <priority value="debug" />
</category>
```

## Dynamic Application Refresh Script

Configure logging behavior for dynamic application refresh script.

1. Navigate to `PA_HOME/config/conf/`
2. Update `server-log.xml` to get detailed logging information about dynamic application refresh script by adding the following XML:

```
<category name="com.altair.gw.aif.applications.utils.DynamicApplicationBuilder">
  <priority value="debug" />
</category>
```

## During the Job Status Retrieval

Configure logging behavior to troubleshoot errors during the job status retrieval.

1. Navigate to `PA_HOME/config/conf/`
2. Update `server-log.xml` to get user information and the total time of the PAS server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest.RESTJobsPortImpl">
  <priority value="debug" />
</category>
```

3. To get job details information coming from the Workload Manager to PAS and details about response from PBS, add the following XML to the `server-log.xml` file:

```
<category name="com.altair.gw.aif.pbs.ifl.responses.JobsStatus_Response">
  <priority value="debug" />
</category>

<category name="com.altair.gw.aif.pbs.ifl.responses.PBSObjectStatus">
  <priority value="debug" />
</category>
```

4. If the SSH adapter is enabled for the communication with the PBS cluster, add the following XML to the `server-log.xml` file to troubleshoot job submission:

```
<category name="com.altair.gw.aif.ssh.implementation.SSHImplementation">
  <priority value="debug" />
</category>
```

This will log the job status attributes as returned to the PAS Server from the script executed through the SSH channel.



## File Operations Execution (Local and Remote) and File Download

Configure logging behavior to troubleshoot errors during the file operations execution (local and remote) and file download.

1. Navigate to `PA_HOME/config/conf/`
2. Update the `server-log.xml` to get more details on user information and the total time of the PAS server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest.RESTFilePortImpl">  
  <priority value="debug" />  
</category>
```

3. Update the `server-log.xml` file to get details about the local and remote file operation (parameters, current working directory, the operation result) at the PAS server level by adding the following XML:

```
<category name="com.altair.gw.aif.fileop.implementation. FileOperations">  
  <priority value="debug" />  
</category>
```

4. Update the `server-log.xml` file to get details about the local file operation by adding the following XML:

```
<category name="com.altair.gw.aif.fileop.implementation. FileOperationsHelper">  
  <priority value="debug" />  
</category>
```

5. Update the `server-log.xml` file to get details about the remote file operations by adding the following XML:

```
<category name=" com.altair.gw.aif.process.ProcessWrapper">  
  <priority value="debug" />  
</category>
```

With this category we'll see more details related to user impersonation when we create the process as specific user.

6. If the SSH adapter is enabled for the communication with PBS cluster, it is possible to enable the logging of additional information related to the SSH tunnel. For the troubleshooting and debugging of remote file operations add the following XML to the `server-log.xml` file:

```
<category name="com.altair.gw.aif.fileop.implementation.cli. RemoteFileOpsTunnel-  
Based">  
  <priority value="debug" />  
</category>
```

It will show the command and parameters passed to the SSH tunnel and what is the result of the communication with the remote host coming back to the PAS Server.

7. Update the `server-log.xml` file to see more information about the file download by adding the following XML:

```
<category name=" com.altair.gw.aif.fileop.implementation. FileDownloadModel">  
  <priority value="debug" />  
</category>
```

## Application Definition Related Errors

Configure logging behavior to troubleshoot application definition related errors.

1. Navigate to `PA_HOME/config/conf/`
2. Update the `server-log.xml` to get more details on user information and the total time of the PAS server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest. ApplicationDefinitionService">  
  <priority value="debug" />  
</category>
```

3. If any errors indicate the failure of communication with the file system, add the following XML to the `server-log.xml` file to log more details about application definition reading and writing from the file system:

```
<category name=" com.altair.gw.aif.applications.utils. ApplicationsRepository">  
  <priority value="debug" />  
</category>
```

Application definitions are cached for better performance. If any discrepancy between the application definition in the upstream products and the file system is observed, the cache debug logging should be enabled to make sure the PAS Server is providing the most current application definition.

4. Update the `server-log.xml` to get more information on cache debug logging by adding the following XML:

```
<category name=" com.altair.gw.aif.utils.generic. CacheManager">  
  <priority value="debug" />  
</category>
```

## User Profile

Configure logging behavior to troubleshoot user profile errors.

1. Navigate to `PA_HOME/config/conf/`
2. Update the `server-log.xml` to get more details on user information and the total time of the PAS Server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest. ProfileService">  
  <priority value="debug" />  
</category>
```

## Server Registration

Configure logging behavior to troubleshoot server registration errors.

1. Navigate to `PA_HOME/config/conf/`
2. Update the `server-log.xml` to get more details on user information and the total time of the PAS Server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest. ServerService">  
  <priority value="debug" />  
</category>
```

## User Account

Configure logging behavior to troubleshoot user account related errors.

1. Navigate to `PA_HOME/config/conf/`
2. Update the `server-log.xml` to get more details on user information and the total time of the PAS Server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest. UserService">  
  <priority value="debug" />  
</category>
```

## Session Errors

Configure logging behavior to troubleshoot session related errors.

1. Navigate to `PA_HOME/config/conf/`
2. Update the `server-log.xml` to get more details on user information and the total time of the PAS Server operation by adding the following XML:

```
<category name="com.altair.gw.aif.rest. SessionService">  
  <priority value="debug" />  
</category>
```

## 9.2.8 Configure JVM Performance

The Java Virtual Machine (JVM) heap size of PAS may need to be adjusted. Currently, the default JVM heap size is 1024 MB. If OutOfMemory errors or warnings are reported in the PAS log file, this value should be increased. It can be increased in multiples of 256 MB.

On Linux, the Java heap size default is stored in a script file called `setenv.sh`. The location of this file for a typical installation of PAS is: `PA_EXEC/pas/scripts`

Modify the JVM argument `-Xmx1024m`. Increase the 1024 value.

This is the area of `setenv.sh` that will need to be modified (this file is too large to show in its entirety):

```
JAVA_OPTS="$JAVA_OPTS -Xmx1024m -XX:PermSize=128m -XX:MaxPermSize=128m"
```

The Access Web service will need to be restarted for the changes to be reflected.

## 9.3 Configure the Remote Session Component

Configurations when you install remote session component.

### 9.3.1 Change the Session Timeout Value for Interactive Applications

Change the duration of a remote session so that it remains active.

The default remote session timeout is 30 minutes. The session is killed if the user does not access the remote session within this time.


1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/displaymanager/`
3. Edit the file `dmrest.properties`
4. Update the value of `jobaction.expiry_time` in seconds.

```
#session expiry time(seconds)
jobaction.expiry_time=1800
```

### 9.3.2 Change the Job Submission Host for Interactive Applications

Change the hostname or IP address of the machine from which jobs are being submitted.

Interactive jobs connect to the remote session service to provide job status updates. When the hostname or IP address of the machine where Access Web is installed changes, the remote session service must be updated with the new value.

 **Note:** This hostname or IP address must be accessible from all execution hosts.


1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/displaymanager/`
3. Edit the file `dmrest.properties`
4. Update the value of `jobsub.monitor.host` to the new hostname or IP address.

```
#Enables handling asynchronous job updates.
jobsub.monitor.host=dm-05
jobsub.monitor.port=4909
```

## 9.3.3 Change the Job Submission Port for Interactive Applications

Change the port that the remote session component listens on for job status updates.

Interactive jobs connect to the remote session service to provide job status updates. Modify the default port that the remote session component listens on for these updates if the default port is already being used by a different process.

 **Note:** The default port that the Interactive component listens on for job status updates is 4909.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/config/displaymanager/`
3. Edit the file `dmrest.properties`
4. Update the value of `jobsub.monitor.port` to the new port number.

```
#Enables handling asynchronous job updates.  
jobsub.monitor.host=blrvml4  
jobsub.monitor.port=4909
```

## 9.3.4 Configure GPU Limits when the Number of GPUs Change

Reconfigure the remote session component when GPUs are added or removed from a cluster.

The installer configures all the node and cluster limits for GPUs. Follow the below procedure in situations where these limits might change (e.g. a node going down or being removed, adding new graphical nodes post-installation, etc.)

### Modify the Cluster GPU Limit

Modify the available number of GPUs in a cluster when graphical nodes or devices are added or removed.

A queue (`iworkq`) is created when the remote session installer is run on the PBS Server. This queue exclusively handles interactive job requests. An attribute is set on the queue which limits the number of GPUs that can be allocated to jobs queued in or running from this queue. Modify the value of this attribute to accommodate any changes in the limit due to the addition or removal of graphical nodes or devices.

1. Login to the machine hosting the PBS Server as root or a user with sudo permissions.
2. Enter the command:

```
qmgr -c "p q iworkq"
```

Output similar to the below is displayed.

```
#  
# Create queues and set their attributes.  
#
```

```
#  
# Create and define queue iworkq  
#  
create queue iworkq  
set queue iworkq queue_type = Execution  
set queue iworkq Priority = 150  
set queue iworkq max_queued_res.ngpus = [o:PBS_ALL=5*]  
set queue iworkq resources_max.ngpus = 1  
set queue iworkq resources_min.ngpus = 1  
set queue iworkq enabled = True  
set queue iworkq started = True
```

The value of `max_queued_res.ngpus` is the available GPU limit for the cluster. This is the cumulative number of all the GPUs available in the cluster managed by the PBS server.

3. Change the value of `max_queued_res.ngpus` using the command:

```
qmgr -c "set queue iworkq max_queued_res.ngpus= [o:PBS_ALL=<GPUS>]"
```

where `<GPUS>` is the new number of GPUs available in the cluster.

## Modify the Node GPU Limit

Modify the available number of GPUs for any execution hosts when graphical nodes or devices are added or removed.

When the remote session installer is run on the PBS MoM, an attribute is set on each graphical node which defines the number of available GPUs for the node. Modify the value of this attribute to accommodate any changes in the limit due to the addition or removal of GPUs.



**Note:** This must be done for any execution hosts that have had graphical nodes or devices added or removed.

1. Enter the command:

```
pbsnodes -a
```

Output similar to the below is displayed.

```
interactive-05  
  Mom = interactive-05.cad.company.com  
  Port = 15002  
  pbs_version = PBSPro_13.1.3.170747  
  ntype = PBS  
  state = free  
  pcpus = 32  
  resources_available.arch = linux  
  resources_available.host = interactive-05  
  resources_available.mem = 131727204kb  
  resources_available.ncpus = 32  
  resources_available.ngpus = 3  
  resources_available.vnode = interactive-05  
  resources_assigned.accelerator_memory = 0kb  
  resources_assigned.mem = 0kb  
  resources_assigned.naccelerators = 0  
  resources_assigned.ncpus = 0  
  resources_assigned.netwins = 0  
  resources_assigned.ngpus = 0  
  resources_assigned.vmem = 0kb  
  resv_enable = True
```

```
sharing = default_shared
```

The value of `resources_available.ngpus` is the available GPU limit for the node, this is the cumulative number of all the graphical devices available for a particular node.

2. Change the value of `resources_available.ngpus` using the command:

```
qmgr -c "set node <VNODENAME> resources_available.ngpus=<NGPUS>"
```

where `<VNODENAME>` is the name of the node and `<NGPUS>` is the new number of GPUs available on this execution host.

## 9.4 Configure Results Visualization Service

This sections provides relevant information for the administrator in configuring Results Visualization Service (RVS).

### 9.4.1 Configure HyperWorks Location

Configure Access Web with HyperWorks location, to enable results visualization capabilities.

Follow these steps when the HyperWorks location was not specified while installing Access Web 2019.1.

1. Edit the file at `PA_HOME/config/resultservice/config/site_config.xml`
2. Change the value of the `location` to the location of HyperWorks.

```
<Products>
  <Product id="ALTAIR_HYPERWORKS" defaultVersion="2017.2">
    <Version id="2017.2" location="HW_EXEC/altair/" />
  </Product>
</Products>
```

3. Restart Access Web Service.

### 9.4.2 Configure HyperWorks Licenses

In the license server that we specify during the Access Web installation should include HWHyperMath and HWHyperViewTrans features. This enables to visualize the supported result files.

You can configure the RVS license in these two ways:

- To add the HyperWorks license in Access Web license file. Refer [Add HyperWorks Licenses to the Access Web License File](#).
- To point RVS license to HyperWorks license server. Refer [Point RVS to the HyperWorks License Server](#).

### Add HyperWorks Licenses to the Access Web License File

Add HyperWorks licenses to the Access Web license file to enable RVS capabilities.

Open your HyperWorks license file to copy the HWHyperMath and HWHyperViewTrans features to the Access Web license file.

1. Login to the machine hosting Access Web.
2. Open the Access Web license configuration file at `PA_HOME/config/license/app.properties`
3. Locate the following line.

```
pbsworks.license.server=port@LICENSE_SERVER_HOSTNAME
```

Where `LICENSE_SERVER_HOSTNAME` is the hostname of the license server.

4. Login to the Access Web license server specified in the previous step.
5. Open the Access Web license file at `/usr/local/altair/licensing14.0/altair_lic.dat`



6. Copy the HWHyperMath and HWHyperViewTrans features from the HyperWorks license file to the Access Web license file `altair_lic.dat`.

7. Restart the LMX license server.

```
/etc/init.d/altairlmxd restart
```

8. Kill any HyperMath sessions that exists in the Access Web machine.

```
kill -9 <process id>
```

This will enable the RVS capabilities of Access Web.

## Point RVS to the HyperWorks License Server

To enable RVS capabilities without merging the HyperWorks licenses with the Access Web license so that you can keep these licenses separate, point RVS to the Hyperworks License Server.

1. Open the file at `PA_EXEC/resultservice/scripts/setenv.sh`

2. Update the Altair license path to point to the HyperWorks license server in this format

```
port@hostname.
```

```
export ALTAIR_LICENSE_PATH=port@hostname
```

3. Kill any HyperMath sessions that exists in the Access Web machine.

```
kill -9 <process id>
```

This will enable the RVS capabilities of Access Web.

## Licensing System of HyperWorks Units

RVS use Altair patented licensing system of HyperWorks Units (HWU).

Animation request will checkout 6 HWU and Plot request will checkout 10 HWU on the server. Units are leveled for the same user but stacked for different users. They are checked out only during the results extraction on the server. As soon as the results are extracted, units are immediately returned to the licensing pool. The client side rendering of plot and animation results are covered by PBSA licensing and does not require any extra units.

### 9.4.3 Configure Solver File Readers

You can activate the result data files such as Abaqus, CFX, Fluent, and STAR-CCM+ that are not supported by default.

Solver log file readers are already present in the standard installation of HyperWorks, but they are not activated by default. Enable them by activating a HyperWorks plotting preference file.

## Activate the Abaqus Reader

Activate the Abaqus reader so that Abaqus data files can be read by HyperWorks.

1. Edit the file at `HW_EXEC/hw/prefinc/preferences_common_plot.mvw`

2. Locate the following line of code:

```
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

3. Add the following line of code directly before the code referenced in the previous step to activate the Abaqus reader:

```
*RegisterExternalReader({external_readers_dir + "/hgabaqus.exe"}, "", "", ascii)
```

The code looks like this when you are done.

```
*RegisterExternalReader({external_readers_dir + "/hgabaqus.exe"}, "", "", ascii)
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

## Activate the CFX Reader

Activate the CFX reader so that CFX data files can be processed by HyperWorks.

1. Edit the file at HW\_EXEC/hw/prefinc/preferences\_common\_plot.mvw

2. Locate the following line of code:

```
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

3. Add the following line of code directly before the code referenced in the previous step to activate the CFX reader:

```
*RegisterExternalReader({external_readers_dir + "/hgCFX.exe"}, "", "", ascii)
```

The code looks like this when you are done.

```
*RegisterExternalReader({external_readers_dir + "/hgCFX.exe"}, "", "", ascii)
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

## Activate the Fluent Reader

Activate the Fluent reader so that Fluent data files can be processed by HyperWorks.

1. Edit the file at HW\_EXEC/hw/prefinc/preferences\_common\_plot.mvw

2. Locate the following line of code:

```
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

3. Add the following line of code directly before the code referenced in the previous step to activate the Fluent reader:

```
*RegisterExternalReader({external_readers_dir + "/hgfluent.exe"}, "", "", ascii)
```

The code looks like this when you are done.

```
*RegisterExternalReader({external_readers_dir + "/hgfluent.exe"}, "", "", ascii)
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

## Activate the STAR-CCM+ Reader

Activate the STAR-CCM reader so that STAR-CCM data files can be processed by HyperWorks.

1. Edit the file at HW\_EXEC/hw/prefinc/preferences\_common\_plot.mvw

2. Locate the following line of code:

```
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

3. Add the following line of code directly before the code referenced in the previous step to activate the STAR-CCM reader:

```
*RegisterExternalReader({external_readers_dir + "/hgStarCCM.exe"}, "", "", ascii)
```

The code looks like this when you are done.

```
*RegisterExternalReader({external_readers_dir + "/hgStarCCM.exe"}, "", "", ascii)
```

```
*RegisterExternalColumnReader({external_readers_dir + "/hgtextcolumn.exe"})
```

4. Copy the hgstarccm executable from the user download area to `HW_EXEC/io/abf_readers/bin/linux64`

## 9.4.4 Supported Result File Types

The supported result file types supported by Access Web for visualizing Plot and Animation.

Table 7: Supported Result File Types for Plotting

Results File Format	Plot Data	Animation Data	Default TOC Type
<b>RadioSS Bulk</b>			
*.op2	Yes	Yes	Animation
*.h3d	Yes	Yes	Animation
*.res	Yes	NA	Plot
*.pch	Yes	NA	Plot
*.gz	Yes	Yes	Animation
<b>RadioSS Block</b>			
*A00#	Yes	Yes	Animation
*.T# #	Yes	NA	Plot
*.gz	Yes	Yes	Animation
<b>Optistruct</b>			
*.op2	Yes	Yes	Animation
*.h3d	Yes	Yes	Animation
*.res	Yes	NA	Plot
*.pch	Yes	NA	Plot
*.hgdata	Yes	NA	Plot

Results File Format	Plot Data	Animation Data	Default TOC Type
<b>MotionSolve</b>			
*.mrf	Yes	NA	Plot
*.plt	Yes	NA	Plot
*.h3d	Yes	Yes	Animation
*.maf	Yes	NA	Plot
<b>Abaqus</b>			
*.odb	Yes	Yes	Animation
*.dat	Yes	NA	Plot
*.out	Yes	NA	Plot
<b>ADAMS</b>			
*.req	Yes	NA	Plot
*.res	Yes	NA	Plot
*.nam	Yes	NA	Plot
*.rsp	Yes	NA	Plot
*.shl	Yes	NA	Plot
*.sta	Yes	NA	Plot
<b>Ansys</b>			
*.rst	Yes	Yes	Animation
*.rth	Yes	Yes	Animation
*.rth	Yes	Yes	Animation
<b>CFX</b>			
*.out	Yes	NA	Plot
<b>Fluent</b>			
*.out	Yes	NA	Plot
output.*	Yes	NA	Plot

Results File Format	Plot Data	Animation Data	Default TOC Type
*.trn	Yes	NA	Plot
*.txt*	Yes	NA	Plot
<b>Ls-Dyna</b>			
d3plot	Yes	Yes	Animation
*dynain	Yes	Yes	Animation
*.fz	Yes	Yes	Animation
Intfor	Yes	Yes	Animation
Ptf	Yes	Yes	Animation
ABSTAT	Yes	NA	Plot
BINOUT	Yes	Yes	Animation
BNDOUT	Yes	Yes	Animation
DBFSI	Yes	NA	Plot
DEFORC	Yes	NA	Plot
*.dyn	Yes	NA	Plot
ELOUT	Yes	NA	Plot
GLSTAT	Yes	NA	Plot
GECOUT	Yes	NA	Plot
JNTFORC	Yes	NA	Plot
MATSUM	Yes	NA	Plot
NCFORC	Yes	NA	Plot
NODFOR	Yes	NA	Plot
NODOUT	Yes	NA	Plot
RBDOUT	Yes	NA	Plot
RCFORC	Yes	NA	Plot
RWFOC	Yes	NA	Plot

Results File Format	Plot Data	Animation Data	Default TOC Type
SBTOUT	Yes	NA	Plot
SECFORC	Yes	NA	Plot
SLEOUT	Yes	NA	Plot
SPHOUT	Yes	NA	Plot
SWFORC	Yes	NA	Plot
<b>NanoFluidX</b>			
nFX	Yes	No	NA
<b>UltraFluidX</b>			
uFX	Yes	No	NA
<b>HyperXtrude</b>			
*.h3d	Yes	Yes	Animation
*.out	Yes	NA	Plot
<b>FEMZIP</b>			
*.fz	Yes	Yes	Animation
*d3plot*	Yes	Yes	Animation
<b>HW ASCII</b>			
*.hwascii	Yes	Yes	Animation
<b>MADYMO</b>			
*.fai	Yes	NA	Plot
*.kn3	Yes	Yes	Animation
<b>Marc</b>			
*.t16	Yes	Yes	Animation
<b>Nastran</b>			
*.op2	Yes	Yes	Animation
*.pch	Yes	NA	Plot

Results File Format	Plot Data	Animation Data	Default TOC Type
<b>NIKE3D</b>			
*n3plot	Yes	Yes	Animation
<b>Pamcrash</b>			
*.DSY	Yes	Yes	Animation
*.erfh5	Yes	Yes	Animation
*.THP	Yes	NA	Plot
*.fz	Yes	Yes	Animation
*.h3d	Yes	Yes	Animation
<b>Permas</b>			
*A# #	Yes	Yes	Animation
<b>Other Ascii formats</b>			
*.xgr	Yes	NA	Plot
*.dat	Yes	NA	Plot
*.col	Yes	NA	Plot
*.csv	Yes	NA	Plot
*.rvp	Yes	NA	Plot



**Note:** The default TOC type (plot or animation) will be identified depending on the file type registration and the parameter `isDefault` in the `plugin_def.xml` file.



**Tip:** To set the Default TOC Type, change the value of `isDefault` to true in the server configuration (`PA_HOME/config/resultservice/plugins/plot_toc_data_provider/plugin_def.xml`). Any new file formats other than the ones mentioned in the table which are supported by HyperWorks can be configured in `plugin_def.xml` file.

## 9.4.5 Configure Data Directory

You can configure RVS data directory for storing the RVS data such as result files, temporary files and cache data.

1. Open the file at `PA_HOME/config/resultservice/config/site_config.xml`
2. Configure the folders to store your RVS data in the following line:

```
<HWE_RM_DATA_LOC><folder_name</HWE_RM_DATA_LOC
```



**Note:** By default, the RVS data is stored in the temp folder.

3. Restart Access Web Service.

## 9.4.6 Set a Data Cleanup

To improve the performance of visualizing the result files you can configure the RVS data cleanup for the RVS cache data.

To configure the RVS data files refer to [Configure Data Directory](#).

You can configure the RVS data cleanup criteria settings in `site_config.xml` file. The recurring cleanup can be configured in these formats: Daily, Weekly or Monthly.



**Note:** By default, the RVS data cleanup is set for Weekly Sun 1:00 AM.

If you wish to setup the cleanup criteria on a daily basis, you need to specify the time as `DAILY 21:45` which represents everyday at 9:45 PM.

If you wish to setup the cleanup criteria weekly, you need to specify the days and the time. Here are a few examples:

`WEEKLY SUN 14:30` represents every Sunday in a week at 2:30 PM.

`WEEKLY MON-FRI 1:00` represents the range of days in a week. Every Monday to Friday at 1 AM.

`WEEKLY MON,WED 3:00` represents the days Monday and Wednesday in a week at 3 AM

If you wish to setup the cleanup criteria monthly, you would need to specify the days and time. Here are a few examples:

`MONTHLY 15 15:30` represents the every 15th day in a month at 3:30 PM.

`MONTHLY 10-20 1:30` represents every 10th day to 20th day in a month at 1:30 AM.

`MONTHLY 1, 11, 21 8:00` represents every 1st day, 11th day and 21st day in a month at 8 AM.

1. Open the file at `PA_HOME/config/resultservice/config/site_config.xml`
2. Set the value of cleanup time `<CleanupTime>` indicate when the cleanup should occur. The below example will set the cleanup daily at 1AM.

```
<CleanupTime>DAILY 01:00</CleanupTime>
```

3. Enter the cleanup time in 24 hours format.
4. Choose one of the cleanup criteria to cleanup the untouched RVS data.



- Specify the value of cleanup criteria `<noofDays>`. The RVS data that is not accessed for the specified number of days is considered for the cleanup.

```
<Criterion id="LAST_ACCESSED_TIME_BASED" noOfDays="30"  
class="com.altair.hwe.publish.resultsmanager.defaultimpl.LastAccessed  
TimeBasedCriterion"/>
```

- Specify the value of cleanup criteria `<noofDays>`. The RVS data that is not modified for the specified number of days is considered for the cleanup.

```
<Criterion id="LAST_MODIFIED_TIME_BASED" noOfDays="100"  
class="com.altair.hwe.publish.resultsmanager.defaultimpl.LastModified  
TimeBasedCriterion"/>  
</CleanupCriteria>
```

5. Replace the criterion id with the framework element value to configure the RVS data cleanup.

```
<Criterion id="FRAMEWORK_CACHE_CLEANUP_CRITERIA">
```

The following snippet is set with Daily cleanup time and the chosen cleanup criteria is, the last modified time to clean the RVS data.

```
<CleanupTime>DAILY 01:00</CleanupTime>  
<CleanupCriteria>  
  <Criterion id="LAST_ACCESSED_TIME_BASED" noOfDays="30"  
    class="com.altair.hwe.publish.resultsmanager.defaultimpl.LastAccessed  
    TimeBasedCriterion"/>  
  <Criterion id="FRAMEWORK_CACHE_CLEANUP_CRITERIA" noOfDays="100"  
    class="com.altair.hwe.publish.resultsmanager.defaultimpl.LastModified  
    TimeBasedCriterion"/>  
</CleanupCriteria>  
<FrameworkCacheCleanupCriteria>FRAMEWORK_CACHE_CLEANUP_CRITERIA</  
FrameworkCacheCleanupCriteria>
```

6. Save the file and restart Access Web Service.

## 9.4.7 Configure RVS Parameters

Main parameters related to RVS in Access Web

The default value of the parameters and the location of the files in which these settings are stored are listed here:

### TOC Size

Specify the maximum TOC size limit in bytes. It helps to send the partial TOC (bytes).

Default value is 2097152 (In bytes)

Configure the maximum TOC size using `<SizeLimit toc="2097152">` and it is located at `PA_HOME/config/resultservice/config/site_config.xml`

### AIF Impersonation

The RVS result extractions and license check out are processed using the portal user.

Default value is set to `true`.

Configure the RVS impersonation using `<AIFImpersonation enabled ="true">` and it is located at `PA_HOME/config/resultservice/config/site_config.xml`



**Note:** If the parameter value is set to false then all the RVS result extractions and license check out are processed as an administrator.

#### *Cache enabled*

Enable or disable data caching for RVS on the server.

Default value is set to `true`.

Configure the RVS data caching using `<Cache enabled="true">` and it is located at `PA_HOME/config/resultservice/config/site_config.xml`

#### *Session defaultTimeout*

Is the maximum amount of time the server should wait for a response from another application before disconnecting.

Default value is 6000 milliseconds.

Configure the session default timeout using `<Session defaultTimeout="6000">` and it is located at `PA_HOME/config/resultservice/config/site_config.xml`

#### *Operation defaultTimeout*

Is the maximum amount of time the server should wait before closing an old connection and creating a new connection.

Default value is 6000 milliseconds.

Configure the operation default timeout using `<Operation defaultTimeout="6000">` and it is located at `PA_EXEC/resultservice/binaries/rvs_lib/config/site_config.xml`

#### *Socket timeout for HMath*

It is the maximum amount of time that the HMath server should wait to setup a connection with RVS.

Default value is 6000 milliseconds.

Configure the socket timeout for HMath in the line `<Application id="HYPERMATH_APPLICATION">` and enter the `<socketTimeout="6000">` value.

The parameter is located at `PA_HOME/config/resultservice/plugins/hypermath_application/plugin_def.xml`

#### *Connection timeout for HMath*

It is the maximum amount of time that the HMath server should wait to respond for the data query from RVS.

Default value is 6000 milliseconds.

Configure the connection timeout for HMath in the line `<Application id="HYPERMATH_APPLICATION">` and enter the `<connectionTimeout="6000">` value.

The parameter is located at `PA_HOME/config/resultservice/plugins/hypermath_application/plugin_def.xml`

### *Request timeout for PBS datasource*

It is the maximum amount of time that the RVS server will wait for a request from PAS.

The default value is 6000 milliseconds.

Configure the request timeout for PAS in the line `<DataSourceHandler id="PBS_DATA_SOURCE_HANDLER">` and enter the `<requestTimeout="6000">` value.

The parameter is located at `PA_HOME/config/resultservice/plugins/pbs_datasource_handler/plugin_def.xml`

### *Connection timeout for PBS datasource*

It is the maximum amount of time that the PAS server should wait to respond for the data query from RVS.

Default value is 6000 milliseconds.

Configure the connection timeout for PAS in the line `<DataSourceHandler id="PBS_DATA_SOURCE_HANDLER">` and enter the `<connectionTimeout="6000">` value.

The parameter is located at `PA_HOME/config/resultservice/plugins/pbs_datasource_handler/plugin_def.xml`

### *Browser Timeout*

It is the amount of time for the browser should wait to respond for any RVS requests. If the server doesn't respond beyond this timeout value then the browser timeout message appears.



**Note:** The timeout value doesn't interrupt any of the RVS background operations.

Default value is 600seconds


Configure the browser timeout for RVS requests in the line `< proxy_read_timeout 600sec>` and enter the timeout value in seconds.

The parameter is located at `PA_HOME/config/api_gateway/default.d/resultmanager.conf`

## 9.5 Access Web Windows Setup

Load Access Web docker image in Windows Docker, install PAS in Windows, install Remote Session Application Definition, and update the Docker Environment list.

- Ensure that PBS Professional cluster for windows is installed and running
- Docker windows is installed and running. Refer to [Install Docker Desktop for Windows](#) for more information.

 **Tip:** For the application to run smoothly, your windows docker requires 8 CPU cores and 16 GB Memory.

Download or obtain the following files using your usual Altair support channels:

- Access Web Docker Tar File
- PAS Execution Folder Zip File (`pas_exec.zip`)
- PAS Home Folder Zip File (`pas_home.zip`)
- Remote Session Application Defintion Zip File (`windows_remotesession_appdef.zip`)
- Docker Environment List (`env.list`)

The following will be the infrastructure after you install Access Web and PAS in Windows:


- PAS will be running in Windows.
- Access Web will be running in Docker.

### 9.5.1 PAS Setup

Installing PAS in Windows.

Download or obtain the `pas_exec.zip` and `pas_home.zip` using your usual Altair support channels.

1. Create the following directory structure in `C:\Program Files\altair\pas\2019.1\PAS`
2. Unzip the `pas_exec.zip` to `C:\Program Files\altair\pas\2019.1\PAS\exec`
3. Unzip the `pas_home.zip` to `C:\Program Files\altair\pas\2019.1\PAS\home`
4. Copy the `joboperation.xml` file from `C:\Program Files\altair\pas\2019.1\PAS\home\config\joboperation\tomcat\conf\Catalina\localhost\` to `C:\Program Files\altair\pas\2019.1\PAS\home\config\pas\tomcat\conf\Catalina\localhost\`
5. In case PAS is installed in a different location from the one mentioned above, then update the installation path in `PAS_Windows_Start.bat` file located at `pas_deploy_dir\PAS\exec\scripts`.

 **Note:** Default installation directory is set as `pas_deploy_dir=C:\Program Files\altair\pas\2019.1`

6. Update `STAGE_ROOT` path in `pas_deploy_dir\PAS\home\config\pas\conf\server.conf` to stage root directory (`C:/stage`) according to Windows path.

7. Provide the permissions to stage root directory (C:/stage).
8. Provide the permissions to different directories under `pas_deploy_dir`
9. Read and execute permissions to `exec` and home directories with service user.
  - a) Right click on `pas_deploy_dir` and select **Properties**.
  - b) Click **Security** tab.
  - c) Click **Advanced**.
  - d) Click **Add** and click on **Select a Principal**.
  - e) Type in **<service user name>** and click **Check Names**
  - f) Click **OK**
  - g) Select **Read&execute** on **Permissions** section.
  - h) Click **OK**.
10. Full control to home directory for Everyone.
  - a) Right click on `pas_deploy_dir\PAS\home` and select **Properties**.
  - b) Click **Security** tab.
  - c) Click **Advanced**.
  - d) Click **Add** and click on **Select a Principal**.
  - e) Type in **Everyone** and click **Check Names**
  - f) Click **OK**
  - g) Select **Full Control** on **Permissions** section.
  - h) Click **OK**.
11. To start PAS run the batch file `PAS_Windows_Start.bat` located at `pas_deploy_dir\PAS\exec\scripts` as administrator.

By default PAS is running on port 5243. Please register this PAS server in Access Web.

## 9.5.2 Access Web and Docker Setup

Load Access Web docker image in Windows Docker and update the Docker Environment list.

Download or obtain the Access Web build image file and Docker environment list (`env.list`) using your usual Altair support channels.

1. Load the Access Web docker image in the Windows docker using the following command:

```
docker load -i <Access Web tar file.tar>
```

2. Update the license path, hostname, and HyperWorks location in Docker environment list (`env.list`).

```
ALTAIR_LICENSE_PATH=6200@10.130.3.175  
HOSTNAME=10.75.20.123  
HW_DESKTOP_LOCATION=10.75.32.34:/apps/hwdesktop
```


3. Start the Access Web Docker container using the following command:

```
docker run -itd --env-file ./env.list --entrypoint /tmp/scripts/access_setup.sh --  
name windows_access --privileged -p 4443:4443 -p 4222:4222 windows_docker:latest  
bash
```

4. Login to Access Web Docker container using the following command:

```
docker exec -it windows_access bash
```


5. Add the MOM hostname mapping to docker Linux in `/etc/hosts`


 **Note:** The users and their credentials has to be the same in Windows and Access Web Docker container.

6. Follow one of the options to create the users list:


- Manually create the Window users and their credentials in Access Web Docker container.
- Provide LDAP configuration in the file `PA_HOME/config/ams/jaas-config/AA_jaas.config` with the following information:

```
LoginModule {  
  com.sun.security.auth.module.LdapLoginModule REQUIRED  
  userProvider="ldap://<IP Address>:<Port Number>/CN=Users,DC=<Domain  
    Name>,DC=com"  
  userFilter="(&((userPrincipalName={USERNAME}@pbsworks.com))(objectClass=user))"  
  authIdentity="{USERNAME}@<Domain Name>.com"  
  authzIdentity="{USERNAME}@<Domain Name>.com"  
  useSSL=false  
  debug=true;  
};
```

 **Note:** Update IP address, Port Number, and Domain Name details according to the domain server that's being used.

 **Note:** If LDAP configuration is updated to create the users lists, then restart Access Web.

7. Login to Access Web portal and add the PAS server.

 **Note:**

- PAS installed in Windows will be running on port 5243. Please register the Windows PAS server in Access Web. The IP address that is provided while adding the local PAS server should be the username.
- Make sure service user which is used for registering the PAS service is logged in once, after restarting the pbsworks-pa service.
- If PBS MOM is also active in same machine as PAS, then make sure you do not start remote session from the same user through which you started the docker and PAS service.

## 9.5.3 Remote Session Windows Setup

Install Remote Session components on Windows.

Download or obtain the Remote Session Component installer using your usual Altair support channels.

1. Install Remote Session Component installer on all PBS MoMs.

- 2.** Check if Remote Session service is running.

## 9.6 Running Job Operations in Windows

Configuration in Windows and Linux for performing the operations faster on a running job.

Earlier the operations executed on a running job used to be slow while interacting with the Access Web. Some of the operations executed on a running job are:

- Executing a custom action
- Generating h3d file custom action
- Starting a remote session
- Running directory file listing

Access Web performs these operation faster on a running job by using messaging-based infrastructure. By default, this feature is disabled, and it can be enabled by performing the following configuration in Windows and Linux access setup.

### 9.6.1 Configuration in Windows for Faster Running Job Operations

Configuration in Windows Execution Node and in PAS server for faster running job operations.


Download or obtain the Windows `momclientmodules.zip` using your usual Altair support channels.

Steps to perform on Windows Execution Node:

1. Extract `momclientmodules.zip` to `C:\`
2. Provide full control permission to `momclientmodules` directory for Everyone:
  - a) Right click on `momclientmodules` and select **Properties**.
  - b) Click **Security** tab.
  - c) Click **Advanced**.
  - d) Click **Add** and click on **Select a Principal**.
  - e) Type in **Everyone** and click **Check Names**
  - f) Click **OK**
  - g) Select **Full Control** on **Permissions** section.
  - h) Click **OK**.

Steps to perform where PAS Server is running:

3. Navigate to `pas_deploy_dir\PAS\home\config\pas\conf\`

 **Note:** Check the `pas_deploy_dir` path. Default installation directory is set as `pas_deploy_dir=C:\Program Files\altair\pas\2019.1`

4. Edit the `server.conf` to set `FRO_Enabled` to `true`.

```
FRO_Enabled=true
```
5. Update the `FRO_Shared_Libs` path to the path where `momclientmodules.zip` is extracted.

```
FRO_Shared_Libs=C:\momclientmodules
```



6. Start PAS batch file `PAS_Windows_Start.bat` located in `pas_deploy_dir\PAS\exec\scripts` as administrator.

Steps to perform where Access Web is running:

7. Log in to altair access web container:

```
docker exec -it windows_access bash
```

8. Navigate to `PA_HOME/config/api_gateway/`

9. Take a backup of the `template.conf`

This backup file should be copied back when FRO is disabled and all PAS servers registered should be deleted and re-registered in Access Web.

10. Copy `template_joboperation.conf` to `template.conf`

11. Navigate to `PA_HOME/config/shared/`

12. Check the value of `net: 0.0.0.0` in the `nats-server.config`.

The value of `net` should be `0.0.0.0`



**Note:** All PAS servers registered should be deleted and re-registered in Access Web.

13. Restart Access Web by entering the command:

```
service pbsworks-pa restart
```

## 9.6.2 Configuration in Linux for Faster Running Job Operations

Configuration in Linux Execution Node and in Access Web for faster running job operations.

Download or obtain the Linux `momclientmodules.zip` using your usual Altair support channels.

Steps to perform on Linux Execution Node:

1. Extract `momclientmodules.zip` to `/opt`

2. Provide the full permission to `/opt/momclientmodules/` using the following command:

```
chmod -R 777 /opt/momclientmodules
```

Steps to perform where Access Web is running:

3. Navigate to `PA_HOME/config/api_gateway/`

4. Take a backup of the `template.conf`

This backup file should be copied back when FRO is disabled and all PAS servers registered should be deleted and re-registered in Access Web.

5. Copy `template_joboperation.conf` to `template.conf`

6. Navigate to `PA_HOME/config/shared/`

7. Edit the `nats-server.config` and update the value `0.0.0.0` of `net: 0.0.0.0` with the hostname of the machine Access Web is installed.

8. Restart Access Web by entering the command:

```
service pbsworks-pa restart
```

Steps at the place where PAS Server is running:

**9.** Navigate to `PA_HOME/config/pas/conf/`

**10.** Update `server.conf` with the following:

- a) Set `FRO_Enabled=true`
- b) Update `MQ_HOSTNAME` to hostname of Access Web instance.
- c) If you have extracted `momclientmodules.zip` to a different location, then update the `FRO_Shared_Libs` path.

**11.** Navigate to `PA_HOME/config/joboperation/`

**12.** Update `application.properties` with the following:

- a) Update `mq.hostname` to hostname of Access Web instance.



**Note:** All PAS servers registered should be deleted and re-registered in Access Web.

**13.** Restart Access Web by entering the command:

```
service pbsworks-pa restart
```

PAS requires a predefined set of instructions, called application definitions, to describe your application parameters to users, store their responses, and prepare those responses for job execution via PBS Professional.

This chapter covers the following:

- [10.1 Application Definition Components](#) (p. 119)
- [10.2 Sample Application Definition ShellScript](#) (p. 121)
- [10.3 Map Icons to an Application](#) (p. 122)
- [10.4 Define a Category in Application Definition](#) (p. 123)
- [10.5 Administration of Application Definition](#) (p. 125)
- [10.6 Sitewide Settings](#) (p. 127)
- [10.7 Interactive Application Definitions](#) (p. 130)

An application definition provides a flexible set of instructions that can be manipulated to allow for precise control over all aspects of application-specific parameters and job execution. These application definitions are stored in a central repository and will make PBS Professional aware of each of them upon server startup. The location of the application directory for a typical installation of PAS is: `PA_HOME/data/pas/targets/localhost/repository/applications`.

## 10.1 Application Definition Components

Overview of application definition components.

An application definition is comprised of a set of Python scripts and two XML files which could include references to site wide configuration settings. A separate application definition with application-specific details is required for each application that will be integrated into PAS. Application definitions are compliant with the Open Grid Forum High Performance Computing Basic Profile (HPCBP), Business Process Execution Language (BPEL), and Job Submission Description Language (JSDL) standards.

Application definitions are stored in the PAS application directory. The default location of this directory is: `PA_HOME/data/pas/targets/localhost/repository/applications/`.

Diving Into Application Definitions explains what an application definition is and how to use an application definition. If you are installing PAS for the first time and are not familiar with application definitions, then Diving Into Application Definitions is a good place to start. A set of tutorials is provided starting with how to create the simplest of application definitions and progressing to more advanced topics. Recipes are also available demonstrating advanced techniques. For more comprehensive information about application definitions and their associated files see *Diving Into Application Definitions*.

### 10.1.1 Application Input File

The application input file is where administrators can define the allowed arguments for a given application. This file is also used by graphical, web-based and even command-line tools to display these arguments to users for job submission.

The mandatory naming convention for the application input file is `app-inp-applicationname.xml` where `applicationname` is whatever name you choose to give your application.

### 10.1.2 Application Converter File (HPCBP Converter)

The application converter file is where administrators take the values received by the user via the input file and communicates this information to the PAS and PBS Professional. This file allows the PAS administrator to configure the job submission environment.

The mandatory naming convention for the application converter file is `app-conv-applicationname.xml` where `applicationname` is whatever name you decide to give to your application.

### 10.1.3 Application Runtime Scripts

The application runtime scripts are what really get executed on the execution hosts. The runtime script, `start.py`, is what will be executed as the "job script". This script file is responsible for executing

the application associated with your application definition, using the information entered by the user (defined by the application input file) and converted (via the application converter file). Additional scripts can also be included that support and enhance the runtime script. Administrators can directly edit these runtime script(s), taking full advantage of Python to add further inspection and complexity to job submission and finally execution of the application itself. This adds tremendous flexibility as nearly infinite possibilities for job control exist at this phase of job description.

For information about how to use runtime scripts see the tutorials *Enhancing your Application with Runtime Scripts*, *Executing Actions on a Running Job* and the *Recipes* section in *Diving Into Application Definitions*.

### 10.1.4 Site Configuration File

A default site configuration file, `site-config.xml`, is installed in the PAS configuration directory.

The site configuration file, `site-config.xml`, is meant to make application definitions more portable by consolidating data that may change from cluster to cluster in a central location. It is where administrators can define things like policies, version, and path information for all the available applications, billing account information, etc. The data in this file is used by the application input and converter files.

The location of this file for a typical installation of PAS is: `PA_HOME/data/pas/targets/localhost/repository/`

For information on how to reference the site configuration file in an application definition see the tutorial *Maintaining Multiple Versions of an Application*, recipes *How to Configure & Use Sitewide Billing Accounts*, *How to Configure & Use Sitewide Policies*, and *How to Configure & Use Application Policies* section in *Diving Into Application Definitions*.

### 10.1.5 Server Configuration File

A server configuration file, `server.conf`, is also installed in the PAS configuration directory.

This file contains all configurable parameters available with PAS. The location of this file for a typical installation of PAS is: `PA_HOME/config/pas/conf`

## 10.2 Sample Application Definition ShellScript

PAS provides a sample application definition, ShellScript, which is located in the application definition directory.

ShellScript is an example of how an administrator could create an application definition enabling users to use custom job scripts akin to the more common PBS Professional job script. ShellScript allows these job scripts to be written in any language by using its runtime script, `start.py`, to parse the first line (shebang line) to determine the correct interpreter to execute your job script against. ShellScript's versatility allows the following:


- extra arguments to be passed to the job script
- specification of advanced multi-node placement options
- the inclusion of additional files

This application definition in conjunction with the *Diving Into Application Definitions* documentation will assist administrators to create and deploy application definitions.


## 10.3 Map Icons to an Application

Icons can be mapped to an application so that it gets displayed in the context menu and in the application list.

The application input file is where administrators can map an icon for a given application. The icon mapped in this file is displayed in the context menu and in the application list.

 **Note:** Only Administrators can map an icon to the application.

1. Login to the machine where Access Web is installed as root.
2. Navigate to `PA_HOME/data/pas /targets/localhost/repository/applications/<appname>`.  
where `<appname>` is the application folder. For example, let's assume that we are adding icon to the ShellScript application definition.
3. Create an `avatar` directory.
4. Navigate to the `avatar` directory.
5. Place the application icon.

 **Note:** You have to place two different images, one for the context menu (smaller size) and the other for the list menu (bigger size) .

6. Navigate to `PA_HOME/data/pas /targets/localhost/repository/applications/ShellScript`.
7. Edit the application input file and add the `<ApplicationIconSmall>` xml element to display the icon in context menu and `<ApplicationIconMedium>` xml element to display the icon in the application list.

```
<ApplicationId>ShellScript</ApplicationId>
<ApplicationName>ShellScript</ApplicationName>
<ApplicationExtension>.fem</ApplicationExtension>
<ApplicationIconSmall>ShellScriptIconSmall.jpg</ApplicationIconSmall>
<ApplicationIconMedium>ShellScriptIconMedium.jpg</ApplicationIconMedium>
```

8. Repeat steps 2 through 7 for all applications.
9. Restart the Access Web by entering the following command:

```
service pbsworks-pa restart
```

## 10.4 Define a Category in Application Definition

Define a category in the application definition input file, so that the application listed can be filtered based on the category.

The XML element, <TAGS> defines the category in which the application will be listed. The category defined in the application input file will be listed Access Web UI which will help the user to filter the application based on the category.

For example, add a category to the Optistruct application using the XML element <TAGS>:

```
<TAGS>
  <TAG>SimulationType:CAD</TAG>
  <TAG>MYSolver:OPTI</TAG>
</TAGS>
```

This tag indicates that the Optistruct application will be listed in SimulationType and MySolver categories. The CAD and OPTI will be the subcategory of SimulationType and MySolver respectively. The category tags can be defined in other application definition input files so that you can filter the application list.

The Optistruct application in the Access Web UI will be displayed with the defined category:






Figure 19: Application Definition Category

## 10.5 Administration of Application Definition

PAS has a central location for storing application definitions - `PA_HOME/data/pas/targets/localhost/repository/applications`.

### 10.5.1 Add a New Application Definitions

Adding an application definition to the applications directory, followed by a restart of Access Web, will expose your application definition to the user.

Follow these steps to add an application definition:

1. Login to the machine hosting the PAS Server.
2. Navigate to the applications directory located at `PA_HOME/data/pas/targets/localhost/repository/applications`.
3. Create a directory called `appname`.  
where `appname` is the name of the application.
4. Place the application definition input file (`app-inp-appname.xml`) and the application definition converter file (`app-conv-appname.xml`) in the application directory.
5. Navigate to the `appname` directory.
6. Create a subdirectory called `runtime` and navigate to that subdirectory.
7. Place any runtime scripts into the runtime directory.
8. Restart the Access Web by entering the following command:

```
service pbsworks-pa restart
```

### 10.5.2 Application Definition Validation

When the Access Web starts, it performs a validation of the existing application definitions. If application definitions fail to meet key criteria, they will be moved to an invalid application directory. This directory will be created if it does not exist. The location of this directory is: `PA_HOME/data/pas/targets/localhost/repository/private/generated/invalid_applications`

In addition, PAS will restore the site configuration file from the last valid backup - `site-config.backup`.

Error messages will be displayed in the PAS log file indicating why the application definition was invalid. Invalid application definitions can be retrieved from the `invalid_applications` directory and modified to meet the criteria necessary to be considered valid. An invalid application definition will not prevent the PAS Server from starting up.

## 10.5.3 Maintenance of Existing Application Definition

Existing application definitions can be modified or removed. To make PAS aware of the modification or the removal of an application definition, restart the Access Web.

### Update an Application Definition

You can easily modify an existing application definition using your favorite XML editor.

1. Login to the machine hosting the PAS Server.
2. Navigate to the applications directory located at `PA_HOME/data/pas/targets/localhost/respository/applications`.
3. Edit and make any modifications necessary to the application definition files.
4. Restart the Access Web by entering the following command:

```
service pbsworks-pa restart
```

### Remove an Application Definition

Removing an application definition from PAS is also very simple.

Simply remove the application definition directory from the applications folder. You have to restart Access Web to remove your application definition from PAS. Follow these steps to remove an application definition:

1. Login to the machine hosting the PAS Server.
2. Navigate to the applications directory located at: `PA_HOME/data/pas/targets/localhost/respository/applications`.
3. Remove the application directory and all of its content including the `runtime` subdirectory and associated files.
4. Restart the Access Web by entering the following command:

```
service pbsworks-pa restart
```

## 10.6 Sitewide Settings

PAS provides a central repository for site specific information such as executable paths, policies, and billing account information. This information is stored in a site configuration file, `site-config.xml`. By putting some site specific application information in the, `site-config.xml` application definitions can be made more portable and reusable among different PBS Professional complexes. For example, putting binaries locations and version availability information here, makes the rest of the application definition reusable on a different cluster just by modifying that cluster's `site-config.xml`. The location of this file is `PA_HOME/data/pas/targets/localhost/repository`.

### 10.6.1 Site Configuration File Content

This file can hold virtually any sort of information, since the information stored in the file can be referenced by any application definition XML file. Altair has included certain data in the site configuration file for the integration and support of other products from the PBS Professional family. The example below shows a sample of the site configuration file with the sections currently used by the PBS Professional product suite:

- Applications - This section holds application specific information.
- Application versions - For each application, you can insert site supported versions and for each version its binary pathname.
- Job projects (billing accounts) - This section is for integrating PAS with other products from Altair. Here you can list a set of strings to be used as "accounting" information to be attached to jobs.
- Policies - Site policies are values that can be used in a site's application definition XML files and/or as values available in job runtime environment (policies are included as environment variables for the jobs).
- Application policies - This section is for setting policies that are specific to an application.

### 10.6.2 Initial Site Configuration File after Installation of PAS

After installation of PAS the site configuration file will contain references to ShellScript, an application definition that is provided out-of-the-box. Placeholders for billing accounts and policies are provided, but will need to be updated according to your site specifications.

```
<?xml version="1.0" encoding="UTF-8"?>
<SiteConfiguration xmlns="http://schemas.altair.com/pbs/2007/01/site-config"
  xmlns:site-config="http://schemas.altair.com/pbs/2007/01/site-config"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://schemas.altair.com/pbs/2007/01/site-config ../schemas/
site-config.xsd">
  <Applications>
    <Application id="ShellScript">
      <ApplicationVersions/>
    </Application>
  </Applications>
</SiteConfiguration>
```

```
</Application>
</Applications>
<JobProjects id="BILLING_ACCOUNT"/>
<Policies/>
</SiteConfiguration>
```

### 10.6.3 Sample of a Site Configuration File

Here is an example of a site configuration file with modifications for site supported application versions, application policies, billing accounts, and sitewide policies:

```
<?xml version="1.0" encoding="UTF-8"?>
<SiteConfiguration xmlns="http://schemas.altair.com/pbs/2007/01/site-config"
  xmlns:site-config="http://schemas.altair.com/pbs/2007/01/site-config"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://schemas.altair.com/pbs/2007/01/site-config ../schemas/
site-config.xsd">
  <Applications>
    <Application id="ShellScript">
      <ApplicationVersions/>
      <Policies>
        <Policy>
          <Option>MAX_CPUS</Option>
          <Value>4</Value>
        </Policy>
      </Policies>
    </Application>
    <Application id="Optistruct">
      <ApplicationVersions>
        <ApplicationVersion>
          <Option>8.0</Option>
          <Executable>/opt/hyperworks/11.0/altair/scripts/optistruct</Executable>
        </ApplicationVersion>
        <ApplicationVersion>
          <Option>9.0</Option>
          <Executable>/sw/optistruct9/optistruct</Executable>
        </ApplicationVersion>
      </ApplicationVersions>
    </Application>
  </Applications>
  <JobProjects id="BILLING_ACCOUNT">
    <Option>Company1</Option>
    <Option>Company2</Option>
  </JobProjects>
  <Policies>
    <Policy>
      <Option>MAX_CPUS</Option>
      <Value>4</Value>
    </Policy>
  </Policies>
</SiteConfiguration>
```

## 10.6.4 Use Site Configuration Information in an Application Definition

For information on how to reference the site configuration file in an application definition see the tutorial *Maintaining Multiple Versions of an Application*, recipes *How to Configure & Use Sitewide Billing Accounts*, *How to Configure & Use Sitewide Policies*, and *How to Configure & Use Application Policies in Diving Into Application Definitions*.

## 10.6.5 Site Configuration File Backup

Upon server start-up, PAS will validate the content of the site configuration file and the content of application definitions. If the content of both the site configuration file and application definitions is valid, the site configuration file will be backed up to a file called `site-config.backup`. If the content of either the site configuration file or any application definition is invalid, the site configuration file will be backed up to a file called `site-config.YYYYMMDDMMSS` where `YYYYMMDDMMSS` is the file creation timestamp. The site configuration file will be restored from the last valid backup, `site-config.backup`.

Up to five (5) backups will be maintained. All backup files will be maintained in the same directory as the site configuration file.

## 10.6.6 Site Configuration File Validation

Upon server startup, PAS validates the site configuration file. It is validated against its XML schema. An XML schema defines the legal building blocks of a particular XML document. An XML schema:

- defines elements that can appear in a document
- defines attributes that can appear in a document
- defines which elements are child elements
- defines the order of child elements
- defines the number of child elements
- defines whether an element is empty or can include text
- defines data types for elements and attributes
- defines default and fixed values for elements and attributes

The validation process also determines if the content of the site configuration file is well-formed (valid). The content is well-formed if the following criteria is met:

- It must have a root element.
- XML elements must have a closing tag.
- XML tags are case sensitive.
- XML elements must be properly nested.
- XML attribute values must be quoted.

## 10.7 Interactive Application Definitions

Interactive application definition mandatory and special arguments.

### 10.7.1 Mandatory Interactive Application Definitions Changes

XML tags that are required for an interactive application definition.

For an application to be identified as interactive, the corresponding application definition must contain the `<Interactive>` element and its value must be set to `true` in the application input file.

```
<Interactive>true</Interactive>
```

Additionally, a boolean argument is necessary to run an interactive application which controls how many GPUs are requested at job submission.

```
<ArgumentChoice>
  <ArgumentBooleanWithDescription>
    <Name>GPU</Name>
    <Description>Is GPU required ?</Description>
    <DisplayName>GPU (?)</DisplayName>
    <InputRequired>>false</InputRequired>
    <Value>true</Value>
  </ArgumentBooleanWithDescription>
</ArgumentChoice>
```

The `<Value>` element controls the request for GPUs. For 2D applications set it to `false` and a request for GPUs will not be made for the application. For 3D applications, `<Value>` option has to be set to `true`.

### 10.7.2 Special Interactive Application Arguments

Arguments that can be added to an interactive application definition.

The following interactive application specific arguments can be added to an application definition to pass arguments and environment variables to the application, define a job working directory, create a backup of job input files, and change the viewing mode from Applet to HTML5.

#### Arguments

A special string argument having the name `DM_APP_ARGS` can be added to an application definition so that arguments can be passed to the application. Multiple arguments can be passed to the application by separating them by `'\n'`.

```
<ArgumentChoice>
  <ArgumentString>
    <Name>DM_APP_ARGS</Name>
    <Description>'\\n' separated args</Description>
    <DisplayName>Arguments</DisplayName>
    <InputRequired>>false</InputRequired>
  </ArgumentString>
</ArgumentChoice>
```

## Environment

A special string argument having the name `DM_APP_ENVS` can be added to an application definition so that environment variables can be passed to the application. Multiple variables can be passed to the application by separating them by `'\n'`.

```
<ArgumentChoice>
  <ArgumentString>
    <Name>DM_APP_ENVS</Name>
    <Description>'\\n' separated envs</Description>
    <DisplayName>Environments</DisplayName>
    <InputRequired>>false</InputRequired>
  </ArgumentString>
</ArgumentChoice>
```

## WorkDirectory

A special string argument having the name `DM_APP_WDIR` can be added to an application definition so a job working directory is created when the job is submitted.

```
<ArgumentChoice>
  <ArgumentString>
    <Name>DM_APP_WDIR</Name>
    <Description>Working dir</Description>
    <DisplayName>Workding Dir</DisplayName>
    <InputRequired>>false</InputRequired>
  </ArgumentString>
</ArgumentChoice>
```



**Note:** The arguments mentioned above are disabled by default. Enable them by setting the `<InputRequired>` field to true.

## Copy Back Files

A special boolean argument having the name `COPY_BACK_FILES` can be added to an application definition so that job input files are copied to the stageout directory.

```
<ArgumentChoice>
  <ArgumentBooleanWithDescription>
    <Name>COPY_BACK_FILES</Name>
    <Description>Should job file(s) be staged out</Description>
    <DisplayName>Copy back files</DisplayName>
    <InputRequired>>true</InputRequired>
    <FeatureEnabled>>false</FeatureEnabled>
    <RefreshOnUpdate>>true</RefreshOnUpdate>
  </ArgumentBooleanWithDescription>
</ArgumentChoice>
```




**Note:** The `COPY_BACK_FILES` arguments is disabled by default. Enable this field by setting the `<FeatureEnabled>` option to true. When `<FeatureEnabled>` is set to true, the person who is submitting the job can choose whether to stageout job input files.

## Client View Mode

A special enumerated list argument having the name `DM_CLIENT_VIEW_MODE` can be added to an application definition so that the person submitting the job can choose the type of mode to view the job results.



```
<ArgumentChoice>
  <ArgumentStringEnumerated>
    <Name>DM_CLIENT_VIEW_MODE</Name>
    <Description>Viewer mode</Description>
    <DisplayName>Viewer Mode</DisplayName>
    <InputRequired>false</InputRequired>
    <Option>Desktop</Option>
    <Option>HTML5</Option>
    <Option>Applet</Option>
    <Value>HTML5</Value>
  </ArgumentStringEnumerated>
</ArgumentChoice>
```

 **Note:** By default, the HTML5 view mode is enabled.

## Mandatory/Optional Application Converter File Changes

In the `app-conv-AppName` application definition file, the following section determines which jobs are displayed in Access Web.

```
<jsdl-hpcp:Environment name="DM_JOB">True</jsdl-hpcp:Environment>
```

If this is set to `False`, apart from the interactive application jobs, all the other jobs belonging to the user will be displayed. Ensure that this is set to `True`.

## 10.7.3 Add a New Interactive Application

Create a new interactive application definition by copying a default interactive application definition and making application specific changes.

Any time a new application is added to your HPC, a corresponding application definition needs to be written. Writing a specific interactive application definition is a bit more complex than writing simple application definitions. We recommend the following procedure of copying and modifying the GLXSpheres application definition which is available after installing the Remote Session components of Access Web.

1. Navigate to `PA_HOME/data/pas/targets/localhost/repository/applications/`
2. Copy the GlxSpheres application definition directory and rename it to the name of the new application.

If the new application is HyperView, then execute the following command:

```
cp -rp GlxSpheres HyperView
```

3. Rename the GlxSpheres application definition files to the name of the new application.

```
mv app-actions-GlxSpheres.xml app-actions-HyperView.xml
mv app-conv-GlxSpheres.xml app-conv-HyperView.xml
mv app-inp-GlxSpheres.xml app-inp-HyperView.xml
```

4. Edit the application input file.

- a) Change the value of the `<ApplicationId>` element to the name of the new application.

```
<ApplicationId>HyperView</ApplicationId>
```

- b) Change the value of the `<ApplicationName>` element to the new application name.

```
<ApplicationName>HyperView</ApplicationName>
```

- c) Locate the application argument `<ArgumentChoice>` called **VERSION**.

```
<ArgumentChoice>
  <ArgumentStringEnumerated>
    <Name>VERSION</Name>
    <Description>Version of the interactive application you
                  selected to start </Description>
    <DisplayName>Version</DisplayName>
    <xi:include href="site-config.xml" pointer="xpath1
                  (//Application[@id='GlxSpheres']/ApplicationVersions//Option)" />
    <ArgumentStringEnumerated>
  </ArgumentChoice>
```

- d) Change the attribute `@pointer` of the `<xi:include>` element to point to the path of the new application:

```
<xi:include href="site-config.xml" pointer="xpath1
          (//Application[@id='HyperView']/ApplicationVersions//Option)" />
```

**5. Edit the application action file.**

- a) Change the value of the `<ApplicationId>` element to the name of the new application.

```
<ApplicationId>HyperView</ApplicationId>
```

- b) Change the value of the `<ApplicationName>` element to the new application name.

```
<ApplicationName>HyperView</ApplicationName>
```

**6. Edit the application converter file.**

- a) Change the value of the `<ApplicationId>` element to the name of the new application.

```
<ApplicationId>HyperView</ApplicationId>
```

- b) Change the value of the `<ApplicationName>` element to the new application name.

```
<ApplicationName>HyperView</ApplicationName>
```

- c) Set the site specific required environment for the application.

You can set the `ALTAIR_LICENSE_PATH`, `NCPUS`, `ngpus`, `MEMORY` etc according to the requirements for the application.

```
<jSDL-hpcp:Environment name="ALTAIR_LICENSE_PATH">6200@licsrv</jSDLhpcp:Environment>
```

**7. Navigate to the directory** `PA_HOME/data/pas/targets/localhost/repository/`

**8. Edit the site-config.xml file.**

- a) Add a new `<Application>` element that points to the new application executable.

```
<Application id="HyperView">
  <ApplicationVersions>
    <ApplicationVersion>
      <Option>13.2</Option>
      <Executable>/altair/hw/13.2/altair/scripts/hv</Executable>
    </ApplicationVersion>
  </ApplicationVersions>
</Application>
```



**Tip:** You can also define multiple executable versions for the application.

```
<Application id="HyperView">
  <ApplicationVersions>
    <ApplicationVersion>
      <Option>13.1</Option>
      <Executable>/altair/hw/13.1/altair/scripts/hv</Executable>
    </ApplicationVersion>
  </ApplicationVersions>
</Application>
```

```
<ApplicationVersion>
  <Option>13.2</Option>
  <Executable>/altair/hw/13.2/altair/scripts/hv</Executable>
</ApplicationVersion>
</ApplicationVersions>
</Application>
```

9. Restart the Access Web for these changes to take effect by entering the following command:


```
service pbsworks-pa restart
```

The new application will be available in Access Web after restart.

Create roles and add users to these roles to grant and restrict access to the various features of Access Web.

This chapter covers the following:

- [11.1 Managing Roles](#) (p. 136)
- [11.2 Managing Users](#) (p. 139)

Access Web roles and privileges are defined by clicking  > **Access Management** located in the upper right-hand of the web page once you have logged into Access Web. This option is only displayed for the portal administrator.



**Note:** The first person to login to Access Web after installation is considered the portal administrator. The portal administrator is the only user who can add or delete service clusters and controls the user management.

## 11.1 Managing Roles

Add a role, change a role's privileges or delete a role.

### 11.1.1 Default Roles and Resources

Overview of the default Access Web roles.

#### Access Web Roles

By default, the first person to login to Access Web after installation is considered the portal administrator. The portal administrator is the only user who can add or delete service clusters and controls the access management.



**Note:** By default, the Access Web users have access to all applications.

#### Resources

By default, the following resource levels are available:



##### *Applications*

This privilege allows access to the applications and its respective profiles available in Access Web, allowing the user to manage the applications in the registered service cluster.

### 11.1.2 Add a New Role

Create a custom role for your site.

Review the [default roles and privileges](#) before adding a new role.

1. Click  > **Access Management**.
2. Click **Roles** from the menu located on the left-hand side of the web page.
3. Click **Add Roles**.  
A role is created with a default role name and application user privileges.
4. Click  located to the right of the name of the role.
  - a) For Role Name, enter a name that describes the role.
  - b) Click **Ok**.
5. Click **+** at the top next to the **Assigned Resources**.  
The **Available Resources** menu is displayed.
6. Choose the resources to give to this role by clicking the check-box located to the right of the resources.  
Resources are not mutually exclusive, so you may assign more than one.


7. Click **Ok** in the **Available Resources** menu.
8. Click **Save**.

The new role is displayed in the Roles list.

### 11.1.3 Change the Resources of a Role



Add or remove access resources for a role.

Review the [default roles and privileges](#) before adding a new role.

1. Click  > **Access Management**.
2. Click **Roles** from the menu located on the left-hand side of the web page.
3. Click the name of the role.  
The **Assigned Resources** menu is displayed.
4. Click **+** at the top next to the **Assigned Resources**.  
The **Available Resources** menu is displayed.
5. Enable the checkbox next to the Resource to assign the resource to the role.
6. Click **Ok** in the **Available Resources** menu.
7. Click **Save**.


### 11.1.4 Change the Name of a Role

Rename a role.

1. Click  > **Access Management**.
2. Click **Roles** from the menu located on the left-hand side of the web page.
3. Click the name of the role.
4. Click  located to the right of the name of the role.
  - a) For Role Name, enter a name that describes the role.
  - b) Click **Ok**.
5. Click **Save**.

### 11.1.5 Delete a Role

Delete a role that is no longer needed.

1. Click  > **Access Management**.
2. Click **Roles** from the menu located on the left-hand side of the web page.
3. Select a role by enabling the checkbox next to the role's name.




**Tip:** Select multiple roles so that they can be deleted in a single click.

4. Click .
5. Click **Ok**.


## 11.2 Managing Users

Add a user, assign or remove a role from a user, or delete a user.

 **Note:** User is auto populated on first time login to the access.


### 11.2.1 Add a User


Add a user so that the user can access the features of Access Web.

1. Click  > **Access Management**.
2. Click **Users** from the menu located on the left-hand side of the web page.
3. Click **Add User**.
  - a) For First Name, enter the first name of the user.
  - b) For Last Name, enter the last name of the user.
  - c) For User Name, enter the user's NIS/SSH username.
  - d) Click **Save**.

### 11.2.2 Assign a Role to a User

Assign a role to the user to establish user resources.

1. Click  > **Access Management**.
2. Click **Users** from the menu located on the left-hand side of the web page.
3. Select a user by enabling the checkbox next to the user's name.

 **Tip:** Select multiple users when you want to assign the same roles to multiple users.

4. Click **Assign Roles**.  
The **Available Roles** menu is displayed.
5. Enable the checkbox next to the Role Name to assign the role to the user.



 **Tip:** More than one role can be assigned to the user.

6. Click **OK**.

### 11.2.3 Remove a Role from a User


Remove a role from a user to limit access to certain features.



1. Click  > **Access Management**.
2. Click **Users** from the menu located on the left-hand side of the web page.
3. Click the name of the user.  
The roles assigned to the user is displayed.
4. Click  to delete the role.
5. **Save**.


## 11.2.4 Change the User Name

Change the first or last name of a user.

1. Click  > **Access Management**.
2. Click **Users** from the menu located on the left-hand side of the web page.
3. Click the name of the user.  
The roles assigned to the user is displayed.
4. Change the first or last name of the user.
5. Click **Save**.

## 11.2.5 Delete a User

Delete a user when the user no longer needs access to Access Web.

1. Click  > **Access Management**.
2. Click **Users** from the menu located on the left-hand side of the web page.
3. Select a user by enabling the checkbox next to the user's name.



**Tip:** Select multiple users so that they can be deleted in a single click.

4. Click .
5. Click **Ok**.

Information about the log files.

This chapter covers the following:

- [12.1 PAS Log File](#) (p. 142)
- [12.2 Other Log Files](#) (p. 143)

## 12.1 PAS Log File

The PAS log file, `pas-server.log`, contains a record of server activities and is useful for identifying issues and problems. The location of the log file for a typical installation of PAS is: `PA_HOME/logs/pas/`

## 12.2 Other Log Files

The PAS installation log file is located in: /opt/altair/pbsworks/pas/2019.1/\_PAS  
Services\_installation/Logs

The log files for the Apache Tomcat web server are located in: PBSWORKS\_EXEC/pas/bin/pas-server/  
logs

Troubleshooting Access Web, PAS, Results Visualization Service, and Remote Session.

This chapter covers the following:

- [13.1 Run the Access Web Diagnosis Script](#) (p. 145)
- [13.2 Troubleshoot PBS Application Services](#) (p. 146)
- [13.3 Troubleshoot Remote Session Components](#) (p. 151)
- [13.4 Troubleshoot Results Visualization Service](#) (p. 157)

The following section provides the troubleshooting information and steps for Access Web and its services.

## 13.1 Run the Access Web Diagnosis Script

Run the diagnosis script provided in Access Web to get information for troubleshooting Access Web.

The diagnosis script will create a zip file which can be shared with Altair support team for troubleshooting.

1. Login to the machine as root where you have installed Access Web and PBS Application Services.
2. Navigate to `PA_EXEC/init/`
3. Run the following command:

```
pa-diagnosis.py
```

A zip file will be created and stored at:

```
/tmp/pbsworks-pa-diagnosis_20181010161835.zip
```

## 13.2 Troubleshoot PBS Application Services

Troubleshooting information and steps for PAS.

The following section provides the information about troubleshooting information and steps for PAS.

### 13.2.1 Verify PAS Status

Monitor PAS using the status page.


A status page is available through the following URL to monitor the status of PAS: <https://HOSTNAME:5243/pas/pasStatus>

HOSTNAME is the hostname of the machine where the PAS Server is installed.

Green indicates that the system is functioning properly. Red indicates an issue that should be investigated.

PAS Status at time: 6:23:29 PM

JVM Platform OS Name (system property os.name)	Linux - OK
JVM Platform OS Version (system property os.version)	3.10.0-693.el7.x86_64 - OK
JVM Platform Architecture (system property os.arch)	amd64 - OK
JVM Data Model (system property sun.arch.data.model)	64 - OK
Java Version	1.8.0_92 - OK
Python	OK
Dependent shared objects	OK
Available heap memory in MB	186 MB - OK
Memory used by AIF server in MB	101 MB - OK
PAS_EXEC directory disk space.	OK
PAS_HOME directory disk space.	OK
PBS status	PBS server is Running - OK
PBS Version	18.2 - OK
PBS execution speed	OK

 **Note:** For the PBS execution speed, PAS retrieves the PBS version by executing `get_PBS_version.py` located in `PA_EXEC/pas/scripts`. If the response takes more than 5 seconds, the execution speed is considered slow and will be displayed in red.

## 13.2.2 Troubleshoot PAS Job Submission Issues

Troubleshoot PAS job submission issues by setting the logging level for specific functional areas and by submitting job script directly to PBS.

### PAS Job Submission Issues by Setting Logging Level

Troubleshooting PAS job submission issues by setting the logging level for specific functional areas.

To troubleshoot errors during job submission and job monitoring, relevant information must be collected:

- user inputs provided for the job submission
- submission environment
- status (success or failure) of all the dependency
- steps which happen during the job submission
- job submission attributes generated by PAS server for the workload manager (PBS)

Follow these steps to gather relevant data:

1. Check the PAS server log file `pas-server.log` located at `PA_HOME/logs/pas/` for errors.
2. Check the Tomcat `catalina.out` log file located at `PA_HOME/logs/pas/` for network or security errors.
3. Check the system logs.



**Note:** For advanced debugging, contact an Altair Application Engineer.

4. Navigate to `PA_HOME/config/pas/conf/`.
5. Update `server-log.xml` file to get detailed logging information about user inputs and to see how long it takes to execute a submission request with the following XML :

```
<category name=" com.altair.gw.aif.rest. RESTJobsPortImpl">
  <priority value="debug" />
</category>
```

6. Update `server-log.xml` file to get information about the process of creating PBS job attributes from user inputs and the application definition with the following XML :

```
<category name=" com.altair.gw.aif.rest.util.PASNextGenJobUtils">
  <priority value="debug" />
</category>
```

PAS supports multiple adapters to communicate with the workload manager.

7. If the SSH adapter is enabled for the communication with the PBS cluster, add the following XML to the `server-log.xml` file to troubleshoot job submission:

```
<category name=" com.altair.gw.aif.ssh.implementation. SSHImplementation">
  <priority value="debug" />
</category>
```

8. Restart Access Web by entering the following command:

```
service pbsworks-pa restart
```



If this troubleshooting steps do not provide enough information to debug the issue, then [submit a job script directly to PBS](#).

## PAS Job Submission Issues by Submitting Job Script

Debug the Job Submission issue by submitting the job script directly to PBS.

1. Enable debug mode for the PAS Server by editing the file `PA_HOME/config/pas/conf/server.conf`

2. Set `DEBUG` to `true`.

```
DEBUG=TRUE
```

3. Restart Access Web by entering the following command:


```
service pbsworks-pa restart
```

The PAS Server will save the job script to a file in `PA_HOME/data/pas/system/temp`

4. Use the job script file to submit a job directly to PBS Professional.
5. Enable debug logging in the PAS job script `PA_EXEC/pas/scripts/job.py` by setting `DEBUG` to `true`.

```
DEBUG=TRUE
```

This provides information about the job process arguments and the job environment at the moment of job execution. This information is available in the job output file.

 **Note:** To gather debugging information for other functional areas of PAS, see [Configuring PAS Server Logging Behavior](#).

### 13.2.3 Troubleshoot Error Messages during Installation

Error messages, explanation, and a resolution for the error that may occur during the installation of PAS.

#### Stage Directory is Blank

##### Condition

During the installation of PAS, I get a Staging Directory is blank warning message.

##### Cause

Staging Directory path is not provided during installation.

##### Remedy

The staging directory is where the necessary files are transferred after job submission, but prior to the portal submitting the job to PAS for transfer to PBS Professional for execution. This staging directory

must exist for the installation to complete successfully. Please enter a pathname to an existing directory which will be designated as the PAS staging directory.

## PAS Service was unable to start

### Condition

During the installation of PAS, I get a PAS Service was unable to start error message.

### Cause

This may be due to port required by PAS is unavailable or busy.

### Remedy

An error occurred while starting PAS. Review the PAS log file for errors and contact system support.

## PAS Log File Contains OutOfMemory Errors

### Condition

There are `OutOfMemoryErrors` in the PAS Server log.

### Cause

This may be due to Heap Memory size occupied is more than configured memory size.

### Remedy

You may need to adjust the Java Virtual Machine (JVM) heap size of PAS. Refer [Configuring JVM Performance](#) for more information. Out of memory errors can indicate a underlying problem, therefore it is recommended to report these errors to PAS system support.

## Job Submission Fails with the Error: Bad UID for Job Execution

### Condition

Our site has installed PAS on a separate machine from the one hosting the PBS Professional Server. When a user submits a job, the job fails with a "Bad UID for job execution" exception.

### Cause

This can be due to multiple reasons like the user is root or `flatuid` is not set.

### Remedy

The PBS Professional `flatuid` attribute must be set to `True`. This attribute specifies whether, for each user, the username at the submission host must be the same as the one at the Server host. The username at the Server host must always be the same as the username at the execution host. When

*flatuid* is set to `True`, the Server assumes that `UserA@host1` is the same as `UserA@host2`. Therefore, if *flatuid* is `True`, `UserA@host2` can operate on `UserA@host1`'s job. Follow these steps to set *flatuid* to `True`:

1. Log into the machine hosting the PBS Professional Server.
2. At the command line, enter the command:  

```
print server
```
3. If the attribute *flatuid* is equal to `False` or is not set (you do not see it in the output from the `print server` command), then set the value to `True` by issuing the command:  

```
set server flatuid = True
```

## Job Submission Fails with the Error: Unknown Resource Resource\_List.<resource>

### Condition

Our site has installed PAS on a separate machine from the one hosting the PBS Professional Server. When a user submits a job, the job fails with a "Unknown resource Resource\_List.xxxxxx" exception.

### Cause

The resource needed for running jobs are not configured in PBS Professional.

### Remedy

Resources required by PAS have not been defined to PBS Professional. Add the required PAS resources to the PBS Professional resource definition file. For more information see [Configuring PBS Resources](#).

## New Features of PBS Professional are not working after Installation

### Condition

I have upgraded PBS Professional to the newest version and now the new features are not working.

### Cause

Whenever PAS starts, it reads PBS configuration and artifacts and keeps into the memory. So after PBS Professional is reinstalled, the new configuration and artifacts will not be available.

### Remedy

After installing a new version of PBS Professional, you must restart the PBS Professional and then restart Access Web.

## 13.3 Troubleshoot Remote Session Components

Troubleshooting information and steps for Remote Session components.

On completing the installation the services relevant to Remote Session should be up and running. This quick troubleshooting checklist assumes services like, dmagent, application services, PBS Professional, and PAS are running and configured.

The following section provides the information about troubleshooting information and steps for Remote Session components.

### 13.3.1 Run the Remote Session Diagnosis Script

Run the diagnosis script provided in Access Web to get information for troubleshooting Remote Session.

Run diagnosis script on PBS Mom, PBS Professional, PAS and Access Web machine as root and share the output with support team.

1. Login to the machine as root where you have installed Access Web.
2. Enter the command:

```
python <PA_EXEC>/displaymanager/scripts/remotesession-diagnosis.py
```

The following is an example of the command output that is displayed:

```
single_machine_installation
- guacd
- Guacd is installed - YES
- Guacd is running - YES
- Guacd configuration
- bind_host = blrvm9vm14
- bind_port = 4822
- pbsaccess
- PBSAccess is installed - YES
- PBSAccess is running - YES
- Gucad hostname matched - YES
- Gucad port matched - YES
- PBSPro
- PBSPro is installed - YES
- PBSPro is running - YES
- PBSPro iworkq configured: YES
- PAS
  - PAS is installed - YES
  - PAS is running - YES
  - Interactive Appdef XML:
    - output: Gedit, HVP, HyperMath, HyperMesh, HyperView, HyperWorks, RFJD
  - Interactive Appdef JSON:
    - output: Gedit, HVP, HyperMath, HyperMesh, HyperView, HyperWorks, RFJD
- execution_node
  - RemoteSession agent: TurboVNC is installed - YES
  - RemoteSession agent: VirtualGL is installed - YES
  - RemoteSession agent: GPU hardware is configured: YES
    - output: OpenGL version string: 2.1 Mesa 17.0.1
  - RemoteSession agent: Direct Rendering: YES
    - output: 300 GLXFBConfigs:
visual  x  bf lv rg d st  colorbuffer  ax dp st accumbuffer  ms  cav  drw
```

id	dep	cl	sp	sz	l	ci	b	ro	r	g	b	a	F	bf	th	cl	r	g	b	a	ns	b	eat	typ	
0x05c	24	tc	0	32	0	r	.	.	8	8	8	8	.	0	0	0	0	0	0	0	0	0	0	None	PXW
0x05d	24	tc	0	32	0	r	.	.	8	8	8	8	.	0	0	0	16	16	16	16	0	0	Slow	PXW	
0x05e	24	tc	0	32	0	r	y	.	8	8	8	8	.	0	0	0	0	0	0	0	0	0	0	None	PXW
0x05f	24	tc	0	32	0	r	y	.	8	8	8	8	.	0	0	0	16	16	16	16	0	0	Slow	PXW	
0x060	24	tc	0	32	0	r	y	.	8	8	8	8	.	0	0	0	0	0	0	0	0	0	0	None	PXW
0x061	24	tc	0	32	0	r	y	.	8	8	8	8	.	0	0	0	16	16	16	16	0	0	Slow	PXW	
0x062	24	tc	0	32	0	r	.	.	8	8	8	8	.	0	16	0	0	0	0	0	0	0	0	None	PXW

- Desktop Manager Environment installed:

- output: gnome-classic.desktop, gnome-custom-session.desktop, gnome.desktop

## 13.3.2 Remote Session Checklist

Checklist for Remote Session components and steps to verify the various components required to run remote session.

Following are the prerequisites for remote session:

- The execution node should be set up to run VNC server
- X server must be configured and running
- Access to X server must be granted for the user. The Remote Session Agent Installer will do this during installation.
- VirtualGL configured and functional

Checklist for the Execution node (or Graphics node):

1. Make sure that all the Remote Session components are able to communicate with each other through hostname.
2. Run the following command to verify if VNC server is set:

```
/opt/TurboVNC/bin/vncserver -noauth
```

- a) Connect using any VNC client to the VNC server:

```
$host:$vncwebport (e.g. v01: 1),
```

- b) Replace `v01` with the VNC server hostname and `:1` with the display number of the VNC server.

If you don't see the virtual desktop, please forward the `~/.vnc` folder to the Altair support team for further investigation.

3. Verify if X server is running for display `:0` (usually with process name `Xorg` or `X`).
4. If X server is not running, then reconfigure X server with:

```
/usr/bin/nvidia-xconfig --use-display- device=NONE --enable-all-gpus --keyboard=us
```

This will overwrite existing configurations and configure the X server with all available GPUs.

5. Verify if X server access is provided to the user by using the following command in a terminal window in the remote desktop session created in Step 2:

```
/opt/VirtualGL/bin/glxinfo -display :0 -c
```

The command should output a list of visuals and complete with no errors.

6. To verify graphics driver support VirtualGL, run the following command:

```
/opt/VirtualGL/bin/glxinfo -display :0 -c
```

OpenGL renderer string: "should state vendor driver version here"

The output should provide visuals with the following:

```
GLX_NV_multisample_coverage, GLX_NV_robustness_video_memory_purge,  
GLX_NV_swap_group, GLX_NV_video_capture, GLX_SGIX_fbconfig,  
GLX_SGIX_pbuffer, GLX_SGI_swap_control, GLX_SGI_video_sync  
OpenGL vendor string: NVIDIA Corporation  
OpenGL renderer string: Quadro 4000/PCIe/SSE2
```

7. Verify if VirtualGL is configured and functional by running the following command in a terminal window in the remote desktop session created in Step 2:

```
/opt/VirtualGL/bin/vgldr -d :0.0 -sp /opt/VirtualGL/bin/glxspheres64
```

If GLXSpheres starts, then VirtualGL is properly configured.



**Note:** If GLXSpheres does not start, then a detailed investigation is required by the support team.

8. Check for errors of the remote session application definition in the PAS logs.
9. Verify that the pbs\_mom logs do not report any error related to the remote session jobs associated with the remote sessions. For example, errors related to file transfers.
10. Verify that PBS Professional jobs submitted as remote session ends up running on the expected host(s) without errors.  
For example, when debugging problems related to the execution host dmhost1, verify that a job like:

```
qsub -l select=1:ncpus=1:mem=8gb:ngpus=1:host=dmhost1 -Wsandbox=PRIVATE -I
```

is correctly running and does not generate any errors in any PBS Professional logs, most importantly in the related pbs\_mom logs. Tune the resource requests to match the actual ones remote session uses when generating this jobs. PBS Professional job history will help identify the correct values:

```
qstat -fx <jid of failed dm job>
```

### 13.3.3 Display Session is shown but not the Application that was Started

#### Condition

After starting an application, you might notice that the display session was shown but not the application.

#### Cause

Generally, this happens when the user doesn't have access to the 3D X server.

#### Remedy

Administrator

1. Change the role from Administrator to the User and verify if the user has access to the 3D X server by running the following command in a terminal:

```
xdpyinfo -display :0" or "/opt/VirtualGL/bin/glxdpyinfo - display :0 -c
```

If the user does not have the permission to access the 3D X Server, then the following message is displayed:

```
"unable to open display :0"
```

2. Follow the steps provided in [http://www.virtualgl.org/vgldoc/2\\_2\\_1/#hd005001](http://www.virtualgl.org/vgldoc/2_2_1/#hd005001) to configure VGL to work with X Server
3. Verify whether X Server is configured to export True Color (24 bit or 32 bit) visuals. To configure X server for nVidia devices, use the following command:  

```
"/usr/bin/nvidia-xconfig --use-display-device=NONE --enable-all-gpus --key-board=us"
```
4. Choose one of the following options:
  - Perform Step 1 to verify if the user has access to the 3D X server
  - Create a new session from Access Web to check if the session is working fine

## 13.3.4 Application Definition working in VirtualGL Environment Issue

### Condition

Only sutain application is having issue running and other applications are working fine.

### Cause

Application having issues working in VirtualGL environment.

### Remedy

Please check with application provider if application works in VirtualGL environment.

## 13.3.5 Desktop Manager not Displaying

### Condition

Remote application is showing but not the desktop.

### Cause

The possible reasons are:

- Desktop Manager is not installed or configured in application definition
- Not using the GPU hardware for OpenGL call

### Remedy

1. Check the `runtime/xstartup.turbovnc` file available inside application definition for configured Desktop Manager.
2. Check if configured Desktop Manager is installed on all the Interactive MOM and executable is correct.
3. Check the [Graphic Card Compatibility Issues](#).
4. In Job running directory check for the `xvnc.log` to check for any error.
5. Try with other Desktop Manager by installing on Interactive MOM and configuring it on `xstartup.turbovnc` in application definition.

## 13.3.6 Graphic Card Compatibility Issues

### Condition

Remote Session Application is not consuming GPU resource.

### Cause

Not using the proper drivers for the graphic card.



**Note:** Use the drivers provided by the manufacturer of the graphic card. If the manufacturer of your 3D adapter provides proprietary drivers for Linux, then it is recommended that you install these.

### Remedy

Administrator

Run the following command and inspect the output:

```
/opt/VirtualGL/bin/glxinfo -display :0 -c
```

For example: if you run the following command:

```
[root@dmsystem-linux ~]# /opt/VirtualGL/bin/glxinfo -display :0 -c
```

The output of the command is displayed as follows:

```
GLX_ARB_context_flush_control, GLX_ARB_create_context,
GLX_ARB_create_context_profile, GLX_ARB_create_context_robustness,
GLX_ARB_fbconfig_float, GLX_ARB_get_proc_address, GLX_ARB_multisample,
GLX_EXT_buffer_age, GLX_EXT_create_context_es2_profile,
GLX_EXT_create_context_es_profile, GLX_EXT_framebuffer_sRGB,
GLX_EXT_import_context, GLX_EXT_stereo_tree, GLX_EXT_swap_control,
GLX_EXT_swap_control_tear, GLX_EXT_texture_from_pixmap,
GLX_EXT_visual_info, GLX_EXT_visual_rating, GLX_NV_copy_buffer,
GLX_NV_copy_image, GLX_NV_delay_before_swap, GLX_NV_float_buffer,
GLX_NV_multisample_coverage, GLX_NV_robustness_video_memory_purge,
GLX_NV_swap_group, GLX_NV_video_capture, GLX_SGIX_fbconfig,
GLX_SGIX_fbconfig, GLX_SGIX_swap_control, GLX_SGIX_video_sync
OpenGL vendor string: NVIDIA Corporation
OpenGL renderer string: Quadro 4000/PCIe/SSE2
OpenGL core profile version string: 4.3.0 NVIDIA 375.82
OpenGL core profile shading language version string: 4.30 NVIDIA via Cg compiler
OpenGL core profile extensions:
GL_AMD_multi_draw_indirect, GL_ARB_ES2_compatibility,
GL_ARB_ES3_1_compatibility, GL_ARB_ES3_2_compatibility,
GL_ARB_ES3_compatibility, GL_ARB_arrays_of_arrays, GL_ARB_base_instance,
GL_ARB_blend_func_extended, GL_ARB_buffer_storage, GL_ARB_cl_event,
```



```

name of display: :0
display: :0 screen: 0
direct rendering: Yes
server glx vendor string: NVIDIA Corporation
server glx version string: 1.4
server glx extensions:
    GLX_ARB_context_flush_control, GLX_ARB_create_context,
    GLX_ARB_create_context_profile, GLX_ARB_create_context_robustness,
    GLX_ARB_fbconfig_float, GLX_ARB_multisample, GLX_EXT_buffer_age,
    GLX_EXT_create_context_es2_profile, GLX_EXT_create_context_es_profile,
    GLX_EXT_framebuffer_sRGB, GLX_EXT_import_context, GLX_EXT_libglvnd,
    GLX_EXT_stereo_tree, GLX_EXT_swap_control, GLX_EXT_swap_control_tear,
    GLX_EXT_texture_from_pixmap, GLX_EXT_visual_info, GLX_EXT_visual_rating,
    GLX_NV_copy_buffer, GLX_NV_copy_image, GLX_NV_delay_before_swap,

359 GLXFBConfigs:
  visual  x  bf lv rg d st colorbuffer ax dp st accumbuffer ms cav  drw
  id dep cl sp sz l  ci b ro  r  g  b  a  F bf th cl  r  g  b  a  ns b eat  typ
-----
0x135 24  tc  0  24  0 r y .  8  8  8  0 .  4  24  8 16 16 16 16  0  0 None PXW
0x136 24  dc  0  24  0 r y .  8  8  8  0 .  4  24  8 16 16 16 16  0  0 None PXW
0x137 24  tc  0  32  0 r y .  8  8  8  8 .  4  24  8 16 16 16 16  0  0 None PXW
0x138 24  dc  0  32  0 r y .  8  8  8  8 .  4  24  8 16 16 16 16  0  0 None PXW
0x139 24  tc  0  24  0 r . .  8  8  8  0 .  4  24  8 16 16 16 16  0  0 None PXW
0x13a 24  dc  0  24  0 r . .  8  8  8  0 .  4  24  8 16 16 16 16  0  0 None PXW
0x13b 24  tc  0  32  0 r . .  8  8  8  8 .  4  24  8 16 16 16 16  0  0 None PXW
0x13c 24  dc  0  32  0 r . .  8  8  8  8 .  4  24  8 16 16 16 16  0  0 None PXW
0x13d 24  tc  0  24  0 r y .  8  8  8  0 .  4  24  0 16 16 16 16  0  0 None PXW
0x13e 24  dc  0  24  0 r y .  8  8  8  0 .  4  24  0 16 16 16 16  0  0 None PXW
0x13f 24  tc  0  32  0 r y .  8  8  8  8 .  4  24  0 16 16 16 16  0  0 None PXW
0x140 24  dc  0  32  0 r y .  8  8  8  8 .  4  24  0 16 16 16 16  0  0 None PXW
0x141 24  tc  0  24  0 r . .  8  8  8  0 .  4  24  0 16 16 16 16  0  0 None PXW

```

Figure 20: Graphic Card Command Output

Check the following information in the output:

- Look at the OpenGL renderer string and make sure it doesn't contain any variant of mesa or software
- Direct Rendering is Yes
- Look for visuals with a class of tc, a buffer size of 24 or 32, a caveat of None, and have a P in the right-most column

## 13.4 Troubleshoot Results Visualization Service

Troubleshooting information and steps for RVS.

The following section provides the information about troubleshooting information and steps for RVS.

### 13.4.1 Troubleshoot Checklist

A quick checklist of pre-requisites for RVS.

1. The RVS server should be installed on a supported operating system and web browsers to visualize the result files. For more information refer [System Requirements for Access Web](#).



**Note:** Turn off pop-up blockers to view auto-refresh loading message for all the supported web browsers.

2. For Linux OS, ensure HyperMath is working fine before running RVS.
  - a) Verify if the shared library is accessible by running HMathserv at: `/opt/2017.2/altair/scriptsh/hmath`
  - b) Install "libXScrnSaver-1.2.2-6.1.el7.x86\_64" package to resolve the shared library error: "error while loading shared libraries:libXss.so.1".
3. HyperWorks installation should be accessible to the portal user.
4. The portal user should have read access to results files.
5. Before accessing RVS, ensure the older version of HMath session is killed.
  - a) To get the HMath session process ids, use the command:

```
ps -ef | grep hmathserv
```

Specify the process id of HMathserv in the following command, "kill -9 <process id>"
  - b) To kill the HMath session, use the command:

```
kill -9 <process id>
```

### 13.4.2 Locate Log Files

The file path details to locate RVS core logs, web server logs, and integration logs are listed.

Locating RVS log files locations:

- a) RVS core logs: `PA_HOME/logs/resultservice/resultservicelog/resultservice.log`
- b) RVS web server logs: `PA_HOME/logs/resultservice/catalina.out`
- c) RVS integration logs: `PA_HOME/logs/resultmanager/resulmanager.log`

## 13.4.3 Common Issues

This section provides list of common issues occurs in RVS. The causes and the resolution steps are provided to resolve these common issues.

### Unable to Use Results Visualization Service Features

Unable to view or perform any of the RVS options.

Review the following checks to enable RVS features.

- The supported RVS result file types, refer [Supported Result File Types](#)
- For RVS Troubleshooting Checklist, refer [Troubleshoot Checklist](#)

The causes could be:

- The selected result file format is unsupported.
- RVS service has not started.

Follow the given steps:

1. Check if RVS is running using the command:  

```
ps -ef | grep resultservice
```
2. If RVS service is running, check for the errors in the RVS core logs at `PA_HOME/logs/resultservice/resultservicelog/resultservice.log`.
3. If the RVS service is not running, check for the error messages in the following path: `PA_HOME/logs/resultservice/catalina.out`.
4. Initiate the RVS service by restarting the Access Web using the command:  

```
service pbsworks-pa restart
```
5. Use the following link: `url:Access Weburl:4443/resultservice/rest/doc` to check if the RVS port page is accessible.

### HyperMath and HVTrans License Errors

Unable to post process the result files due to HyperMath and HVTrans license errors.

Update the Altair license path in the `setenv.sh` file. Refer, [Configure HyperWorks Licenses](#).

The causes could be:

- HWHyperMath and HWHyperViewTrans licenses are not available in the HyperWorkslicense server.
- Due to shortage of licenses.
- The License Server is not reachable.

Follow the given steps:

1. Navigate to RVS license configuration location at `PA_EXEC/resultservice/scripts/setenv.sh`
2. Verify if the provided license server is reachable.
3. Verify the HWHyperMath and HWHyperViewTrans licenses are valid and available.
4. You can verify the availability of licenses in the Altair Utility.

5. To check the old instance of HMath sessions, use the command:

```
ps -ef | grep hmathserv
```

Specify the `process id` of HMathserv in the following command, "`kill -9 <process id>`"

6. To kill any running or older HMath sessions, use the command:

```
kill -9 <process id>
```

## Unable to Extract TOC of a Result File

RVS is unable to post process the output files.

Perform the checks listed in the [Troubleshoot Checklist](#)

The causes could be:

- Insufficient permissions to read the result file.
- HyperWorks is not installed properly.
- May be an issue with the shared library.

Follow the given step:

If the registered user does not have read permission to open the result file update the user's permissions to read the result files.

## HyperMath Execution Error: HW\_APP\_FAILED Message

HyperMath service is not running or does not have the permissions to execute.

Perform the checks listed in the [Troubleshoot Checklist](#).

Follow the given step:

Check if the HWHyperMath service has started successfully, using the command:

```
ps -ef | grep hmathserv
```

The following entries shows the HWHyperMath is running successfully.

```
pbsworks 7226 1 0 Sep26 ? 00:00:00 /bin/sh /opt/hw2017.2/altair/scripts/hmathserv -port 5678
pbsworks 7227 7226 0 Sep26 ? 00:00:05 /opt/hw2017.2/altair/hwx/bin/linux64/hmathserv -port 5678
```

## Result File Reader is Unrecognized

The error, HW File Error: File not recognized displays when you try to plot or animation.

- To check the supported result file list, refer [Supported Result File Types](#).
- To configure a solver file reader, refer [Configure Solver File Readers](#)

The error occurs if a result solver file reader is not registered in HyperWorks.

The causes could be:

- The result file reader is not configured in HyperWorks.

Follow the given steps:

1. Verify if your result file reader is configured.

For the Fluent file reader, the entry should be as following:

```
*RegisterExternalReader({external_readers_dir + "/hgfluent.exe"}, "", "", ascii)
```

2. If not configured, then you need to configure the solver file reader.

## HML Script Execution Failed

This error occurs due to Hyperworks license are not configured properly.

- For RVS Troubleshooting Checklist, refer [Troubleshoot Checklist](#).

Follow the steps given here:

1. Resolve any HyperWorks license related issues, verify the license file at HyperWorks at `PA_EXEC/resulttservice/scripts/setenv.sh`
2. If the error still persist, run through the RVS troubleshooting checklist.